

Low-VOC TPO Spray Adhesive



EverGuard® TPO **QuickSpray** Adhesive LV50



Description:

EverGuard® TPO Quick Spray Adhesive LV50 is a low-VOC sprayable, solvent-based contact adhesive useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

Features and Benefits:

- Faster installation than traditional bonding adhesive
- High initial tack
- 2 year shelf life from the date of manufacture

Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- For TPO Membrane, spraying from 8"- 12" (203 - 305 mm) away, apply adhesive uniformly to both the substrate and the underside of the membrane
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply at an ambient temperature of 20°F (-6.7°C) and above. The cylinders must be kept above 50°F (10°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C).
- Apply pressure with a push broom and weighted roller to ensure complete bonding
- To clean Hose & Gun Kit, attach hose and gun to EverGuard® Quick Spray LV50 Cleaning Kit and run cleaner through hose and gun for approximately 10-15 seconds. Each cleaner canister should get approximately 9-10 cleanings for the 10 square size.
- If used as a primer for SA Vapor Retarder, apply to the substrate only

Product Details:

- Item Numbers:
SKU **7807** - 3 Square - GW 16 lb. (7.3 kg)
SKU **7801** - 10 Square - GW 40 lb. (18.1 kg)
- VOC: <90 g/L
- Installation Temperature: 20°F (-6.7°C) and rising
- Cleaner SKU: **7803**
- Hose & Gun SKU: **7804** or **7805**
Hose Splitter (for large canisters) - **7826**
25' (7.6 m)Hose (for large canisters) - **7825**

Codes & Compliance:

▪ UL Classified ¹	
▪ FM Approved ²	
▪ State of Florida Approved	

¹ Refer to UL Online Certification Directory for actual assemblies.

² Refer to www.RoofNav.com for actual assemblies.

Note: Coverage area assumes application in accordance with GAF instructions.



Visit gaf.com

For additional information, contact GAF Technical Support at **1-877-423-7663** or designservices@gaf.com

We protect what matters most™

