

EverGuard® TPO QuickSpray Adhesive



Description:

EverGuard® TPO Quick Spray Adhesive and EverGuard® TPO Quick Spray Adhesive LV50 are sprayable, solvent-based contact adhesives useful for bonding smooth EverGuard® and EverGuard Extreme® TPO membranes to various substrates.

Features and Benefits:

- Up to 10 squares (93 square meters) of installed membrane per canister
- Faster installation than traditional bonding adhesive
- High initial tack

Application:

- Substrate should be dry, clean, and free from oil, grease, and other contaminants
- Spraying from 8"– 12" (203–305 mm) away, apply adhesive uniformly to both the substrate and the underside of the membrane
- Allow adhesive to dry to a tacky feel before bonding membrane to substrate
- Apply at an ambient temperature of 20°F (-6.7°C) and above. The cylinders must be kept above 50°F (10°C) for the product to spray properly. Utilize power-heated blankets and hot boxes when necessary. Ensure that cylinder temperatures stay below 150°F (65.6°C).
- Apply pressure with a push broom or weighted roller to ensure complete bonding.
- To clean Hose & Gun Kit, attach hose and gun to EverGuard® Quick Spray or EverGuard® Quick Spray LV50 Cleaning kit and run cleaner through hose and gun for approximately 10–15 seconds. Each cleaner canister should get approximately 9–10 cleanings.

Product Details:

EverGuard® TPO Quick Spray Adhesive

- Item Numbers: 7792 - 40.15 lb. Canister (18.2 kg), 7806 - 9 lb. Canister
- VOC: 489 g/L
- Shelf Life: 1 year
- Installation Temperature: 20°F (-6.7°C) and rising
- Cleaner SKU: 7802
- Hose & Gun SKU: 7804 or 7805

EverGuard® TPO Quick Spray Adhesive LV50

- Item Numbers: 7801 - 36.3 lb. Canister (16.5 kg), 7807 - 9 lb. Canister
- VOC: <90 g/L
- Shelf Life: 1 year
- Installation Temperature: 20°F (-6.7°C) and rising
- Cleaner SKU: 7803
- Hose & Gun SKU: 7804 or 7805

Codes & Compliance:




Refer to UL Online Certification Directory for actual assemblies.



State of Florida Approved

For additional information, contact GAF Technical Support at 1-800-766-3411 or technicalquestions@gaf.com

**Coverage rates and flash time may vary in colder temperatures.*



Visit [gaf.com](https://www.gaf.com)

We protect what matters most™

