



Description:

EverGuard® TPO Yellow Safety
Tape helps make a roof safer for
everyone who needs to access it.
It provides a highly visible warning
to take caution around a variety
of potential hazards:

- Edges
- Skylights
- Expansion joints
- Solar panels
- Other rooftop features

EverGuard® TPO Yellow Safety Tape is easy to install and lasts for years while requiring less maintenance than many paint coatings that perform the same function.

Application:

Clean the entire surface to be covered with soap and water, and dry thoroughly. Wipe the area to be primed with a white cloth moistened with of EverGuard® TPO Seam Cleaner. Apply EverGuard® TPO Primer on surfaces matina with the butyl tape — only on the surfaces receiving the tape. After the primer has dried, pull a portion of the release paper on the back of the tape, exposing the butyl adhesive, and mate the two surfaces. Roll the tape portion of the cover strip at a 45-degree angle to ensure a good bond.*

SPECIFICATIONS Width 6" (152 mm) Length 100' (30.48 m) SHIPPING SPECIFICATIONS Qty per box 2 Weight per box 38 lb. / 17.24 kg Boxes per pallet 36 PRODUCT SKU TPO Yellow Safety Tape 755F902

Product Information:

EverGuard® TPO Yellow Safety Tape is a 6"- (152 mm) wide by 100'- (30.48 m) long cover tape made from nominal 30 mil unreinforced TPO. It can be used in conjunction with EverGuard® Yellow Walkway Rolls.

Also Available:





Visit gaf.com

^{*} See EverGuard® Application and Specifications Manual for detailed application instructions and additional information on Yellow Safety Tape and Cover Tape.