



**NOTE:**

1. ADD BALLAST PER SPEC FOR BALLASTED SYSTEMS.
2. FOR SELF-ADHERED RAPIDSEAM™ SYSTEMS, UP TO 10-YR. MAXIMUM GUARANTEE ONLY.
3. FOR SELF-ADHERED HEAT-WELDED SYSTEMS, UP TO 15-YR. MAXIMUM GUARANTEE ONLY.
4. FIELD-FABRICATED EXPANSION JOINT SHOULD NOT BE FLEECE-BACK OR SELF-ADHERING MEMBRANE. USE STANDARD EVERGUARD® MEMBRANE.
5. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



www.gaf.com  
1 Campus Drive,  
Parsippany, NJ 07054

**EverGuard**  
SINGLE-PLY ROOFING SYSTEMS  
EXPANSION JOINT  
SERIES

DRAWING #

**403B**

SCALE  
N.T.S.

**FIELD FABRICATED WALL EXPANSION  
JOINT DETAIL - FLAT TYPE**

**THIS DETAIL APPLIES TO:**  
Adhered Systems  
Ballasted Systems  
Mechanically Attached Systems  
Self-Adhered Systems  
TriPosite Systems

REVISION DATE  
**5-1-15**