



NOTE:

1. FLEXSEAL™ CAULK GRADE SEALANT IS TO BE ADDED TO ALL TERMINATION BAR EDGES, OPEN HOLES, AND DRILL-TEC™ FASTENER HEADS.
2. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICAL SYSTEMS ONLY.
3. IF EVERGUARD® FREEDOM™ MEMBRANE IS USED, BONDING ADHESIVE IS NOT NEEDED AND WALL MUST BE PRIMED.
4. FOR SELF-ADHERED RAPIDSEAM™ TECHNOLOGY SYSTEMS, SEE EVERGUARD® DETAIL 330 FOR LAP APPLICATION.
5. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO DETAIL EVERGUARD® 115).



www.gaf.com
1 Campus Drive,
Parsippany, NJ 07054



DRAWING #
313

SCALE
N.T.S.

**WALL EDGE FLASHING WITH
TERMINATION BAR DETAIL**

THIS DETAIL APPLIES TO:
Adhered Systems
Ballasted Systems
Mechanically Attached Systems
Self-Adhered Systems

REVISION DATE
6-20-16