



NOTE:

1. T-JOINT PATCH REQUIRED FOR 60, 70 & 80 MIL TPO AND 80 MIL PVC, REFER TO EVERGUARD® DETAIL 105.
2. FOR HEAT-WELDING LAPS USE 1" MAX (25.4 mm) WELD WITH AUTOMATIC MACHINE WELDER AND 2" WELD WITH HAND WELDER.
3. FOR SELF-ADHERED HEAT-WELDED SYSTEMS, UP TO 15-YR. MAXIMUM GUARANTEE ONLY.
4. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



EverGuard
SINGLE-PLY ROOFING SYSTEMS
FIELD OF ROOF
SERIES

DRAWING #
104A

END LAP DETAIL

THIS DETAIL APPLIES TO:

- Adhered Systems
- Ballasted Systems
- TriPosite Systems
- Mechanically Attached Systems

www.gaf.com
1 Campus Drive,
Parsippany, NJ 07054

SCALE
N.T.S.

FOR 45 MIL TPO AND 50 & 60 MIL PVC MEMBRANE ONLY

REVISION DATE
6-22-15