



APPLY SECOND T-JOINT COVER PATCH OVER ADJACENT HEAT-WELDED LAP

TRIM EDGE OF OVERLYING SHEET FOR EASY INSTALL OF T-JOINT (NOT REQUIRED)

**NOTE:**

1. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICAL SYSTEMS ONLY.
2. T-JOINT IS TO BE USED FOR 60, 70 & 80 MIL TPO AND 80 MIL PVC ONLY.
3. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



**EverGuard**  
SINGLE-PLY ROOFING SYSTEMS  
FIELD OF ROOF SERIES

DRAWING #  
**105A**  
SCALE  
N.T.S.

**T-JOINT COVER PATCH DETAIL**  
FOR 60 THRU 80 MIL TPO AND 80 MIL PVC MEMBRANES ONLY

THIS DETAIL APPLIES TO:  
Adhered Systems  
Ballasted Systems  
RhinoBond Systems  
Mechanically Attached Systems  
TriPosite Systems  
REVISION DATE  
**6-6-16**