



NOTE:

1. FOR INSULATION THICKNESS GREATER THAN 8" (203 mm), A HARD BOARD IS REQUIRED ON MECHANICALLY FASTENED SYSTEMS ONLY.
2. REFER TO EVERGUARD® DETAIL 204 FOR COATED METAL JOINTS.
3. A CONTINUOUS METAL CLEAT IS REQUIRED.
4. FOR SELF-ADHERED RAPIDSEAM™ TECHNOLOGY SYSTEMS, SEE EVERGUARD® DETAIL 330 FOR LAP APPLICATION.
5. 25-YEAR GUARANTEES AND ABOVE MUST USE EXTREME ACCESSORIES.
6. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO EVERGUARD® DETAIL 115).



EverGuard
SINGLE-PLY ROOFING SYSTEMS
ROOF EDGE SERIES

DRAWING #

211

**GUTTER WITH COATED METAL EDGE
DETAIL**

THIS DETAIL APPLIES TO:

- Adhered Systems
- Self-Adhered Systems
- TriPosite Systems
- Mechanically Attached Systems

www.gaf.com
1 Campus Drive,
 Parsippany, NJ 07054

SCALE
N.T.S.

REVISION DATE
6-20-16