

# Low-VOC California Compliant Single-Ply Components

| Primer   | Product image   | Description   |
|--|---|---|
| <p><b>EverGuard® TPO Low VOC Primer</b><br/>VOC &lt; 240 g/l</p>             |    | <p>A primer designed for use with EverGuard® TPO membrane and EverGuard® Freedom™ self-adhered TPO products.</p> <p>Container size - 1 gallon (6 containers per box)</p>  |
| Adhesives  | Product image   | Description   |
| <p><b>EverGuard® TPO Low VOC Bonding Adhesive</b><br/>VOC &lt; 250 g/l</p>   |    | <p>EverGuard® TPO Low VOC Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding smooth back TPO single-ply roofing membranes and flashings to various roofing substrates.</p> <p>Up to 6 sq./5-gallon (18.9 liter) of installed membrane per container</p> |
| <p><b>EverGuard® TPO Quick Spray Adhesive - LV50</b><br/>VOC &lt; 80 g/l</p> |   | <p>EverGuard® TPO Quick Spray Adhesive LV50 is a low-VOC, solvent-based, sprayable contact adhesive useful for bonding smooth TPO membranes to various substrates.</p> <p>Up to 10 squares (93 square meters) of installed membrane per canister</p>                                    |
| Sealants   | Product image   | Description   |
| <p><b>EverGuard® One-Part Pourable Sealant</b><br/>VOC &lt; 25 g/l</p>       |  | <p>A one-part, moisture-cure, self-leveling sealant designed for use in pitch pans on single-ply roof systems. It's self-leveling, leaving a smooth, professional finished look with good color stability.</p> <p>Container size - 2 liters (4 per box)</p>                             |
| <p><b>EverGuard® Water-Block Mastic</b><br/>VOC &lt; 150 g/l</p>             |  | <p>A one-part, butyl-based high-viscosity sealant suitable for sealing between flashing membrane and substrate surfaces, behind exposed termination bars, and between roofing membrane and drain flanges.</p> <p>Tube size - 10.5 oz (20 tubes per box)</p>                             |
| <p><b>GAF FlexSeal™ Caulk Grade Sealant</b><br/>VOC 50 g/l</p>               |  | <p>A white solvent-based synthetic elastomeric sealant that is extremely flexible and durable, but with a higher viscosity formulation than Standard FlexSeal™.</p> <p>Tube size - 10 oz (20 tubes per box)</p>   |
| <p><b>GAF CleanWeld Low VOC Conditioner</b><br/>VOC 50 g/l</p>               |  | <p>Designed to clean exposed or contaminated seams prior to heat welding to remove any residual soap or to revitalize aged membranes.</p> <p>Container Size - 1 gallon (4 containers per box)</p>   |