

# EverGuard® Base and Ply Sheets

## Information Sheet



*Quality You Can Trust Since 1886...  
From North America's Largest Roofing Manufacturer™*

# Product Data Sheet

## EverGuard®

### Base and Ply Sheets

#### Description

GAF EverGuard® single-ply roofing systems include a full line of GAFGLAS® asphalt fiberglass base and ply sheets. GAF base and ply sheets are always included as part of a TriPosite™ system. In addition, GAF base sheets can also be installed in conjunction with EverGuard fleece-backed membrane as a venting base sheet recover/separation layer. The following base and ply sheets are available:

Product	Description	Benefit/Application	Quantity/Size	Applicable Standards
<b>GAFGLAS Stratavent® Eliminator™ Perforated Venting Base Sheet</b>	Perforated heavy-duty asphalt coated fiberglass base sheet with mineral surfacing on underside	<ul style="list-style-type: none"> <li>• Dry-applied venting base sheet over isocyanurate insulation, smooth surfaced asphalt built-up/modified bitumen roofing, and prepared mineral-surfaced asphalt or SBS cap sheets</li> <li>• Perforations allow hot asphalt attachment of EverGuard fleece-backed membrane through base sheet to underlying substrate</li> <li>• 1 roll provides 1.25 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 40 2/3'</li> <li>• 75 lbs.</li> </ul>	ASTM D4897, Type II UL Type G2 FM Approved Dade County Product Approval
<b>GAFGLAS Stratavent Eliminator Nailable Venting Base Sheet</b>	Non-perforated heavy-duty asphalt coated fiberglass base sheet with mineral surfacing on underside	<ul style="list-style-type: none"> <li>• Mechanically attached venting base sheet installed directly over nailable decks of all types, and as separation sheet over smooth or mineral surfaced existing roof surfaces</li> <li>• Allows hot asphalt attachment of EverGuard fleece-backed membrane directly to base sheet</li> <li>• 1 roll provides 1.25 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 40 2/3'</li> <li>• 75 lbs.</li> </ul>	ASTM D4897, Type II UL Type G2 FM Approved Dade County Product Approval
<b>GAFGLAS FlexPly® 6 Premium Ply Sheet</b>	Premium asphalt coated fiberglass Type VI ply sheet	<ul style="list-style-type: none"> <li>• Ply sheet installed as 2-ply or 3-ply assembly beneath fleece-backed membrane in TriPosite™ system</li> <li>• Ply sheet installed as 1-ply or 2-ply vapor retarder assembly</li> <li>• 1 roll provides 5 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 162'</li> <li>• 44 lbs.</li> </ul>	ASTM D2178, Type VI UL Type G1 FM Approved Dade County Product Approval
<b>GAFGLAS Ply 4</b>	Asphalt coated fiberglass Type IV ply sheet	<ul style="list-style-type: none"> <li>• Ply sheet installed as 2-ply or 3-ply assembly beneath fleece-backed membrane in TriPosite system</li> <li>• Ply sheet installed as 1-ply or 2-ply vapor retarder assembly</li> <li>• Meets or exceeds ASTM D2178, type IV</li> <li>• 1 roll provides 5 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 162'</li> <li>• 40 lbs.</li> </ul>	ASTM D2178, Type IV UL Type G1 FM Approved Dade County Product Approval
<b>GAFGLAS #75 Base Sheet</b>	Premium roofing base sheet	<ul style="list-style-type: none"> <li>• Allows hot asphalt attachment of EverGuard fleece-backed membrane directly to base sheet</li> <li>• Allows mechanical attachment of base sheet to all types of nailable decks</li> <li>• Meets or exceeds ASTM D4601, Type II</li> <li>• 1 roll provides 3 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 97.5'</li> <li>• 75 lbs.</li> </ul>	ASTM D4601, Type II UL Type G2 FM Approved Dade County Product Approval
<b>GAFGLAS #80 Ultima Base Sheet</b>	High performance roofing base sheet	<ul style="list-style-type: none"> <li>• Allows hot asphalt attachment of EverGuard fleece-backed membrane directly to base sheet</li> <li>• Allows mechanical attachment of base sheet to all types of nailable decks</li> <li>• Meets or exceeds ASTM D4601, Type II</li> <li>• 1 roll provides 2 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 65'</li> <li>• 75 lbs.</li> </ul>	ASTM D4601, Type II UL Type G2 FM Approved Dade County Product Approval
<b>Ruberoid® 20</b>	SBS modified premium base sheet	<ul style="list-style-type: none"> <li>• Base sheet installed as 2-ply assembly beneath fleece-backed membrane in TriPosite system</li> <li>• Base sheet installed as a 1 ply vapor retarder assembly</li> <li>• Meets or exceeds ASTM D6163, Type I</li> <li>• 1 roll provides 1.5 square coverage</li> </ul>	<ul style="list-style-type: none"> <li>• 39" x 49'</li> <li>• 95 lbs.</li> </ul>	ASTM D6163, Type I Grade S UL Listed FM Approved Dade County Product Approval

**Note:** Mass and dimensions stated as nominal unless otherwise indicated.