



PRODUCT DESCRIPTION

Knockdown Texture Cement is a unique blend of cement and aggregate that, when mixed with HydroStop™ BarrierGuard® acrylic resin and water, creates a mixture that can create a textured, slip-resistant surface.

When mixed correctly, the Knockdown Texture Mix can be used to enhance and beautify residential or commercial areas designed for light pedestrian foot traffic.

WARRANTY

See applicable warranties and guarantees for complete coverage and restrictions.

PACKAGING & SHELF LIFE

50 pound bag

Shelf life 18 months if unopened and stored between 50°F and 90°F.

GAF

1 Campus Drive
Parsippany, NJ 07054
1-800-ROOF-411
gaf.com

GAF Liquid-Applied

January 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 2023, 2024

For technical, system, and warranty information, visit gaf.com or call 1-800-766-3411.

ADVANTAGES & BENEFITS

- Improves the appearance of walkable decks
- Increases design variety for TrafficCoat Deck Coating applications
- Conceals PremiumCoat® Fabric lap lines for a more consistent finished surface
- Withstands foot traffic and inclement weather

PHYSICAL PROPERTIES

KNOCKDOWN TEXTURE CEMENT	
Appearance	Fine white powder
Weight per Bag	50 pounds

APPLICATION INSTRUCTIONS

MIXING: Mix BarrierGuard® and cold water in a 1:1 ratio. For each 50 pound bag of dry **Knockdown Texture Cement**, you will need approximately five quarts of the BarrierGuard®/water mixture. The amount of liquid will vary (\pm 10%) depending on the applicator and weather conditions.

Dispense approximately 2½ quarts of the BarrierGuard®/water mixture into a clean 5 gallon pail. Utilizing a variable speed drill with attached mixing paddle, slowly add ½ bag (25 pounds) of dry **Knockdown Texture Cement**.

The Knockdown Texture Mix (composed of BarrierGuard®, cold water, & dry **Knockdown Texture Cement**) is usu-

ally applied on conjunction with TrafficCoat Deck Coating over a PremiumCoat® System application.

Two surface coats of TrafficCoat Deck Coating are used to completely cover the cured Knockdown Texture Mix, providing both UV protection and a consistent surface color. Applying two thin coats of Acrysheen, a clear, water-based epoxy penetrating sealer will improve the maintenance of and ease in cleaning the deck surface.

For more specific instructions, please refer to the TrafficCoat Deck Coating Decorative Coating Specification.

SAFETY & HANDLING

For specific information regarding safe handling of this material please refer to the Safety Data Sheet (SDS).

CLEAN UP

Thoroughly rinse application equipment with clean water.

Our products are guaranteed to meet established quality control standards, information contained in our technical data is based on laboratory and field testing, but is subject to change without prior notice. No guarantee of accuracy are given or implied, nor does GAF assume any responsibility for coverage, performance on injuries resulting from storage, handling or use of our products. Liability, if any, is limited to product replacement or, if applicable, to the terms stated within the executed project warranty.