



LiveRoof® System

Quality You Can Trust...From North America's Largest Roofing Manufacturer!™
gaf.com

Why the LiveRoof® System?

GAF is partnering with LiveRoof® to combine the proven performance of EverGuard® Single-Ply Membranes with LiveRoof's patented, proven, hybrid green roof system.

- Each LiveRoof® module arrives to the jobsite fully grown and is simply set in place on the rooftop.
- LiveRoof® modules can be used over mechanically attached, fully adhered, and RhinoBond® TPO and PVC systems. TPO and PVC are loose laid over the roofing system with a 6 in. (15.25 cm) overlap to act as a slip sheet.
- During installation, the unique patent-pending LiveRoof® Soil Elevator™ is removed to allow for a seamless fit to provide the look of a "built-in" system, but without the extensive, ongoing costs of maturation.
- Systems are locally grown by a network of over 20 licensed growers across the USA and Canada, under the care of professional horticulturists, who select RoofTop Proven™ plant mixes suitable to each project and climate.
- LiveRoof® modules can be custom cut to create natural-looking green roofs with sweeping curves and full vegetation.

Systems:

LiveRoof® systems offer a variety of plant options with four system depths:


- **LiveRoof® Lite** – For retrofit projects where load limitations exist
- **LiveRoof® Standard** – Maximizes storm water management; integrates perfectly with new construction and existing buildings
- **LiveRoof® Deep** – Irrigated to expand plant biodiversity to an array of drought-resistant, conventional, and native perennials, grasses, and vegetables
- **LiveRoof® MAXX** – Meets municipal codes in locales with 8 in. (20.3 cm) soil depth requirement. Perimeter ballast supports drought-resistant perennials, grasses, and vegetables, and can be used to optimize biodiversity



Delivery and Installation:

Each LiveRoof® module arrives to the jobsite with fully established plants inside the module and is simply set in place on the rooftop. The unique, patent-pending Soil Elevator™ is then removed for a seamless fit. There is no need to start with a brown roof and farm it for years, hoping and waiting for it to become a green roof. The GAF LiveRoof® system can be installed over EverGuard® TPO and PVC membranes.

Step 1



The licensed grower inserts the LiveRoof® Soil Elevator™ into the module.

Step 2



LiveRoof® module is filled to the top of Soil Elevator™ with LiveRoof® engineered growing medium.

Step 3



LiveRoof® plants are grown to maturity approximately 1 inch above the LiveRoof® module.

Step 4



Certified Installer sets LiveRoof® modules tightly in place on the roof within RoofEdge® aluminum edge restraint.

Step 5



LiveRoof® Soil Elevator™ is removed for a beautiful, seamless, instantly mature green roof.

Step 6



Water thoroughly to settle any loose growing medium and to get your green roof off to a great start.

SYSTEM	LITE	STANDARD	DEEP	MAXX
Soil Depth	2.5 in (65 mm)	4.25 in (110 mm)	6 in (150 mm)	8 in (200 mm)
Dry Weight	±12 lbs/ft ² (±0.6 kPa)	±20 lbs/ft ² (±1.0 kPa)	±30 lbs/ft ² (±1.4 kPa)	±40 lbs/ft ² (±1.9 kPa)
Fully Saturated Weight <i>Maximum, varies by vegetation type and maturity level</i>	≤17 lbs/ft ² (≤0.8 kPa)	≤29 lbs/ft ² (≤1.4 kPa)	≤50 lbs/ft ² (≤2.4 kPa)	≤65 lbs/ft ² (≤3.1 kPa)
Maximum Water-Holding Capacity (ASTM E2397)	48.3%			
Wilt Point of Plants	10%			
Maximum Available Capacity of Growing Medium to Hold Water	38.3%			
Growing Medium Maximum Moisture Storage	.96 in (24 mm) 0.6 gal/ft ² (24.4 L/m ²)	1.6 in (40 mm) 1 gal/ft ² (41.3 L/m ²)	2.2 in (55 mm) 1.3 gal/ft ² (55.9 L/m ²)	3 in (76 mm) 1.8 gal/ft ² (76.2 L/m ²)
Plant Moisture Storage (Sedums)	0.4 in (10 mm) 0.25 gal/ft ² (10.1 L/m ²)			
System Total Storm Water Storage (Assuming Initial Moisture 0.25 in/6mm)	1.11 in (28 mm) 0.7 gal/ft ² (28.2 L/m ²)	1.75 in (44 mm) 1.1 gal/ft ² (44.4 L/m ²)	2.35 in (60 mm) 1.5 gal/ft ² (59.7 L/m ²)	3.15 in (80 mm) 2 gal/ft ² (80 L/m ²)
Water Permeability (saturated hydraulic conductivity)	0.434 in/min (0.018 cm/s)			
WITH ROOFBLUE™ RISER (for use with control-flow drain system)				
Maximum Water Depth	3.5 in (89 mm)			
Void Space	90.5%			
Maximum Water Volume Detained	456 in ³ (7472 cm ³) 1.97 gal/ft ² (80.4 L/m ²)			
Maximum Water Volume Managed with Retention and Detention <i>Actual water retained/detained will vary with drain selection, spacing, and roof pitch</i>	615 in ³ /ft ² 2.6 gal/ft ² (108 L/m ²)	708 in ³ /ft ² 3 gal/ft ² (125 L/m ²)	793 in ³ /ft ² 3.4 gal/ft ² (140 L/m ²)	908 in ³ /ft ² 3.9 gal/ft ² (160 L/m ²)
WIND AND FIRE RESISTANCE				
FM Approval Standard for Vegetative Roof Systems (FM 4477)	FM Approved			
Fire Resistance (ASTM E108) with Succulent Plantings <i>* Test Performed</i> <i>** Performance Expected Based on Similar Testing</i>	Class A**	Class A**		Class A*
External Fire Design Standard for Vegetative Roofs (ANSI/SPRI VF-1)	Meets requirements for generic fire-resistive vegetative systems (4.1)			
Wind Uplift Resistance (CAN/CSA A123.24-15) <i>* Full Scale Test Performed</i> <i>** Performance Expected Based on Similar Testing of Lighter System(s)</i>	200 PSF (9.6 kPa) sustained* (133 PSF (6.4 kPa) rating after 1.5 experimental factor)	200 PSF** (133 PSF after 1.5 experimental factor)		
Wind Flow Resistance (CAN/CSA A123.24-15) <i>* Test Performed – Sustained maximum wind speed produced by testing equipment.</i> <i>** Performance Expected Based on Similar Testing of Lighter System(s)</i>		124 mph (200 km/h) sustained* (83mph (133 km/h) rating after 1.5 experimental factor)	124 mph (200 km/h)** (83mph (133 km/h) after 1.5 experimental factor)	
Wind Design Standard for Vegetative Roofing Systems (ANSI/SPRI RP-14)	#4 Ballast (3.13.1)	#2 Ballast (3.13.2) and #4 Ballast (3.13.1)		

Contact your local representative for details.

LiveRoof® is a registered trademark of Hortech, Inc.



gaf.com