



# M-BOND™ ADHESIVE/SEALANT

## Description

M-Bond™ Adhesive/Sealant is a moisture-curing polyether roofing sealant that bonds to asphaltic membranes, concrete, steel, aluminum, wood, glass, and PVC.

## Uses

Designed for use in the M-Curb™ Pitch Pocket System to seal around penetrations; also used to adhere the M-Curb™ Pitch Pocket System to the asphaltic roof. See M-Curb™ Pitch Pocket System Installation Instructions at [gaf.com](http://gaf.com) for more information.

## Surface Preparation

All surfaces shall be clean, sound, dry, and free of loose materials like rust, oil, wax, and grease. Wipe all new metal with rubbing alcohol before sealant application.

## Packaging

10.1 fl. oz. (300 ml)

## Color

Black

## Shelf Life

Shelf life of M-Bond™ Adhesive/Sealant is 12 months from date of manufacture when stored at 70°F (21°C) with 50% relative humidity. High temperature and high relative humidity may significantly reduce shelf life. M-Bond™ Adhesive/Sealant will not freeze under normal conditions.

## Precautions

- Do not store in elevated temperatures. Elevated temperatures will reduce shelf life.
- Store unopened containers in a cool, dry area. Protect unopened containers from water, heat, and direct sunlight.
- Use only on clean, dry surfaces that are free of all surface contaminants.
- Do not apply in temperatures below 32°F (0°C).
- Do not cut or thin M-Bond™ Adhesive/Sealant.
- Cold temperatures and low humidity will slow curing.
- Do not use on TPO or Kynar® PVDF coated materials.
- Always test substrates to confirm adhesion.

## For Application Questions

Contact GAF Technical Services at 1-800-766-3411 or visit [gaf.com](http://gaf.com) for SDS, technical data specifications, and warranty information.

