

PRODUCT SPECIFICATIONS & USAGE RECOMMENDATIONS (Based on the 1/300 Attic Ventilation Rule)

SSB960A / SSB960G

Total Attic Square Footage	Recommended Number Of SSB960 Louvers	Minimum Intake Ventilation (Net Free Area In Sq. In.)
0-1000	4	240
1001-1500	6	360
1501-2000	8	480
2001-2500	10	600
2501-3000	12	720

IR65

Total Attic Square Footage	Recommended Number Of IR65 Louvers	Minimum Intake Ventilation (Net Free Area In Sq. In.)
0-1000	4	260
1001-1500	6	390
1501-2000	8	520
2001-2500	10	650
2501-3000	12	780

RT65

Total Attic Square Footage	Recommended Number Of RT-65 Louvers	Minimum Intake Ventilation (Net Free Area In Sq. In.)
0-1000	4	240
1001-1500	6	360
1501-2000	8	480
2001-2500	10	600
2501-3000	12	720

IR61

Total Attic Square Footage	Recommended Number Of IR-61 Louvers	Minimum Intake Ventilation (Net Free Area In Sq. In.)
0-1000	7	259
1001-1500	10	370
1501-2000	13	481
2001-2500	17	629
2501-3000	20	740

Roof Louver Size & Color Chart

Mill	Brown	Black	Weathered Wood	ShingleMatch™ Weathered Wood	Gray	White	Shakewood	Construction	Opening Size	Flashing Dimensions	Height	NFA (Sq. In.)
SSB960A	SSB960ABR	SSB960ABL	SSB960AWW	SSB960ASMWW	—	SSB960AW	—	Aluminum	10"	16" x 20.5"	5 1/2"	60
SSB960AWF	SSB960AWFBR	SSB960AWFBL	SSB960AWFWW	—	—	SSB960AWFW	—	Aluminum w/ Weather Filter	10"	16" x 20.5"	5 1/2"	60
—	SSB960ASCBR	SSB960ASCBL	SSB960ASCWW	—	—	—	SSB960ASCW	Aluminum w/ Granule Coating	10"	16" x 20.5"	5 1/2"	60
—	SSB960GBR	SSB960GBL	SSB960GWW	—	—	—	—	Galvanized	10"	16" x 20.5"	5 1/2"	60
R50A	R50ABR	R50ABL	R50AWW	—	—	—	—	Aluminum	9" x 9"	17 3/8" x 15 1/8"	4"	50
RV50G	RV50GBR	RV50GBL	RV50GWW	—	—	—	—	Galvanized	9"	15" x 16 1/2"	4"	50
RV50A	RV50ABR	RV50ABL	RV50AWW	—	—	—	—	Aluminum	9"	15" x 16 1/2"	4"	50
HCD144	HCD144BR	HCD144BL	HCD144WW	—	—	—	—	Galvanized	15"	25" x 25"	8"	144
—	IR65BR	IR65BL	IR65WW	—	IR65G	—	—	High-Impact Resin	11 3/8" x 10 3/8"	20 1/2" x 18"	5 1/8"	65
—	RT65BR	RT65BL	RT65WW	—	RT65G	—	—	High-Impact Resin	11 1/8" x 10"	18 1/2" x 18"	4"	60
—	IR61BR	IR61BL	IR61WW	—	IR61G	—	—	High-Impact Resin	11 3/8" x 9 3/8"	18 1/2" x 17 1/2"	3 3/8"	37

Note: Minimum roof pitch is 3:12

RV50A/RV50G & R50A

Total Attic Square Footage	Recommended Number Of RV50/R50 Louvers	Minimum Intake Ventilation (Net Free Area In Sq. In.)
0-1000	5	250
1001-1500	8	400
1501-2000	10	500
2001-2500	12	600
2501-3000	15	750

HCD144

Total Attic Square Footage	Recommended Number Of HCD144 Vents	Minimum Intake Ventilation (Net Free Area in Sq. in.)
0-1000	2	288
1,001 - 1,500	3	432
1,501 - 2,000	4	576
2,001 - 2,500	5	720

Aluminum Gable Wall Louvers

Model Number	Opening Dimensions	Overall Dimensions	NFA(Sq. In.)
DA12x12	12" x 12"	14 1/2" x 14 5/8"	60
DA12x18	12" x 18"	14 1/2" x 20 1/2"	90
DA14x24	14" x 24"	16 1/2" x 26 3/8"	141
DA18x24	18" x 24"	20 1/2" x 26 3/8"	181
DA24x30	24" x 30"	26 1/2" x 32 1/4"	302

Note: Add "W" to model number for painted white.

Thermoformed Plastic Gable Wall Louvers

Model Number	Opening Dimensions	Overall Dimensions	NFA(Sq. In.)
SL8x8	8" x 8"	10 1/2" x 10 1/2"	17
SL12x12	12" x 12"	14 1/2" x 14 1/2"	43
SL12x18	12" x 18"	14 1/2" x 20 1/2"	65
SL18x24	18" x 24"	20 3/4" x 26 3/4"	141

Plastic Circular Louvers

Model Number	Size	NFA(Sq. In.)
RLSC2	2"	1.50
RLSC3	3"	3.20
RLSC4	4"	5.17

Note: Always have a balanced attic ventilation system. The amount of exhaust ventilation should NEVER exceed the amount of intake ventilation.