

# Power Attic Vent Accessories

## Gable Mount - Automatic Shutter SGM 20

- **Versatile...** Use with all power gable vents
- **Automatic...** Moving air opens the louvers only when the power vent is operating
- **Weather-Resistant...** When vent is off, shutter helps prevent infiltration of rain, snow, insects, etc.
- **Maintenance-Free...** White aluminum construction can be painted if desired



**Opening Dimensions**  
16 1/2" x 16 1/2"

**Overall Dimensions**  
19 1/4" x 19 1/4"

## Humidistat (Model H1)

- Fully adjustable for all climate conditions
- Can be used with all Master Flow® & previous LL Building Products Inc. Power Vents
- Helps power ventilator reduce damaging attic moisture



## Replacement Thermostat (Model PT6)

- Automatic and adjustable
- Compatible with all single-speed Master Flow® & previous LL Building Products Inc. Power Vents
- UL listed



## Humidistat/Thermostat (Model HT1)

- Fully adjustable for all climate conditions
- Can be used with all Master Flow® & previous LL Building Products Inc. Power Vents
- Helps power vents reduce damaging attic heat & moisture



## Replacement Motors (not shown)

- **Model PVM105** – Replaces motor for the following models: PG1, CPG2 (available in Canada only), PG2, PR1, CPR1D, PR1D, CPR2D, PR2D, PR2DHT, ERV & EGV Series
- **Model PVM115** – Replacement motor for the following models: PSG3, PSG3HT, PG3X, PSR10D, PSR10DHT, PR3XD & PRX3DH

## PRODUCT SPECIFICATIONS

### Choose the Right Master Flow® Power Attic Vent–Roof Mount

	CERV4 <sup>1</sup> , ERV4	CERV5 <sup>1</sup> , ERV5, ERV5HT*	ERV6, ERV6HT*
For Maximum Attic Size (sq. ft. @ 4:12 roof pitch)	1,600	2,200	2,800
Air Flow (CFM)	1,000	1,250	1,500
Minimum Intake Ventilation Needed at Soffits or Fascia, etc. (Net Free Area in sq. in.)	480	600	720
Energy Usage vs. Competitors' Units**	Up to 55% Less	Up to 55% Less	Up to 15% Less
Roof Pitch Range	2:12 – 12:12	2:12 – 12:12	2:12 – 12:12
Adjustable Thermostat Included	Yes	Yes	Yes
Optional Adjustable Humidistat/Thermostat Available	–	Yes	Yes
Length of Ltd. Warranty*** (yrs.)	5	5	10
Length of Labor Protection Plus plan*** (yrs.)	2	3	5

### Power Attic Vent–Roof Mount Color Availability

Mill	Black	Brown	Weathered Wood	ShingleMatch™ Weathered Wood
ERV4	ERV4BL	ERV4BR	CERV4WW <sup>1</sup> , ERV4WW	–
ERV5	ERV5BL	ERV5BR	CERV5WW <sup>1</sup> , ERV5WW	–
ERV5HT*	ERV5BLHT*	ERV5BRHT*	ERV5WWHT*	–
–	ERV6BL	ERV6BR	ERV6WW	ERV6SMWW
–	ERV6BLHT*	ERV6BRHT*	ERV6WWHT*	ERV6SMWWHT*

### Choose the Right Master Flow® Power Attic Vent–Gable Mount

	CEGV5 <sup>1</sup> , EGV5	EGV6, EGV6HT*
For Maximum Attic Size (sq. ft. @ 4:12 Roof Pitch)	2,300	3,000
Air Flow (CFM)	1,450	1,600
Minimum Intake Ventilation Needed at Soffits or Fascia, etc. (Net Free Area in sq. in.)	696	768
Adjustable Thermostat Included	Yes	Yes
Optional Adjustable Humidistat/Thermostat Available	–	Yes
Length of Ltd. Warranty*** (yrs.)	5	10
Length of Labor Protection Plus plan*** (yrs.)	3	5

<sup>1</sup>Available in Canada Only  
<sup>\*</sup>Includes adjustable humidistat/thermostat  
<sup>\*\*</sup>Based on GAF testing at 120 volts  
<sup>\*\*\*</sup>See Master Flow® Powered Ventilation Products Limited Warranty for complete coverage and restrictions.

Note: Always have a balanced attic ventilation system. The amount of exhaust ventilation should NEVER exceed the amount of intake ventilation.