

GAF Safety Data Sheet SDS # 1008A

SDS Date: June 2023

SECTION 1: PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: Weather Watch 2.0

Weather Watch 1.5

StormGuard StormFlash

TRADE NAME: Roll Roofing

MANUFACTURER: GAF

ADDRESS: 1 Campus Drive, Parsippany, NJ 07054

24-HOUR EMERGENCY

800 - 424 - 9300

PHONE (CHEMTREC):
INFORMATION ONLY:

800 - 766 - 3411

PREPARED BY: Corporate EHS

APPROVED BY: Corporate EHS

SECTION 2: HAZARDS IDENTIFICATION

As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, the products listed below are considered articles and do not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, GAF would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and be made available for employees and other users of this product. In addition, the recommendations for handling and use of these products should be included in worker training programs.

ADDITIONAL HAZARD IDENTIFICATION INFORMATION:

PRIMARY ROUTE OF EXPOSURE: Occasional nuisance dust, Inhalation

SIGNS & SYMPTOMS OF

EXPOSURE

EYES: May cause irritation to the eyes.

SKIN: May cause irritation to the skin.

INGESTION: This product is not intended to be ingested. If ingested, it may

cause temporary irritation to the gastrointestinal (digestive)

tract.

INHALATION: May cause irritation to the respiratory tract.

ACUTE HEALTH HAZARDS: None known.

CHRONIC HEALTH HAZARDS: Studies in humans have found that exposure to respirable

crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is a serious and irreversible disease; it may be progressive even after exposure has ceased; it can lead to disability and death. Human studies also have found that silicosis is a risk factor for tuberculosis, and that occupational exposure to respirable crystalline silica is associated with chronic obstructive pulmonary disease, including bronchitis and emphysema. Some studies show excess numbers of cases of scleroderma, connective tissue disorders, lupus, rheumatoid arthritis, chronic kidney diseases and and stage kidney disease in workers exposed to

and end-stage kidney disease in workers exposed to

respirable crystalline silica.

CARCINOGENICITY: NIOSH has concluded that the collective data from human,

animal, genotoxicity and exposure studies provide sufficient evidence that roofing asphalt fumes are a potential

occupational carcinogen.

Occupational exposure to respirable crystalline silica is classified as a known carcinogen in humans. IARC has determined that respirable crystalline silica is carcinogenic to humans (Group 1), based on findings of sufficient evidence of carcinogenicity in both humans and experimental animals. NTP has classified respirable crystalline silica as a known human carcinogen based on sufficient evidence of carcinogenicity from studies in humans indicating a causal relationship between occupational exposure to respirable crystalline silica and increased lung cancer rates. NIOSH has determined that respirable crystalline silica is a potential

occupational carcinogen.

IARC has determined that occupational exposure to Titanium Dioxide is possibly carcinogenic to humans (Group 2B). IARC concluded lung tumors were observed in rats following high doseexposure by inhalation and in female rats exposed by intra-tracheal instillation. Other studies have shown no tumors in rats following inhalation exposure and no tumors in mice or

rats following oral exposure.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

			OCCUPATIONAL EXPOSURE LIMITS			
CHEMICAL NAME	CAS#	% (BY WT)	OSHA	ACGIH	OTHER	
Granules/Slag	-	40-50	NE	NE	NE	
Oxidized Asphalt	64742-93-4	25-30	NE	0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)	5 mg/m3 – ceiling (15 min. fumes)	
Limestone	1317-65-3	5-10	5 mg/m3 resp. 15 mg/m3 total	3 mg/m3 resp. 10 mg/m3 total	REL: 5 mg/m3 resp. 15 mg/m3 total	
Fiberglass Mat	65997-17-3	1-3	1 f/cc – resp.	1 f/cc – resp.	REL: 5 mg/m3 – total fibers	
Silica, Crystalline Quartz	14808-60-7	0-1	50 ug/m3 / (% SiO2 + 2) – resp.	0.025 mg/m3	REL: 0.05 mg/m3 – resp.	
Titanium Dioxide	13463-67-7	0–1	15 mg/m3 total	10 mg/m3 total	NE	

NE = Not Established

SECTION 4: FIRST AID MEASURES

FIRST AID PROCEDURES

EYES: Hold eyelids open and wash with gentle stream of water for at least 15

minutes preferably at eyewash fountain.

SKIN: Wear appropriate gloves. If contacted by hot asphalt cool with ice or

water. Do not attempt to remove asphalt immediately. Consult medical

personnel.

Treat symptomatically

INHALATION: Move to fresh air.

INGESTION: Not expected to be ingested.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

SECTION 5: FIRE FIGHTING PROCEDURES

SUITABLE EXTINGUISHING MEDIA: Water spray, alcohol foam, carbon dioxide, or dry chemical.

HAZARDOUS COMBUSTION

PRODUCTS:

Carbon dioxide and carbon monoxide.

RECOMMENDED FIRE FIGHTING

PROCEDURES:

NIOSH-approved self contained breathing apparatus is

recommended for smoke protection.

UNUSUAL FIRE & EXPLOSION

HAZARDS:

None.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE

MEASURES:

Pick up large pieces. Avoid creating dusts during clean up.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool, dry place.

OTHER PRECAUTIONS: None.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS /

VENTILATION:

Not applicable.

RESPIRATORY PROTECTION: Not required under normal use conditions. In circumstances

where dust or fumes are generated and may exceed recognized

allowable exposure levels, appropriate NIOSH approved

respiratory protection is recommended.

EYE PROTECTION: Safety glasses with side shields

SKIN PROTECTION: Cotton or leather gloves are recommended when handling.

OTHER PROTECTIVE EQUIPMENT: None

Wash exposed skin prior to eating, drinking or smoking and at the

WORK HYGIENIC PRACTICES: end of each shift.

EXPOSURE GUIDELINES:

These products should be handled using methods and techniques that minimize or eliminate dust or fume generation.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE & ODOR:	Thin black sheet in roll form, may be surfaced with granules, talc, sand or film. Slight asphalt odor.				
FLASH POINT:	>500° F	LOWER EXPLOSIVE LIMIT:	No Data		
METHOD USED:	COC	UPPER EXPLOSIVE LIMIT:	No Data		
EVAPORATION RATE:	No Data	BOILING POINT:	No Data		
pH (undiluted product):	No Data	MELTING POINT:	No Data		
SOLUBILITY IN WATER:	No Data	SPECIFIC GRAVITY:	No Data		
VAPOR DENSITY:	No Data	PERCENT VOLATILE:	No Data		
VAPOR PRESSURE:	No Data	MOLECULAR WEIGHT:	No Data		
VOC WITH WATER (LBS/GAL):	No Data	WITHOUT WATER (LBS/GAL):	No Data		

SECTION 10: STABILITY AND REACTIVITY					
THERMAL STABILITY:	STABLE X	UNSTABLE			
CONDITIONS TO AVOID (STABILITY):	None known.				
INCOMPATIBILITY (MATERIAL TO AVOID):	None known.				
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	None known.				
HAZARDOUS POLYMERIZATION:	Will not occur.				
SECTION 11: TOXICOLOGICAL INFORMATION					
TOXICOLOGICAL None available for the product. See section 3. INFORMATION:					

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No information available

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: This product, as supplied, is not regulated as a hazardous waste by the

U.S. Environmental Protection Agency (EPA) under Resource

Conservation and Recovery Act (RCRA) regulations. Comply with state

and local regulations for disposal.

RCRA HAZARD CLASS: None

SECTION 14: TRANSPORTATION INFORMATION

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA: This product and its components are listed on the TSCA 8(b)

inventory.

CERCLA: None

SARA

311/312 HAZARD CATEGORIES: None

313 REPORTABLE

None

INGREDIENTS:

CALIFORNIA PROPOSITION 65: This product contains oxidized asphalt, silica and titanium dioxide,

chemicals known to the state of California to cause cancer.

Other state regulations may apply. Check individual state requirements. The following components appear on one or more of the following state hazardous substances lists:

Chemical Name	CAS#	CA	MA	MN	NJ	PA	RI
Oxidized Asphalt	64742-93-4	Yes	Yes	Yes	Yes	Yes	Yes
Crystalline Silica	14808-60-7	Yes	Yes	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	No	Yes	Yes	Yes	Yes	Yes
Limestone	1317-65-3	No	Yes	Yes	No	Yes	Yes
Fiberglass Mat	65997-17-3	Yes	No	Yes	Yes	No	Yes

SECTION 16: OTHER INFORMATION

ADDITIONAL COMMENTS: None

DATE OF PREVIOUS SDS: May 2018

CHANGES SINCE PREVIOUS SDS: Product name change, Prop 65 update.

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.