



STORMSAFE™ ANCHOR SHEET



Description

StormSafe™ Anchor Sheet for self-adhered membranes is a tough, non-breathable synthetic anchor sheet designed and manufactured to meet industry and code requirements for self-adhered low-slope roofing applications. It is a polypropylene woven fabric coated on both sides with polypropylene.

Uses

StormSafe™ Anchor Sheet is designed for use as an anchor sheet for LIBERTY™ (modified bitumen) and EverGuard® Freedom™ TPO self-adhered roof systems.

StormSafe™ Anchor Sheet's woven fabric creates a tough, durable reinforcement and its polypropylene coating makes it suitable for many applications. StormSafe™ Anchor Sheet is alkaline resistant, making it suitable for use over lightweight insulating concrete systems. The tough woven fabric makes it extremely tear resistant. In addition, the polypropylene coating ensures a good bond with both the butyl adhesive of Freedom™ membranes and the SBS modified adhesive of LIBERTY™ SBS Self-Adhering Base/Ply Sheet and LIBERTY™ SBS Self-Adhering Cap Sheet.

Advantages

- System guarantees are available for up to 20 years.*
- Lightweight — Adds less than 1.3 lbs per square to the system.
- Durable — Woven fabric provides superior tear strength and excellent dimensional stability.

Application

StormSafe™ Anchor Sheet should be applied with the beige color on top (weather side) and white color coating toward the deck side. Suitable substrates include plywood, OSB, acceptable EnergyGuard™ Insulations, and lightweight insulating concrete. The product is designed to be installed mechanically over approved roofing substrates using acceptable fasteners that include galvanized nails with 1-inch (25 mm) integral heads or Drill-Tec™ Fasteners and Plates in accordance with applicable specifications. Prior to installing any self-adhering membrane, StormSafe™ Anchor Sheet must be clean and dry. Use care walking on the sheet when it is wet as it may be slippery.

* See applicable guarantee for complete coverage and restrictions.

Applicable Standards

Slip Sheet for Roofing Systems
AS TO EXTERNAL FIRE EXPOSURE

State of Florida Product Approved

See *Modified Bitumen and Built-Up Roofing Application and Specifications Manual* or UL Directory for specific approval

Product Specifications (nominal)

Roll Size	22 squares net (2,200 gross sq. ft.) (204.39 m ²)
Roll Length	600' (182.9 m)
Roll Width	48" (1.2 m)
Approx. Roll Weight	67.9 lbs (30.8 kg)
Permeability Rating	< 3