

SAFETY DATA SHEET



1. Identification

Product identifier STREETBOND COLORANT HUNTER GREEN

Other means of identification

Product Code

Recommended use Green.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GAF
1 Campus Drive
Parsippany, NJ 07054 USA

Telephone 1-800-766-3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300
Within USA and CANADA 1-800-424-9300
Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Titanium Dioxide | | 13463-67-7 | 5 to <10 |
| Carbon Black | | 1333-86-4 | 1 to <5 |
| Propylene Glycol | | 57-55-6 | 1 to <5 |
| PARAFFINIC PETROLEUM OIL | | 64742-54-7 | 0.1 to <1 |
| Other components below reportable levels | | | 80 to <90 |

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Direct contact with eyes may cause temporary irritation. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|-----------------------------------|------|-----------------------|-------------|
| Carbon Black (CAS 1333-86-4) | PEL | 3.5 mg/m ³ | |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m ³ | Total dust. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|----------|---------------------|
| Carbon Black (CAS 1333-86-4) | TWA | 3 mg/m3 | Inhalable fraction. |
| PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) | TWA | 5 mg/m3 | Inhalable fraction. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | 10 mg/m3 | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|------------------------------|------|-----------|
| Carbon Black (CAS 1333-86-4) | TWA | 0.1 mg/m3 |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value | Form |
|--------------------------------|------|----------|----------|
| Propylene Glycol (CAS 57-55-6) | TWA | 10 mg/m3 | Aerosol. |

| | |
|--|---|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | If contact is likely, safety glasses with side shields are recommended. |
| Skin protection | |
| Hand protection | For prolonged or repeated skin contact use suitable protective gloves. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties**Appearance**

| | |
|---|----------------|
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Green. |
| Odor | Not available. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | Not available |
| Initial boiling point and boiling range | Not available |
| Flash point | Not available |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available |

| | |
|--|--|
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 10.08 lbs/gal |
| Flammability class | Not available |
| Percent volatile | 84.07 % |
| Specific gravity | 1.21 |
| VOC | 1.395571 lbs/gal Material estimated 4.256792 lbs/gal Regulatory estimated 167.231273 g/l Material estimated 510.091385 g/l Regulatory estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

| | |
|---|--|
| Symptoms related to the physical, chemical and toxicological characteristics | Direct contact with eyes may cause temporary irritation. |
|---|--|

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results |
|--------------------------------|----------------|---------------------|
| Carbon Black (CAS 1333-86-4) | | |
| <u>Acute</u> | | |
| Oral | | |
| LD50 | Rat | > 8000 mg/kg |
| Propylene Glycol (CAS 57-55-6) | | |
| <u>Acute</u> | | |
| Oral | | |
| LD50 | Guinea pig | 18.4 g/kg |
| | Mouse | 23.9 g/kg |
| | Rabbit | 18 g/kg |

| Components | Species | Test Results |
|------------|---------|--------------|
| | Rat | 30 g/kg |

* Estimates for product may be based on additional component data not shown.

| | | |
|---|--|--|
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not available. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Suspected of causing cancer. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Carbon Black (CAS 1333-86-4) | 2B Possibly carcinogenic to humans. | |
| Titanium Dioxide (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) | | |
| Not listed. | | |
| US. National Toxicology Program (NTP) Report on Carcinogens | | |
| PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) | Known To Be Human Carcinogen. | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not available. | |
| Chronic effects | Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. | |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|-----------------------------------|---------|---|
| Propylene Glycol (CAS 57-55-6) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 10000 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours |
| Titanium Dioxide (CAS 13463-67-7) | | |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 1000 mg/l, 48 hours |
| Fish | LC50 | Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

| | | |
|--|---|--|
| Persistence and degradability | No data is available on the degradability of this product. | |
| Bioaccumulative potential | | |
| Partition coefficient n-octanol / water (log Kow) | | |
| Propylene Glycol | -0.92 | |
| Mobility in soil | No data available. | |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. | |

13. Disposal considerations

| | |
|-----------------------------------|--|
| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |

| | |
|--|--|
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. |

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Carbon Black (CAS 1333-86-4)
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Carbon Black (CAS 1333-86-4)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Black (CAS 1333-86-4)

Propylene Glycol (CAS 57-55-6)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Black (CAS 1333-86-4)

Propylene Glycol (CAS 57-55-6)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)

Listed: February 21, 2003

Titanium Dioxide (CAS 13463-67-7)

Listed: September 2, 2011

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|----------------------|---|
| Issue date | 12-04-2014 |
| Revision date | 12-03-2015 |
| Version # | 09 |
| HMIS® ratings | Health: 1* Flammability: 0 Physical hazard: 0 |
| NFPA ratings | Health: 0 Flammability: 0 Instability: 0 |

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS