SAFETY DATA SHEET



1. Identification

Product identifier STREETBOND COLORANT BROWN SUEDE

Other means of identification

Product Code

Recommended use Colorant.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GAF

1 Campus Drive

Parsippany, NJ 07054 USA

Telephone 1-800–766–3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300

Within USA and CANADA 1-800-424-9300
Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%	
Titanium Dioxide		13463-67-7	20 to <30	

Material name: STREETBOND COLORANT BROWN SUEDE Version #: 05 Revision date: 12-03-2015

SDS 3203

Chemical name	Common name and synonyms	CAS number	%
Carbon Black		1333-86-4	1 to <5
Propylene Glycol		57-55-6	1 to <5
Silicate		14807-96-6	1 to <5
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable lev	/els		60 to <70

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Rinse mouth. Get medical attention if symptoms occur. Ingestion Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: STREETBOND COLORANT BROWN SUEDE Version #: 05 Revision date: 12-03-2015

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
Silicate (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
US. Workplace Environmental Exp	osure Level (WEEL) Guides		
Components	Туре	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.

Biological limit values

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

SDS 3203

Physical state Liquid.
Form Liquid.
Color Brown.
Odor Not available.
Odor threshold Not available.

Material name: STREETBOND COLORANT BROWN SUEDE Version #: 05 Revision date: 12-03-2015 pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 16.34 lbs/gal
Flammability class Not available.
Percent volatile 59.63 %
Specific gravity 1.96

VOC 155.18716 g/l Material estimated

1.295061 lbs/gal Material estimated 2.347963 lbs/gal Regulatory estimated 281.356406 g/l Regulatory estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Material name: STREETBOND COLORANT BROWN SUEDE Version #: 05 Revision date: 12-03-2015

SDS US

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Carbon Black (CAS 1333-86-4)		
<u>Acute</u>		
Oral		
LD50	Rat	> 8000 mg/kg
Propylene Glycol (CAS 57-55-6)		
<u>Acute</u>		
Oral		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritationProlonged skin contact may cause temporary irritation. **Serious eye damage/eye**Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species **Test Results** Propylene Glycol (CAS 57-55-6) Aquatic Crustacea > 10000 mg/l, 48 hours EC50 Water flea (Daphnia magna) Fish LC50 Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours Titanium Dioxide (CAS 13463-67-7) Aquatic Crustacea EC50 Water flea (Daphnia magna) > 1000 mg/l, 48 hours

Material name: STREETBOND COLORANT BROWN SUEDE

Version #: 05 Revision date: 12-03-2015

SDS 3203

Components Species **Test Results** Mummichog (Fundulus heteroclitus) > 1000 mg/l, 96 hours Fish LC50

* Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Propylene Glycol -0.92

No data available. Mobility in soil

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910,1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

> Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

Material name: STREETBOND COLORANT BROWN SUEDE

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Carbon Black (CAS 1333-86-4)

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Silicate (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Carbon Black (CAS 1333-86-4)

Silicate (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Black (CAS 1333-86-4)

Propylene Glycol (CAS 57-55-6)

Silicate (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Black (CAS 1333-86-4)

Propylene Glycol (CAS 57-55-6)

Silicate (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Material name: STREETBOND COLORANT BROWN SUEDE Version #: 05 Revision date: 12-03-2015

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 12-04-2014

 Revision date
 12-03-2015

Version # 05

HMIS® ratings Health: 1*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 0

Flammability: 0 Instability: 0

DisclaimerThis information relates to the specific material designated and may not be valid for such material

used on combination with any other materials or in any process. Such information is to the best of

our knowledge and belief accurate and reliable as of the date compiled. However, no

representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information Product and Company Identification: Converted to GAF SDS

Material name: STREETBOND COLORANT BROWN SUEDE

Version #: 05 Revision date: 12-03-2015

SDS 3203

SDS US

8/8