SAFETY DATA SHEET

1 703-741-5970



1. Identification		
Product identifier	STREETBOND COLORANT SA	AFETY BLUE
Other means of identification Product Code		
Recommended use	Colorant.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	GAF 1 Campus Drive Parsippany, NJ 07054 USA	
Telephone Emergency phone number	1-800–766–3411 CHEMTREC [DAY OR NIGHT] Within USA and CANADA	1-800-424-9300 1-800-424-9300

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		

Outside USA and Canada:



Signal word	None.
Hazard statement	Suspected of causing cancer.
Precautionary statement	
Prevention	Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Not available.
Disposal	Not available.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	30 to <40
Propylene Glycol		57-55-6	5 to <10
Copper Phthalocyanine		147-14-8	1 to <5
Silicate		14807-96-6	1 to <5
PARAFFINIC PETROLEUM OI	L	64742-54-7	0.1 to <1
Other components below report	able levels		50 to <60
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptoms d	evelop or persist.	
Skin contact	Wash off with soap and water. Get medical attent	tion if irritation develops a	and persists.
Eye contact	Rinse with water. Get medical attention if irritation	n develops and persists.	
Ingestion	Rinse mouth. Get medical attention if symptoms	occur.	
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irr	itation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat s Symptoms may be delayed.	ymptomatically. Keep vio	tim under observati
General information	IF exposed or concerned: Get medical advice/atte of the material(s) involved, and take precautions		cal personnel are av
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon	dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this w	vill spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be fo	rmed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full prote	-	orn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so v	vithout risk.	
Specific methods	Use standard firefighting procedures and conside	er the hazards of other inv	volved materials.
General fire hazards	No unusual fire or explosion hazards noted.		
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people low areas. Wear appropriate protective equipmen damaged containers or spilled material unless we adequate ventilation. Local authorities should be contained. For personal protection, see section 8	nt and clothing during cle earing appropriate protec advised if significant spil	an-up. Do not touch tive clothing. Ensur
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is wi possible. Cover with plastic sheet to prevent spre and place into containers. Prevent entry into wate Following product recovery, flush area with water	eading. Absorb in vermice erways, sewer, basement	ulite, dry sand or ea
	Small Spills: Wipe up with absorbent material (e. remove residual contamination.	g. cloth, fleece). Clean si	urface thoroughly to

Environmental precautionsNever return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Value Form Components Type Value Form Titanium Dioxide (CAS PEL 15 mg/m3 Total dust. 13463-67-7) Total dust. Total dust.

US. OSHA Table Z-3 (29 CF Components	R 1910.1000) Type	Value	Form
Silicate (CAS 14807-96-6)	TWA	0.3 mg/m3 0.1 mg/m3	Total dust. Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	o Chemical Hazards		
Components	Туре	Value	Form
Copper Phthalocyanine (CAS 147-14-8)	TWA	1 mg/m3	Dust and mist.
Silicate (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.
US. Workplace Environmer	tal Exposure Level (WEEL) Guides		
Components	Туре	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.
logical limit values	No biological exposure limits noted for	or the ingredient(s).	
propriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to mair exposure limits have not been establ	pplicable, use process enclosu tain airborne levels below reco	res, local exhaust ventilation mmended exposure limits. I
vidual protection measures	, such as personal protective equipm	ent	
Eye/face protection	If contact is likely, safety glasses with	n side shields are recommende	d.
Skin protection			
Hand protection	For prolonged or repeated skin conta	act use suitable protective glove	S.
Other	Wear suitable protective clothing.	1 0	
Respiratory protection	In case of insufficient ventilation, we	ar suitable respiratory equipmer	at
Thermal hazards	Wear appropriate thermal protective		п.
mermai nazarus			
eral hygiene siderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		
Physical and chemical	properties		
earance			
Physical state	Liquid.		
Form	Liquid.		
Color	Blue		
or	Not available.		

Not available.

Not available

Not available

Not available. Not available.

Evaporation rate

Melting point/freezing point

Initial boiling point and boiling

рΗ

range Flash point

Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	Not available	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Density	12.40 lbs/gal	
Percent volatile	53.94 %	
Specific gravity	1.49	
VOC	156.587613 g/l Regulatory estimated 84.883618 g/l Material estimated 1.306748 lbs/gal Regulatory estimated 0.708367 lbs/gal Material estimated	
10. Stability and reactivity		

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxical arisel off	a a ta

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Propylene Glycol (CAS 57-55-6)		
<u>Acute</u>		
Oral		
LD50	Guinea pig	18.4 g/kg

Components	Species	Test Results	
	Mouse	23.9 g/kg	
	Rabbit	18 g/kg	
	Rat	30 g/kg	
* Estimates for product may	be based on additional component data not shown.		
kin corrosion/irritation	Prolonged skin contact may cause temporary irrita	ation	
serious eye damage/eye ritation		Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitiz	zation.	
Germ cell mutagenicity	No data available to indicate product or any compo mutagenic or genotoxic.		
Carcinogenicity	Suspected of causing cancer.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
Titanium Dioxide (CAS 1		nogenic to humans.	
	ogram (NTP) Report on Carcinogens		
	UM OIL (CAS 64742-54-7) Known To Be Hun	8	
Reproductive toxicity	This product is not expected to cause reproductive	e or developmental effects.	
pecific target organ toxicity - ingle exposure	Not classified.		
Specific target organ toxicity - epeated exposure	Not classified.		
Aspiration hazard	Not available.		
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.		
12. Ecological informatio	n		
Ecotoxicity	The product is not classified as environmentally ha possibility that large or frequent spills can have a h		
Components	Species		
	Species	Test Results	
Propylene Glycol (CAS 57-55	-	Test Results	
Propylene Glycol (CAS 57-55 Aquatic	-	Test Results	
	-	> 10000 mg/l, 48 hours	
Aquatic	5-6)	> 10000 mg/l, 48 hours	
Aquatic Crustacea	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror	> 10000 mg/l, 48 hours	
Aquatic Crustacea Fish	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror	> 10000 mg/l, 48 hours	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror	> 10000 mg/l, 48 hours	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346 Aquatic	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7)	> 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346 Aquatic Crustacea Fish	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus	> 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours	
Aquatic Crustacea Fish Titanium Dioxide (CAS 13463 Aquatic Crustacea Fish * Estimates for product may 1	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours 	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346 Aquatic Crustacea Fish * Estimates for product may Persistence and degradability	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours 	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346 Aquatic Crustacea Fish * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa	5-6) EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Water flea (Daphnia magna) LC50 Mater flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus be based on additional component data not shown. No data is available on the degradability of this proceed nol / water (log Kow) Kow	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours 	
Aquatic Crustacea Fish Titanium Dioxide (CAS 13463 Aquatic Crustacea Fish * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Propylene Glycol	5-6) EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus be based on additional component data not shown. No data is available on the degradability of this pro- nol / water (log Kow) -0.92	> 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours	
Aquatic Crustacea Fish Titanium Dioxide (CAS 1346 Aquatic Crustacea Fish * Estimates for product may I Persistence and degradability Bioaccumulative potential Partition coefficient n-octa	5-6) EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus be based on additional component data not shown. No data is available on the degradability of this pro nol / water (log Kow) -0.92 No data available. -0.92 No other adverse environmental effects (e.g. ozon	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours oduct. 	
Aquatic Crustacea Fish Titanium Dioxide (CAS 13463 Aquatic Crustacea Fish * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Propylene Glycol Mobility in soil Dther adverse effects	5-6) EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus be based on additional component data not shown. No data is available on the degradability of this proc nol / water (log Kow) -0.92 No data available. No other adverse environmental effects (e.g. ozon potential, endocrine disruption, global warming potential)	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours oduct. 	
Aquatic Crustacea Fish Titanium Dioxide (CAS 13463 Aquatic Crustacea Fish * Estimates for product may Persistence and degradability Bioaccumulative potential Partition coefficient n-octa Propylene Glycol Mobility in soil	5-6) EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales pror 3-67-7) EC50 Water flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Muter flea (Daphnia magna) LC50 Mummichog (Fundulus heteroclitus be based on additional component data not shown. No data is available on the degradability of this proc nol / water (log Kow) -0.92 No data available. No other adverse environmental effects (e.g. ozon potential, endocrine disruption, global warming potential)	 > 10000 mg/l, 48 hours melas) 710 mg/l, 96 hours > 1000 mg/l, 48 hours s) > 1000 mg/l, 96 hours oduct. 	

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste
disposal company.Waste from residues / unused
productsDispose of in accordance with local regulations. Empty containers or liners may retain some
product residues. This material and its container must be disposed of in a safe manner (see:
Disposal instructions).Contaminated packagingEmpty containers should be taken to an approved waste handling site for recycling or disposal.
Since emptied containers may retain product residue, follow label warnings even after container is
emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper Phthalocyanine (CAS 147-14-8)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Hazard categories

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

Material name: STREETBOND COLORANT SAFE4TY BLUE

Silicate (CAS 14807-96-6) Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Silicate (CAS 14807-96-6) Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Copper Phthalocyanine (CAS 147-14-8) Propylene Glycol (CAS 57-55-6) Silicate (CAS 14807-96-6) Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Propylene Glycol (CAS 57-55-6) Silicate (CAS 14807-96-6) Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7)

Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-10-2014
Revision date	12-07-2015
Version #	10
HMIS® ratings	Health: 1* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 0 Flammability: 0 Instability: 0

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS