SAFETY DATA SHEET



1. Identification		
Product identifier	STREETBOND COLORANT W	HITE
Other means of identification		
Product Code		
Recommended use	Not available.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufacturer		
Company name	GAF	
	1 Campus Drive	
	Parsippany, NJ 07054 USA	
Telephone	1-800–766–3411	
Emergency phone number	CHEMTREC [DAY OR NIGHT]	1-800-424-9300
	Within USA and CANADA	1-800-424-9300
	Outside USA and Canada:	1 703-741-5970

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 2
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Warning
Hazard statement	Suspected of causing cancer.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Observe good industrial hygiene practices.
Response	If exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Titanium Dioxide		13463-67-7	60 to <70
Propylene Glycol		57-55-6	5 to <10
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Other components below reportable le	vels		20 to <30

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from
the chemicalDuring fire, gases hazardous to health may be formed.Special protective equipment
and precautions for firefightersSelf-contained breathing apparatus and full protective clothing must be worn in case of fire.Fire fighting
equipment/instructionsMove containers from fire area if you can do so without risk.Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.General fire hazardsNo unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. Workplace Environmen	tal Exposure Level (WEEL) Guides		
Components	Туре	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.
ological limit values	No biological exposure limits noted for	or the ingredient(s).	
	applicable, use process enclosures, maintain airborne levels below recon established, maintain airborne levels sufficient to maintain concentrations (OEL), suitable respiratory protection	nmended exposure limits. If ex to an acceptable level. If engin of dust particulates below the	posure limits have not been neering measures are not
dividual protection measures,	, such as personal protective equipm	ent	
Eye/face protection	If contact is likely, safety glasses with	n side shields are recommende	ed.
Skin protection			
Hand protection	For prolonged or repeated skin conta	act use suitable protective glove	es.
Other	Wear suitable protective clothing.		
Respiratory protection	If engineering controls do not mainta limits (where applicable) or to an acc been established), an approved resp if there is a risk of exposure to dust/fu	eptable level (in countries whe irator must be worn. Use a NIC	re exposure limits have not DSH/MSHA approved respira
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
eneral hygiene	When using, do not eat, drink or smo as washing after handling the materi	ke Always observe good pers	anal hygiana maasuras, suo

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Powder.
Color	Not available.
Odor	Not available.

Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-74.2 °F (-59 °C) estimated
Initial boiling point and boiling range	370.76 °F (188.2 °C) estimated
Flash point	210.0 °F (98.9 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.6 % estimated
Flammability limit - upper (%)	12.6 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	2784.25 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	700 °F (371.11 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	16.99 lbs/gal
Flammability class	Combustible IIIB estimated
Percent volatile	63 %
Specific gravity	2.04
VOC	307.30751 g/l Regulatory estimated 162.872936 g/l Material estimated 2.564529 lbs/gal Regulatory estimated 1.3592 lbs/gal Material estimated
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous	No dangerous reaction known under conditions of normal use.

No dangerous reaction known under conditions of normal use.
Keep away from heat, sparks and open flame. Avoid temperatures exceeding the flash point. Contact with incompatible materials. Minimize dust generation and accumulation.
Strong oxidizing agents.
No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Dust may irritate respiratory system. Prolonged inhalation may be harmful.
Skin contact	Dust or powder may irritate the skin.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.

Information on toxicological effects

.

Acute toxicity		
Components	Species	Test Results
Propylene Glycol (CAS 57-55-6)		
<u>Acute</u>		
Oral		
LD50	Guinea pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg
* Estimates for product may I	be based on additional compon	ent data not shown.
Skin corrosion/irritation	Prolonged skin contact may	cause temporary irritation.
Serious eye damage/eye rritation	Direct contact with eyes may	cause temporary irritation.
Respiratory or skin sensitization	n	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected	to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Suspected of causing cance	r.
IARC Monographs. Overall	Evaluation of Carcinogenicity	1
Not listed. US. National Toxicology Pr	ed Substances (29 CFR 1910. ogram (NTP) Report on Carci	nogens
Reproductive toxicity	UM OIL (CAS 64742-54-7) This product is not expected	Known To Be Human Carcinogen. to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - epeated exposure	Not classified.	
Aspiration hazard	Not available.	
Chronic effects	Prolonged inhalation may be	harmful. Prolonged exposure may cause chronic effects.
12. Ecological information	า	
Ecotoxicity		as environmentally hazardous. However, this does not exclude the ent spills can have a harmful or damaging effect on the environment
Components	Species	Test Results

57-55-6)		
EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
LC50	Fathead minnow (Pimephales promelas)	710 mg/l, 96 hours
13463-67-7)		
EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
	EC50 LC50 13463-67-7) EC50	EC50 Water flea (Daphnia magna) LC50 Fathead minnow (Pimephales promelas) 13463-67-7) EC50 Water flea (Daphnia magna)

* Estimates for product may be based on additional component data not shown. Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)		
Propylene Glycol	-0.92	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated.

Material name: STREETBOND COLORANT WHITE Version #: 07 Revision date: 12-07-2015 SDS 3225 Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Titanium Dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Titanium Dioxide (CAS 13463-67-7) US. New Jersey Worker and Community Right-to-Know Act

Propylene Glycol (CAS 57-55-6)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Propylene Glycol (CAS 57-55-6) Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7)	Listed: September 2, 2011
-----------------------------------	---------------------------

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Ri	co Toxic Substances Control Act (TSCA) Inventory	Yes
** ***		

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-04-2014
Revision date	12-07-2015
Version #	07
Further information	Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
HMIS® ratings	Health: 1* Flammability: 2 Physical hazard: 0
NFPA ratings	Health: 0 Flammability: 2 Instability: 0

Disclaimer

This information relates to the specific material designated and may not be valid for such material used on combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

Revision Information

Product and Company Identification: Converted to GAF SDS