# SAFETY DATA SHEET



## 1. Identification

Product identifier STREETBOND SB120 PAVEMENT COATING PART A

Other means of identification

**Product Code** 

Recommended use Not available.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GAF

1 Campus Drive

Parsippany, NJ 07054 USA

**Telephone** 1-800–766–3411

Emergency phone number CHEMTREC [DAY OR NIGHT] 1-800-424-9300

Within USA and CANADA 1-800-424-9300
Outside USA and Canada: 1 703-741-5970

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Crystalline Silica		14808-60-7	60 to <70
PARAFFINIC PETROLEUM OIL		64742-54-7	0.1 to <1
Non-Hazardous Ingredients			30 to <40

# 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop orpersist.

Material name: STREETBOND SB120 PAVEMENT COATING PART A Version #: 07 Revision date: 11-24-2015

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important

symptoms/effects, acute and

delayed

Irritation of eyes and mucous membranes. Coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

**General information** 

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

During fire, gases hazardous to health may be formed.

General fire hazards No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form	
Crystalline Silica (CAS 14808-60-7)	TWA	0.3 mg/m3 0.1 mg/m3	Total dust. Respirable.	
		2.4 mppcf	Respirable.	

Material name: STREETBOND SB120 PAVEMENT COATING PART A Version #: 07 Revision date: 11-24-2015

US. ACGIH Threshold Limit Values					
Components	Туре	Value	Form		
Crystalline Silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.		
PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.		
US. NIOSH: Pocket Guide to Chen	nical Hazards				
Components	Туре	Value	Form		
Crystalline Silica (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.		

**Biological limit values** No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

For prolonged or repeated skin contact use suitable protective gloves. Hand protection

Other Wear suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Liquid. Physical state **Form** Liquid. Not available. Color

Not available. Odor Odor threshold Not available. Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling range

Not available. Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

**Explosive limit - lower (%)** Not available. Not available. Explosive limit - upper (%)

Vapor pressure Not available. Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Viscosity

Other information

Density 14.00 lbs/gal Percent volatile 42.62 % 1.68 Specific gravity

VOC 17.27637 g/l Regulatory estimated

> 0.144174 lbs/gal Regulatory estimated 10.105623 g/l Material estimated 0.084333 lbs/gal Material estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Powerful oxidizers. Chlorine. Incompatible materials

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

## 11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

No adverse effects due to skin contact are expected. Skin contact Direct contact with eyes may cause temporary irritation. Eye contact

Expected to be a low ingestion hazard. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Irritation of eyes and mucous membranes. Coughing.

Information on toxicological effects

Not available. **Acute toxicity** 

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Not available. Respiratory sensitization

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline Silica (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline Silica (CAS 14808-60-7) Known To Be Human Carcinogen. PARAFFINIC PETROLEUM OIL (CAS 64742-54-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

Material name: STREETBOND SB120 PAVEMENT COATING PART A

Version #: 07 Revision date: 11-24-2015 SDS 3073

Not available. **Aspiration hazard** 

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Test Results** Product **Species** 

STREETBOND 120 PT-A

Aquatic

LC50 Fish Fish 18890.5781 mg/l, 96 hours estimated

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions** 

contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

the IBC Code

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: STREETBOND SB120 PAVEMENT COATING PART A Version #: 07 Revision date: 11-24-2015

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

### **US state regulations**

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Crystalline Silica (CAS 14808-60-7)

PARAFFINIC PETROLEUM OIL (CAS 64742-54-7)

#### **US. Massachusetts RTK - Substance List**

Crystalline Silica (CAS 14808-60-7)

# US. New Jersey Worker and Community Right-to-Know Act

Crystalline Silica (CAS 14808-60-7)

### US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline Silica (CAS 14808-60-7)

#### **US. Rhode Island RTK**

Not regulated.

### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline Silica (CAS 14808-60-7) Listed: October 1, 1988

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Material name: STREETBOND SB120 PAVEMENT COATING PART A Version #: 07 Revision date: 11-24-2015 SDS 3073

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 10-14-2014 **Revision date** 11-24-2015

Version # 07

HMIS® ratings Health: 1\*

Flammability: 0 Physical hazard: 0

NFPA ratings Health: 0

Flammability: 0 Instability: 0

**Disclaimer** This information relates to the specific material designated and may not be valid for such material

used on combination with any other materials or in any process. Such information is to the best of

our knowledge and belief accurate and reliable as of the date compiled. However, no

representation, warranty or guarantee, expressed or implied, is made as to its accuracy, reliability, or completeness. GAF cannot anticipate all conditions under which this information and product, or the products of other manufacturers in combination with this product, may be used. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license of valid patents.

**Revision Information** Product and Company Identification: Converted to GAF SDS

Material name: STREETBOND SB120 PAVEMENT COATING PART A

Version #: 07 Revision date: 11-24-2015