LayerLock™ Technology



Reinforcing the Common Bond

The new LayerLock™ Technology powers the industry's widest nailing zone and the first wind warranty with no maximum wind speed limitation.¹



LayerLock™ Technology

Benefits:

- Timberline® Shingles with LayerLock™ Technology are engineered for the best possible installation.
- LayerLock™ Technology mechanically fuses the common bond between overlapping shingle layers.
- Our legendary Dura Grip[™] sealant pairs with the smooth microgranule surface of the StrikeZone[™] nailing area for fast tack. Then, an asphaltto-asphalt monolithic bond cures for durability, strength, and exceptional wind uplift performance.
- The added strength at the common bond powers the StrikeZone[™] —
 The industry's widest nailing area.


- Up to 99.9% nailing accuracy The StrikeZone™ nailing area is so easy to hit that a roofer placed 999 out of 1,000 nails correctly in our tests.²
- Up to 30% faster nail fastening thanks to the industry's largest nail zone.²
- WindProven™ Limited Wind Warranty — When installed with the required combination of GAF Accessories, Timberline® Shingles with LayerLock™ Technology are eligible for an industry first: a wind warranty with no maximum wind speed limitation.¹

LayerLock™ TechnologyPowers the industry's widest nailing zone



Beautiful finished lookIt's the same Timberline® Shingle you know and love, now even better

Product details:



- 1. Alignment guide
- 2. StrikeZone™ Nailing Area
- Dura Grip[™] Adhesive
- **4.** LayerLock[™] Technology
- **5.** Smooth microgranule surface
- ¹ 15-year WindProven™ limited wind warranty on Timberline® Shingles with LayerLock™ Technology requires the use of GAF starter strips, roof deck protection, ridge cap shingles, and leak barrier or attitic ventilation. See GAF Roofing System Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products.
- ² Results based on study conducted by Home Innovation Research Labs, on independent research lab, comparing installation of Timberline HD® Shingles to Timberline® HDZ™ Shingles on a 16-square roof deck using standard 4-nail nailing pattern under controlled laboratory conditions. Actual results may vary.



