

WeatherBlocker[®] Premium Starter Strip Shingles

Help prevent shingle blow-off and reduce waste



- A cost-effective alternative to using cut-up 3-tab shingles as the starter course
- Made with a high-quality, factory-applied adhesive that will tightly lock your shingles in place
- Specifically designed to be compatible with all GAF shingles




WeatherBlocker[™] Premium Starter Strip Shingles

Benefits:

- Properly positioned Dura Grip™
 Adhesive helps to lock down the roof edges at the eaves and rakes to reduce the risk of shingle blow-off
- Pre-perforated design is easy to use and install, with no cutting on the roof
- No more wasted time (or material) cutting your own starter strips
- Straighter roof edges with no messy black cement

- At least 42% more coverage per bundle (versus typical 3-tab shingles)
- GAF offers increased wind coverage on many GAF shingles when you use GAF starter strip shingles and follow special installation instructions[†]
- Eligible for up to a Lifetimet limited warranty when installed on Lifetimet Shingle roofs. They're also an eligible accessory product in the Starter Strip Category of GAF residential enhanced warranties.


Installation:



3-Tab & Laminate Shingles: When up to an 8.5" (216 mm) width starter strip meets the need, simply tear the starter shingle in half along the perforations



Designer & Extra-Large Shingles: When up to a 17" (432 mm) width starter strip meets the need, simply install the entire starter shingle



Product details:

For use with all asphalt shingles

- **Full sheet:** 17" x 40" (432 x 1,016 mm)
- Half sheet: 8.5" x 40" (216 x 1,016 mm)

Packaging:

 Bundle count: 15 pieces (full sheet), 30 pieces (half sheet)

Coverage:

- 100 lineal ft. (31 lm) per bundle when used as half sheets
- 50 lineal ft. (15 lm) per bundle when used as full sheets

Code Approvals:

- State of Florida Approved
 Miami-Dade County Product Control approved
- Control approved ICC-ES ESR-1475
- ICC-ES ESR-14/5
 ASTM D3462¹
- ASTM D3462
 ASTM D3018
- ASTM D3018
 ASTM D3161 Class F
- UL Listed to ANSI/UL 790 Class A²

[†] Lifetime refers to the length of warranty coverage provided and means as long as the original individual owner(s) of a single-family detached residence [or eligible second owner(s)] owns the property where the qualifying GAF products are installed. For other owners/structures, Lifetime coverage is not applicable. Lifetime coverage on shingles requires the use of GAF Lifetime Shingles only. See the GAF Shingle & Accessory Limited Warranty for complete coverage and restrictions. Visit gaf.com/LRS for qualifying GAF products. Lifetime Shingle and at least 3 qualifying GAF Accessories. See the GAF Roofing System Limited Warranty for complete coverage and restrictions. For installations not eligible for the GAF Roofing System Limited Warranty, see the GAF Shingle & Accessory Limited Warranty. Visit gaf.com/LRS for qualifying GAF products.

 Periodically tested by independent and internal labs to ensure compliance with ASTM D3462 at time of manufacture.
 Refer to UL Online Certification Directory for actual assemblies.



To learn more about the Lifetime Roofing System visit **gaf.com/Lifetime**



