

Specially designed to replicate the look of old asbestos siding



- Virtually identical in size and shape to many old asbestos siding shingles that are no longer available
- WeatherSide[™] Fiber-Cement Siding contains NO asbestos
- Great for siding small additions, changing windows, or for making small repairs without the hassles and expense of installing new siding on the entire house




WeatherSide[™] Fiber-Cement Siding

Benefits:

- Distinct design, unavailable in other siding products, helps to closely replicate the look of older, no-longeravailable asbestos siding
- After properly removing and disposing of the old siding in accordance with local, state, and federal regulations regarding asbestos-containing products², simply nail in place and paint
- Unlike some other fiber-cement siding products, no caulking is required at the joints
- Pre-primed from the factory and ready to paint the color of your choice

Siding Shingle Selector:



Wavy, or Thatched edge.

Approx.

Exposure

Thickness

Pcs./Bundle

Bundles/Sq.

Sq./Pallet

Lb./Sq.

Specs

Size

Purity

11 in

18

3

20

168

¹¹⁄₆₄ in.

Straight"/Wavy

12 in. x 24 in.

 Purity Shingle
 Em

 Textured surface with Straight,
 Exd

Purity

10 ½ in

¹‰ in.

19


3

20

186

Thatched"

12 in. x 24 in.



Emphasis[™] Shingle Extra-thick wood grain look with Thatched edge.

Emphasis[™]

13 in.

%32 in.


11

Δ

10

268

14 ⁵/₈ in. x 25 ⁵/₃₂ in.



Profile[™] Shingle

Straight edge.

Profile[™] 9

9 x 32 in

8 in

19

3

15

177

¹¹⁄⁄₆₄ in.

Striated surface with

Profile[™] 12

12 x 24 in.

11 in.

18

3

20

165

¹¹⁄⁄₆₄ in.

Profile[™] 14

13 ⁵/₈ in.

¹¹⁄₆₄ in.

11

3

15

171

14⁵/₈ in. x 32 in.

Durable fiber-cement construction

helps resist warping, rotting,

expansion/contraction, UV

- with ASTM E136Backed by a **25-year**
- limited warranty¹



Product Details:

Siding Standards & Code Approvals:

- UL Classified to ANSI/UL723
- ASTM E136 non-combustible
- Meets or exceeds ASTM C1186
- State of Florida approved
- Meets or exceeds the requirements of the Texas Department of Insurance (excludes Profile[™] 14)
- Miami-Dade County Product Control Approved (excludes Emphasis[™] and Profile[™] 14)

Matching Accessories:

WeatherSide[™] Fiber-Cement Siding accessories offer faster, easier, more accurate installation, and include:





1¾" Hot-Dipped Galvanized Siding Nails

Backer Strips (9", 12", and 14")



Individual Pre-Primed Corners with Woodgrain Surface (9", 12", 14", and Emphasis™)



Visit gaf.com/WeatherSide

 See WeatherSide[™] Fiber-Cement Siding Limited Warranty for complete coverage and limitations.
 If your project involves the handling, removal, and/or disposal of asbestos-containing products, always use a licensed asbestos-abatement professional. C/A