

## 1 Identification

### Product identifier

Trade name: ***Bridgemaster Resin***

SDS ID Number: 80044

Relevant identified uses of the substance or mixture, and uses advised against: Waterproofing.

### Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

GCP Applied Technologies  
62 Whittemore Avenue  
Cambridge, MA 02140 USA

GCP Canada, Inc.  
294 Clements Road W.  
Ajax, Ontario L1S 3C6 Canada

#### Information department:

Environmental Health & Safety  
USA: +1-617-876-1400 (24 hours)  
+1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts  
CAN: 1-905-683-8561 (24 hours)  
Email address: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

## 2 Hazard(s) identification

### Classification of the substance or mixture

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of causing cancer.  
May cause respiratory irritation.

**Label elements:** The product is classified and labeled according to the Globally Harmonized System (GHS)

#### Hazard pictograms



Danger

#### Hazard statements

Highly flammable liquid and vapor.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
Suspected of causing cancer.  
May cause respiratory irritation.

#### Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Take precautionary measures against static discharge.

## Safety Data Sheet

Printing date 08/27/2019

Version Number 1.0

Reviewed on 08/27/2019

**Trade name:** *Bridgemaster Resin*

(Cont. from page 1)

Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.

**Hazard description:** Flammable**NFPA ratings (scale 0 - 4)**

Health = 2  
 Fire = 3  
 Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = \*2  
 Flammability = 3  
 Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**3 Composition/information on ingredients****Chemical characterization: Mixture****Description:** Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.**Hazardous components:**

80-62-6	Methyl methacrylate	22-<30%
97-88-1	n-butyl methacrylate	22-<30%
99-97-8	N,N-dimethyl-p-toluidine	0.1-<1%

**Additional information:** Non-hazardous ingredients may be listed in Section 15; Right-To-Know disclosure.**4 First-aid measures****Description of first aid measures****General information:** Get medical advice/attention if you feel unwell.**After inhalation:** IF INHALED: Remove person to fresh air and keep comfortable for breathing.**After skin contact:**

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

**After eye contact:** Rinse cautiously with water for several minutes.**After swallowing:**

Rinse mouth.

Do NOT induce vomiting.

(Cont. on page 3)

USGHS

**Trade name:** *Bridgemaster Resin*

(Cont. from page 2)

### Information for doctor:

#### Most important symptoms and effects, both acute and delayed

Allergic reactions

Irritating to eyes.

**Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## 5 Fire-fighting measures

### Extinguishing media

**Suitable extinguishing agents:** CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture** No further relevant information available.

### Advice for firefighters

**Protective equipment:** Wear personal protective equipment.

**Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

## 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

### Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13 of the SDS.

### Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

### Handling:

#### Precautions for safe handling

Prevent formation of aerosols.

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Avoid contact with eyes.

Do not eat, drink or smoke when using this product.

Store in a well ventilated place. Keep container tightly closed.

Use only outdoors or in a well-ventilated area.

(Cont. on page 4)

**Trade name:** *Bridgemaster Resin*

(Cont. from page 3)

**Information about protection against explosions and fires:**



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Empty containers may retain hazardous residue, both liquid and vapor.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ground/bond container and receiving equipment.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** Store in a cool location.

**Information about storage in one common storage facility:** Keep respirator available.

**Further information about storage conditions:**

Protect from frost.

Store in a dry place.

Keep receptacle tightly sealed.

Keep cool.

**Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**Additional information about design of technical systems:** No further data; see item 7.

### Control parameters

**Components with limit values that require monitoring at the workplace:**

**80-62-6 Methyl methacrylate**

PEL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 410 mg/m <sup>3</sup> , 100 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm DSEN

**99-97-8 N,N-dimethyl-p-toluidine**

WEEL (USA)	Long-term value: 0.5 ppm
------------	--------------------------

**Additional information:** The lists that were valid during the creation were used as basis.

### Exposure controls

**Personal protective equipment:**

**General protective and hygienic measures:** The usual precautionary measures for handling chemicals should be followed.

**Breathing equipment:**

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

**Protection of hands:** Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

(Cont. on page 5)

## Safety Data Sheet

Printing date 08/27/2019

Version Number 1.0

Reviewed on 08/27/2019

Trade name: *Bridgemaster Resin*

(Cont. from page 4)

**Material of gloves** Rubber or other impervious gloves should be worn to prevent skin contact.

**Eye protection:**



Safety glasses with side shield protection.

**Body protection:**

Use personal protective equipment as required.

Take off contaminated clothing.

## 9 Physical and chemical properties

### Information on basic physical and chemical properties

#### General Information

**Appearance:**

<b>Form:</b>	Viscous liquid
<b>Color:</b>	Various colors
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

**pH-value (~):** Not determined.

#### Change in condition

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	~100 °C (~212 °F)
<b>Flash point:</b>	~17 °C (~62.6 °F)

**Flammability (solid, gaseous):** Not applicable.

**Ignition temperature:** ~430 °C (~806 °F)

**Decomposition temperature:** Not determined.

**Auto igniting:** Not determined.

**Danger of explosion:** In use, may form flammable/explosive vapor-air mixture.

#### Explosion limits:

<b>Lower:</b>	2 Vol %
<b>Upper:</b>	13 Vol %
<b>VOC Content (max):</b>	Not determined.

**Vapor pressure:** Not determined.

**Density: (~)** Not determined.

**Vapor density** Not determined.

**Evaporation rate** Not determined.

#### Solubility in / Miscibility with

**Water:** Not miscible or difficult to mix.

**Partition coefficient (n-octanol/water):** Not determined.

#### Viscosity:

**Dynamic at 20 °C (68 °F):** 90-250 P

**Kinematic:** Not determined.

**Molecular weight** Not applicable.

#### Other information

No further relevant information available.

## 10 Stability and reactivity

**Reactivity** Will exothermically polymerize in the presence of initiators.

(Cont. on page 6)

USGHS

## Safety Data Sheet

Printing date 08/27/2019

Version Number 1.0

Reviewed on 08/27/2019

Trade name: *Bridgemaster Resin*

(Cont. from page 5)

**Chemical stability** Stable in the presence of inhibitor.**Thermal decomposition:** No decomposition if used according to specifications.**Possibility of hazardous reactions**

Susceptible to polymerization initiated by prolonged storage or the presence of catalyst.

**Conditions to avoid** Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Incompatible materials:**

Polymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

**Hazardous decomposition products:** Carbon monoxide and carbon dioxide**11 Toxicological information****Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****97-88-1 n-butyl methacrylate**

Dermal	LD50	22,600 mg/kg (rat)
	LD50	11,300 mg/kg (rabbit)
Inhalation	LC50, 4h	4,910 mg/l (rat)

**Primary irritant effect:****on the skin:** Causes skin irritation.**on the eye:** Causes serious eye irritation.**inhalation:** May cause respiratory irritation.**Sensitization:** May cause an allergic skin reaction.**Additional toxicological information:** Suspected of causing cancer.**Carcinogenic categories****IARC (International Agency for Research on Cancer) Human Carcinogenicity:**  
Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

80-62-6	Methyl methacrylate	3
99-97-8	N,N-dimethyl-p-toluidine	2B

**NTP (National Toxicology Program)****K–Known to be carcinogenic, R–May reasonably be anticipated to be carcinogenic**

None of the ingredients are listed.

**OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients are listed.

**12 Ecological information****Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.

(Cont. on page 7)

USGHS

Trade name: *Bridgemaster Resin*

(Cont. from page 6)

**Additional ecological information:**

**General notes:** Not known to be hazardous to water.

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**Other adverse effects** No further relevant information available.

**13 Disposal considerations****Disposal methods:**

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing product for disposal. Dispose of waste in accordance with all applicable regulations.

**Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packagings:**

**Recommendation:** Dispose of contents/container in accordance with local/regional/national/international regulations.

**14 Transport information****UN-Number**

DOT, IMDG, IATA UN1866

**UN proper shipping name**

DOT Resin solution  
IMDG, IATA RESIN SOLUTION

**Transport hazard class(es)**

DOT



Class 3 Flammable liquids  
Label 3

IMDG, IATA



Class 3 Flammable liquids  
Label 3

**Packing group**

DOT, IMDG, IATA II

**Environmental hazards:** Not applicable.

**Special precautions for user** Warning: Flammable liquids

(Cont. on page 8)

## Safety Data Sheet

Printing date 08/27/2019

Version Number 1.0

Reviewed on 08/27/2019

Trade name: *Bridgemaster Resin*

(Cont. from page 7)

**Danger code (Kemler):** 33  
**EMS Number:** F-E,S-E  
**Stowage Category** A

**Transport/Additional information:****IMDG**

**Limited quantities (LQ)** 5L  
**Excepted quantities (EQ)** Code: E2  
 Maximum net quantity per inner packaging: 30 ml  
 Maximum net quantity per outer packaging: 500 ml

**15 Regulatory information****SARA (Superfund Amendments and Reauthorization Act)****Section 302/304 (extremely hazardous substances):**

None of the ingredients is listed.

**Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):**

80-62-6	Methyl methacrylate	29.7%
---------	---------------------	-------

**SARA Section 312/Tier I & II Hazard Categories:**

Physical Hazard - Flammable (gases, aerosols, liquids, or solids)  
 Health Hazard - Carcinogenicity  
 Health Hazard - Skin Corrosion or Irritation  
 Health Hazard - Respiratory or Skin Sensitization  
 Health Hazard - Serious eye damage or eye irritation  
 Health Hazard - Specific target organ toxicity (single or repeated exposure)

**North America Chemical Inventory Status****TSCA (Toxic Substances Control Act - United States):**

All ingredients are listed or exempt from listing unless otherwise noted below.

**CEPA (Canadian DSL):**

All ingredients are listed or exempt from listing unless otherwise noted below.

**Right to Know Ingredient Disclosure:**

Proprietary Polyurethane Polymer - NJTSN801416143

**California Proposition 65: (Substances <0.1% unless noted in Section 3)****Chemicals known to cause cancer:**

di-"isononyl" phthalate  
 N,N-dimethyl-p-toluidine

**Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

**Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

**Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

**Carcinogenicity Categories****TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists)****Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable**

Methyl methacrylate	A4
---------------------	----

**NIOSH-Cancer (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

**Volatile Organic Compounds (VOC) reported per the Emission Standards. 40 g/L**



## Safety Data Sheet

Printing date 08/27/2019

Version Number 1.0

Reviewed on 08/27/2019

**Trade name: *Bridgemaster Resin***

(Cont. from page 8)

**16 Other information**

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

**Department issuing SDS:**

GCP Applied Technologies  
62 Whittemore Avenue  
Cambridge, MA 02140 USA  
USA: +1-617-876-1400 (24 hours)  
+1-800-354-5414

**The first date of preparation** 08/27/2019**Number of revision times and the latest revision date** 1.0 / 08/27/2019

USGHS