gcp

SAFETY DATA SHEET

1. Identification

Product identifier Bituthene Liquid Membrane Part A

Other means of identification

Product Identifier 60025

Synonyms Detail Liquid

Recommended use Construction materials.

Recommended restrictions No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GCP Applied Technologies

Address 20 Moores Rd.

Malvern, PA 19355 United States

Telephone +1 866-333-3726 E-mail Not available.

Emergency phone number 3E Global Incident Hotline

1 760 476 3962

1 866 519 4752 (Toll Free) Access Code: 336250

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Category 1A

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Extracts (petroleum), heavy paraffinic distillate solvent		64742-04-7	15 - 40
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-TERMINATED		69102-90-5	10 - 30

Material name: Bituthene Liquid Membrane Part A 6681 Version #: 01 | Issue date: 03-26-2024

Chemical name	Common name and synonyms	CAS number	%
Asphalt		8052-42-4	10 - 30
precipitated silica (amorphous)		7631-86-9	7 - 13
Glycerol, propoxylated		25791-96-2	3 - 7

Composition comments

The exact concentrations of the above listed chemicals are being withheld as a trade secret. All concentrations are in percent by weight.

4. First-aid measures

Inhalation Move t

Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Most important

symptoms/effects, acute and

delayed

Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in closed original container in a dry place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components		Type			Value	Form
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)		PEL			5 mg/m3	Mist.
US. OSHA Table Z-3 Permis Components		Limit Type	s (PEL) for Miner	al Dusts (29	CFR 1910.1000) Value	Form
precipitated silica (amorphous) (CAS 7631-86-9)		TWA			5 mg/m3	Respirable fraction.
					15 mg/m3	Total dust.
					0.8 mg/m3	
US. ACGIH Threshold Limit	Values (TLV)					
Components		Туре			Value	Form
Asphalt (CAS 8052-42-4)		TWA			0.5 mg/m3	Inhalable fume.
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)		TWA			5 mg/m3	Inhalable fraction.
NIOSH. Immediately Danger			(IDLH) Values, as	amended	Malaa	
Components		Туре			Value	
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)		IDLH			2500 mg/m3	
precipitated silica (amorphous) (CAS 7631-86-9)		IDLH			3000 mg/m3	
US. NIOSH: Pocket Guide to			Recommended Ex	posure Lim		_
Components		Type			Value	Form
Asphalt (CAS 8052-42-4)		Ceilin	g		5 mg/m3	Fume.
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)		STEL			10 mg/m3	Mist.
		TWA			5 mg/m3	Mist.
precipitated silica (amorphous) (CAS 7631-86-9)		TWA			6 mg/m3	
ogical limit values						
ACGIH Biological Exposure	Indices (BEI)					
Components V	alue		Determinant	Specimer	Sampling T	ïme
Asphalt (CAS 8052-42-4) 2	.5 μg/l		1-Hydroxypyre ne, with hydrolysis (1-HP)	Urine	*	
* - For sampling details, pleas	e see the source	e docı	ıment.			
ropriate engineering trols	applicable, use maintain airbo	e proc rne le	ess enclosures, lo	cal exhaust v nended expo	entilation, or other sure limits. If expo	matched to conditions. I r engineering controls to sure limits have not bee
vidual protection measures, Eye/face protection	-	_	otective equipme with side shields			
Skin protection Hand protection	Chemical resis	stant g	lloves.			
Other	Wear suitable	prote	ctive clothing. Use	of an imperv	ious apron is reco	mmended.
Respiratory protection	Use a NIOSH/	MSH/	A approved respira	tor if there is	a risk of exposure	to dust/fume at levels
, , , , , , , , , , , , , , , , , , ,	exceeding the				•	

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormSemi-solid.ColorBlack.

Odor Characteristic.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not miscible.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Particle size Varies.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materialsChlorine. Fluorine.Hazardous decompositionCarbon oxides.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Material name: Bituthene Liquid Membrane Part A 6681 Version #: 01 Issue date: 03-26-2024

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Asphalt (CAS 8052-42-4)

<u>Acute</u> Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

precipitated silica (amorphous) (CAS 7631-86-9)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritation

Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye

Due to partial or complete lack of data the classification is not possible.

irritation

Respiratory or skin sensitization

Respiratory sensitization

Skin sensitization

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt (CAS 8052-42-4) 2B Possibly carcinogenic to humans.

Extracts (petroleum), heavy paraffinic distillate solvent 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-04-7)

precipitated silica (amorphous) (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Asphalt (CAS 8052-42-4) Known To Be Human Carcinogen.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible. **Specific target organ toxicity -**Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Material name: Bituthene Liquid Membrane Part A 6681 Version #: 01 Issue date: 03-26-2024

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard categories

Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Asphalt (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Asphalt (CAS 8052-42-4)

Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)

California Proposition 65



WARNING: This product can expose you to Asphalt, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Asphalt (CAS 8052-42-4) Listed: January 1, 1990

International Inventories

Taiwan

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Taiwan Chemical Substance Inventory (TCSI)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 03-26-2024

Version # 01

United States & Puerto Rico

Disclaimer GCP Applied Technologies cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: Bituthene Liquid Membrane Part A 6681 Version #: 01 Issue date: 03-26-2024

Yes

Yes

gcp

SAFETY DATA SHEET

1. Identification

Product identifier Bituthene Liquid Membrane Part B

Other means of identification

Product Identifier 583

Synonyms Detail Liquid.

Recommended useConstruction materials.

Recommended restrictions

No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GCP Applied Technologies

Address 20 Moores Rd.

Malvern, PA 19355 United States

Telephone +1 866-333-3726 E-mail Not available.

Emergency phone number 3E Global Incident Hotline

1 760 476 3962

1 866 519 4752 (Toll Free) Access Code: 336250

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

Skin corrosion/irritation

Serious eye damage/eye irritation

Category 2

Sensitization, respiratory

Category 1

Sensitization, skin

Category 1

Carcinogenicity

Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful

if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe mist/vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate

ventilation wear respiratory protection.

If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable Response

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison

center/doctor. Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. **Storage**

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Hydrocarbons, C9-unsaturated, polymerized		71302-83-5	15 - 40
4 4'-Methylenediphenyl diisocyanate		101-68-8	10 - 30
Methylenediphenyl diisocyanate (MDI)		26447-40-5	10 - 30
Methylenediphenyl diisocyanate, homopolymer		39310-05-9	10 - 30
Triethyl phosphate		78-40-0	0.5 - 1.5

Composition comments

The exact concentrations of the above listed chemicals are being withheld as a trade secret. All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. If experiencing respiratory symptoms: Call a poison center or doctor/physician.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Type	Contaminants (29 CFR 1910.1000) Value	
4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m3	
		0.02 ppm	
US. ACGIH Threshold Limit Valu	es (TLV)		
Components	Туре	Value	
4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)	TWA	0.005 ppm	
NIOSH. Immediately Dangerous	to Life or Health (IDLH) Values,	as amended	
Components	Туре	Value	
4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)	IDLH	75 mg/m3	
US. NIOSH: Pocket Guide to Che	mical Hazards Recommended I	·	
Components	Туре	Value	
4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)	Ceiling	0.2 mg/m3	
		0.02 ppm	
	TWA	0.05 mg/m3	
		0.005 ppm	
US. OARS. Workplace Environm	ental Exposure Level (WEEL) G	uide	
Components	Type	Value	
Triethyl phosphate (CAS 78-40-0)	TWA	7.45 mg/m3	
,			

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Recommended: Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Liquid. Physical state **Form** Liquid. Color Clear.

Odor Characteristic. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available. Relative density Not available.

Solubility(ies)

Not miscible. Solubility (water) Partition coefficient Not available. (n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials
Hazardous decomposition

None known.
Carbon oxides.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)

Acute Inhalation

LC50 Rat 369 mg/m3, 4 Hours

Triethyl phosphate (CAS 78-40-0)

<u>Acute</u>

Dermal

LD50 Rabbit > 20 g/kg

Inhalation

LC50 Rat > 8817 mg/m3, 4 Hours

Oral

LD50 Rat 1.6 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8) 3 Not classifiable as to carcinogenicity to humans. Methylenediphenyl diisocyanate (MDI) (CAS 26447-40-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Triethyl phosphate (CAS 78-40-0)

Aquatic Acute

Fish LC50 Fathead minnow (Pimephales promelas) > 100 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

4 4'-Methylenediphenyl diisocyanate 5.22
Triethyl phosphate 0.8

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Methylenediphenyl

diisocyanate (MDI))

Transport hazard class(es)

Class 9
Subsidiary hazard Packing group III

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

TSCA Chemical Action Plans, Chemicals of Concern

4 4'-Methylenediphenyl diisocyanate

(CAS 101-68-8)

Methylenediphenyl diisocyanate (MDI)

(CAS 26447-40-5)

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds

Action Plan [RIN 2070-ZA15]

Methylene Diphenyl Diisocyanate (MDI) And Related Compounds

Action Plan [RIN 2070-ZA15]

CERCLA Hazardous Substance List (40 CFR 302.4)

4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
4 4'-Methylenediphenyl diisocyanate	101-68-8	10 - 30	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4 4'-Methylenediphenyl diisocyanate (CAS 101-68-8) Methylenediphenyl diisocyanate (MDI) (CAS 26447-40-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 03-26-2024

Version # 01

Disclaimer GCP Applied Technologies cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Material name: Bituthene Liquid Membrane Part B 6682 Version #: 01 Issue date: 03-26-2024