



Printing date 03/30/2018 Version Number 1.4 Reviewed on 03/27/2017

1 Identification

Product identifier

Trade name: Flex SLV PURe

SDS ID Number: 2459

Relevant identified uses of the substance or mixture, and uses advised against:

Waterproofing

Specialty construction product. Not intended for other uses.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GCP Applied Technologies 62 Whittemore Avenue Cambridge, MA 02140 USA

GCP Canada, Inc. 294 Clements Road W.

Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours)

+1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts

CAN: 1-905-683-8561 (24 hours) Email address: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Label elements:

Hazard pictograms





GHS07 GHS08

Danger

Hazard statements

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

(Cont. on page 2)

(Cont. from page 1)

Safety Data Sheet

Printing date 03/30/2018 Version Number 1.4 Reviewed on 03/27/2017

Trade name: Flex SLV PURe

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 0

HMIS-ratings (scale 0 - 4)



Health = *2 Flammability = 1 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture

Description: Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.

Hozondona	components:

Huzur dous components.			
26447-40-5	Methylenediphenyl diisocyanate, mixture of isomers	20-25%	
101-68-8	Diphenylmethane-4,4'-di-isocyanate	1.0-2.0%	

Additional information: Non-hazardous ingredients may be listed in Section 15; Right-To-Know disclosure.

4 First-aid measures

Description of first aid measures

General information: Get medical advice/attention if you feel unwell.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

After eye contact:

Rinse opened eye for several minutes under running water.

(Cont. on page 3)

Trade name: Flex SLV PURe

(Cont. from page 2)

Rinse cautiously with water for several minutes.

Seek immediate medical advice.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Immediately call a doctor.

Information for doctor:

Most important symptoms and effects, both acute and delayed

Irritating to eyes.
Allergic reactions

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Special hazards arising from the substance or mixture No further relevant information available.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Methods and material for containment and cleaning up:

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.

Sweep up spilled product into receptacles.

Dispose contaminated material as waste according to section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Avoid contact with skin.

Open and handle receptacle with care.

Prevent formation of aerosols.

Avoid contact with eyes.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Information about storage in one common storage facility: No special measures required.

(Cont. on page 4

Trade name: Flex SLV PURe

(Cont. from page 3)

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

101-68-8 Diphenylmethane-4,4'-di-isocyanate

PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm
	Ceiling limit value: 0.2* mg/m³, 0.02* ppm
	*10-min
TLV (USA)	Long-term value: 0.051 mg/m ³ , 0.005 ppm

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Avoid contact with the eyes and skin.

The usual precautionary measures for handling chemicals should be followed.

Breathing equipment:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Due to the presence of isocyanate, supplied air respirators must be worn whenever the product is applied in poorly ventilated areas unless local exhaust will maintain exposures below acceptable limits. A chemical cartridge respirator with organic vapor cartridge is required when local exhaust is unavailable or inadequate to control exposures below required limits. When supplied-air respirators are not available or use is not practical, an air-purifying respirator may be an acceptable alternative if the recommendations below are followed:

Use of fans to improve air circulation and general ventilation or exhaust ventilation to remove isocyanate vapors when working in confined spaces.

The use of an air-purifying respirator fitted with organic vapor cartridge and a well managed cartridge change schedule. Due to the low exposure limits and poor odor warning properties, cartridges should be replaced on a daily basis at a minimum. To complement the above, a viable isocyanate measurement system should be used to monitor workplace levels.

Protection of hands: Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eye protection:



Safety glasses with side shield protection.

Safety glasses with side shields should be worn to prevent contact due to splashing. Under high vapor mist concentrations, tightly sealed goggles should be worn.



A face shield should also be worn if there is potential exposure to splash or spray.

Printing date 03/30/2018 Version Number 1.4 Reviewed on 03/27/2017

Trade name: Flex SLV PURe

(Cont. from page 4)

Body protection:

Protective work clothing

Use personal protective equipment as required.

Take off contaminated clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties		
General Information Appearance: Form: Color: Odor: Odor threshold:	Liquid According to product specification Characteristic Not determined.	
pH-value (~):	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. > 100 °C (>212 °F) > 100 °C (>212 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	Undetermined.	
Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Product is not self-igniting. Product does not present an explosion hazard.	
Explosion limits: Lower: Upper: VOC Content (max):	Not determined. Not determined. Not determined.	
Vapor pressure: Density: (~) Relative density Vapor density Evaporation rate	Not determined. Not determined. Not determined. Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/water): Not determined.		
Viscosity: Dynamic: Kinematic: Molecular weight	Not determined. Not determined. Not applicable.	
Other information	No further relevant information available.	

10 Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability

Thermal decomposition: No decomposition if used according to specifications.

Possibility of hazardous reactions Reacts with acids, oxidising agents.

(Cont. on page 6)

Printing date 03/30/2018 Version Number 1.4 Reviewed on 03/27/2017

Trade name: Flex SLV PURe

(Cont. from page 5)

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

Additional information: See section 7 for information on handling, storage and conditions to be avoided.

11 Toxicological information

Delayed and immediate effects and chronic effects from short or long term exposure

May cause damage to organs through prolonged or repeated exposure.

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:				
101-68-8 I	101-68-8 Diphenylmethane-4,4'-di-isocyanate			
Oral	LD50 > 10000 mg/kg (rat)			
Dermal	LD50	> 9400 mg/kg (rabbit)		
Inhalation	LC50, 4h	h 0.49 mg/l (rat)		
LC50 $0.00224 \text{ mg/m}^3 \text{ (rat)}$		$0.00224 \text{ mg/m}^3 \text{ (rat)}$		

Primary irritant effect:

on the skin: Causes skin irritation.

on the eye: Causes serious eye irritation.

inhalation:

Harmful if inhaled.

Causes damage to organs.

Ingestion: May cause damage to organs through prolonged or repeated exposure.

Sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Additional toxicological information: Suspected of causing cancer.

Carcinogenic categories

Ι	ARC (I	nternation	al Agency	for Research	on Cancer)	Human Caro	inogenicity:
•	٦ 1	D '4'	C 2 A	D 1. 1. 1. 1. /	1 AD D	1-1 - O	. 2 NI-4 OI

Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

101-68-8 Diphenylmethane-4,4'-di-isocyanate

NTP (National Toxicology Program)

K-Known to be carcinogenic, R-May reasonably be anticipated to be carcinogenic

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

(Cont. on page 7)

3

Trade name: Flex SLV PURe

(Cont. from page 6)

Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Disposal methods:

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing product for disposal. Dispose of waste in accordance with all applicable regulations.

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Dispose of contents/container in accordance with local/regional/national/international regulations.

14 Transport information	
UN-Number DOT, IMDG, IATA	Not applicable.
UN proper shipping name DOT, IMDG, IATA	Not applicable.
Transport hazard class(es)	
DOT, IMDG, IATA Class	Not applicable.
Packing group DOT, IMDG, IATA	Not applicable.
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport/Additional information	ion: Not classified as a dangerous good for transport by road, rail or air.
DOT Remarks:	Not Regulated.
UN "Model Regulation":	Not applicable.

USGHS

Trade name: Flex SLV PURe

(Cont. from page 7)

15 Regulatory information

SARA (Superfund Amendments and Reauthorization Act)

Section 302/304 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

101-68-8 Diphenylmethane-4,4'-di-isocyanate

1.8%

SARA Section 312/Tier I & II Hazard Categories:

Health Hazard - Carcinogenicity

Health Hazard - Acute toxicity (any route of exposure)

Health Hazard - Skin Corrosion or Irritation

Health Hazard - Respiratory or Skin Sensitization

Health Hazard - Serious eye damage or eye irritation

Health Hazard - Specific target organ toxicity (single or repeated exposure)

North America Chemical Inventory Status

TSCA (Toxic Substances Control Act - United States):

All ingredients are listed or exempt from listing unless otherwise noted below.

CEPA (Canadian DSL):

All ingredients are listed or exempt from listing unless otherwise noted below.

Right to Know Ingredient Disclosure:

105-76-0 Dibutyl maleate

Modified MDI

California Proposition 65: (Substances <0.1% unless noted in Section 3)

Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenicity Categories

TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists)

Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable

None of the ingredients is listed.

NIOSH-Cancer (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

Volatile Organic Compounds (VOC) reported per the Emission Standards.

If no g/L value is provided this product is not subject to above standard.

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

Department issuing SDS:

GCP Applied Technologies 62 Whittemore Avenue Cambridge, MA 02140 USA

USA: +1-617-876-1400 (24 hours)

+1-800-354-5414

(Cont. on page 9)

Printing date 03/30/2018 Version Number 1.4 Reviewed on 03/27/2017

Trade name: Flex SLV PURe

(Cont. from page 8)

Other Information:

In the previous SDS, version control was by Issue Number and Date. With the change to automated SDS creation software, version control is now based on printing and review dates which appear at the top of each page. Also consequent on this change, amendments have been made in all Sections of this SDS. In future updates to SDS, amended sections will be indicated by an asterisk (*) in the left-hand margin.

Date of preparation / last revision 03/30/2018 / 1.3

The first date of preparation 05/01/2015

Number of revision times and the latest revision date $1.4 \, / \, 03/27/2017$

USGHS