



Transportation
Sealants & Adhesives

TECHNICAL DATA

2010[®] BRUSHABLE REPAIR COATING

1. PRODUCT NAME:

2010[®] Brushable
Repair Coating

2. MANUFACTURER:

Geocel Products Group
A Business Unit of
The Sherwin-Williams Company
("Geocel Products Group")
Cleveland, OH 44115
Phone: (800) 348-7615

3. PRODUCT DESCRIPTION:

2010[®] Brushable Repair Coating is a single-component, brushable grade repair coating designed for many construction, commercial, agricultural, manufacturing, and industrial applications.

Product Benefits:

- May be applied at most working temperatures
- Exhibits quick adhesion to many construction materials, including damp, non-porous surfaces, and oily or dirty surfaces
- May be applied in layers to build up desired sealant thickness
- Forms a tough and flexible film with outstanding adhesion to metal, concrete, wood, and glass
- Withstands water contact right after application to stop leaks fast

Basic Uses:

- Coats and rustproofs metal surfaces such as: Agricultural equipment, autos and trucks, awnings, chimney caps, condensate pans, doors, flashing, gutters, mobile homes, recreational vehicles, roof panels, roof valleys, and roof vents
- Seals and waterproofs concrete, brick, block, or stone surfaces such as: chimney crowns, foundations, grain elevators (exterior), planters, pre-cast concrete, retaining walls, storage tanks (exterior), and other non-traffic-bearing concrete surfaces
- Coats and seals wood surfaces such as: Bracing, deck supports, doors, framing, posts, siding, thresholds, tree wounds and grafts, trim, window sills, wood foundations, and wooden gutters

Adheres To: Concrete, glass, vinyl, wood, steel, and other common building substrates

Composition and Materials: 2010 Brushable Repair Coating is based on a proprietary

formulation. This formula produces a product with exceptional adhesion, flexibility, and resistance to tear, shear, stress, and weathering.

Grade: Semi-self-leveling, brushable grade consistency

Primer: Not required on most surfaces. If primerless adhesion to a particular substrate is in question, a test application is recommended. Contact Geocel Product Group's Technical Service Department for further information.

Packaging: Quart cans, 1-gallon cans, and 5-gallon pails

Color: Clear/translucent and gray (gallon only)

Limitations:

- Do not use for cosmetic applications or traffic-bearing surfaces
- Do not use on plastics, styrofoam, EPDM, or continuous submersion applications
- Do not use for potable water applications
- Do not use on polystyrene insulation sheathing
- Do not use in areas where food is processed or stored
- Do not use on flexible acrylic surfaces
- Do not use as a complete surface coating - Recommended application area should be no greater than 8 sq. ft.
- For exterior use only due to odor emitted during cure.

4. INSTALLATION:

Surface Preparation: For best results, areas to be sealed should be basically clean and surface dry, although moderate amounts of dampness will not interfere with adhesion. For maximum adhesion to heavily oiled or dirty surfaces, areas to be sealed may need to be wiped with a solvent and allowed to dry. Follow manufacturer's instructions for safe use. Use of a dry rag or brush to remove dust, dirt, or other contaminants is recommended.

Elongation: 413%

Tack Free: 45 minutes

Cure: 2 days

Application and Tooling: Apply with brush, trowel, or putty knife, tooling coating into seams and cracks. Applied coating thickness should not exceed 1/8" per coat. If applied thicker than 1/8" per coat, coating will not cure properly and may crack or split

during curing. To obtain a thicker cured film, apply several light coats of coating, allowing 24 hours between coats. Do not thin coating.

Cleaning: Remove spilled or misapplied sealant from tools or other surfaces as soon as possible since cured material will be extremely difficult to remove. Use solvents such as MEK (lacquer thinner), xylene, Toluol, or chlorinated solvents.

Cured material may be removed by cutting with sharp tools, by scraping, or by sanding. Observe manufacturer's precautions when using toxic or flammable solvents.

Storage Life: One year (unopened cans)

Cautions: CONTAINS AROMATIC HYDROCARBONS. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

First Aid: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

5. AVAILABILITY AND COST:

Available from various distributors. Cost and further technical data are available from your local Geocel Products Group representative or from Geocel Products Group's office.

6. LIMITED WARRANTY:

If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to perform in accordance with this limited warranty. Labor or costs associated with labor are not included. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED. Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

7. MAINTENANCE:

No maintenance should be required. If the coating is damaged, either remove it and reseal with 2010 Brushable Repair Coating, or apply additional 2010 Brushable Repair Coating over the damaged area.

8. TECHNICAL SERVICES:

Geocel Products Group representatives throughout the U.S. are available to provide technical assistance. Geocel Products Group's in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information and/or applications testing.

Theoretical Yield per Gallon

SURFACE TYPE	COATING THICKNESS	Yield (approx.)
SMOOTH (sheet metal)	1/16" (62 mils)	100 sq. ft.
POROUS (wood shingles)	1/16" (62 mils)	25 sq. ft.

For additional product information, refer to the product spec sheet located at www.GeocelUSA.com.