



# Geocel ProFit® Pocket Penetration Sealant System

The Patented Geocel Pro Fit® Pocket is a highly flexible, easy solution for sealing roof penetrations. The Pocket is easily shaped to fit around even the most challenging configuration without the complex cutting or assembly found with other pockets and pans.

Geocel Pro Fit Pocket seals roof penetrations on EPDM, primed TPO, primed PVC, BUR, metal, asphalt, and other roofing substrates. It installs in 15 minutes or less with no flashing, priming, or complicated roof expertise required. See back for various configurations.

Geocel Pro Fit Pocket is extruded from advanced PVC specifically designed for rigorous weather and roof movement conditions. Even in adverse temperature ranges the Pocket will not crack or degrade. Available in black, it comes in 2" or 4" heights.



- Fits penetrations that prefabricated pockets and pans cannot.
- Can be installed in damp conditions
- Create a single or multiple pockets from one 56" pocket
- Quick, easy installation

### Basic Uses:

- Sealing large, small, cluster, parapet wall, and roof anchoring roof penetrations

### Adheres To:

Text

| Part #  | Color (USA) |  | UPC             | SCC               |
|---------|-------------|--|-----------------|-------------------|
| GC55812 | Black       |  | 0 79239 55812 5 | 000 79239 55812 5 |
| GC55814 | Black       |  | 0 79239 55814 9 | 000 79239 55814 9 |

10 cartridges (17lbs.) per case; Case dimensions: 9.50 L x 19.00 W x 6.00 H

## PRODUCT DATA SHEET

### OTHER

#### Packaging:

56" x 2", 56" x 4"

#### Color:

Black

#### Primer:

Not needed

#### Limitations:

Do not apply, store, or install in temperatures of 30°F (-1° C) or below.

#### Installation:

Before installing Geocel Pro Fit System on an existing roof, confirm whether or not a contractor or manufacturer's warranty is in effect. Installing this System on a warranted roof without prior authorization from those issuing the warranty may void it. If the existing roof system is covered by a warranty, be sure to obtain proper authorization prior to installation. Geocel 4500 Sealant is used to seal around the roof penetration, bond the overlapping ends of the Pro Fit Pocket, and seal around the exterior perimeter of the Pro Fit Pocket. It can also be used to affix the Pro Fit Pocket to the roof surface in place of mechanical fasteners. To complete the installation, pour 4525™ Semi-self-leveling Sealant into the Pocket cavity and tool as needed. Make sure to tool the sealant in an upward direction toward the penetration. When installing on TPO and PVC membranes and using Geocel 4500 Roof Bonding Sealant a primer must be used.

### Surface Preparation:

For best results, ensure surfaces are clean, dry, sound, and frost-free, although some moisture will not interfere with the sealants adhesion. Use a wire brush to remove all previously applied caulk, asphalt, pitch, cement, and other contaminants surrounding the penetration. Also be sure to remove contaminants, such as plastic cement and asphalt, from roof penetrations and pipes. Brush away all loose debris before installing the Pocket.

### Availability and Cost:

ProFit® Pocket is available from various construction material and industrial distributors. Cost and further technical data are available from your local Geocel Products Group representative or from our office.

### Maintenance:

No maintenance should be required.

### Limited Warranty:

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable except that if a contractor purchased and applied the product to the property for you, then the warranty is transferable to you. If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform, contact us at 1-800-348-7615 and upon satisfactory evidence of product failure, and with your proof of purchase, you may either receive a replacement of an equivalent quantity of product free of charge, or request a refund from the store where purchased. This warranty shall not apply to any defect, damage, or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application or maintenance of the product. Your sole remedy, and the sole liability of Geocel under this warranty is the replacement of product or refund and does not include labor or costs associated with the application or removal of any product. IN NO EVENT SHALL GEOCEL BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY. Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state.

