

Roof Patch Plastic Roof Cement



1. PRODUCT NAME:

Roof Patch Plastic Roof Cement

2. MANUFACTURER:

Geocel Products Group A Business Unit of The Sherwin-Williams Company ("Geocel Products Group") Cleveland, OH 44115
Phone: (800) 348-7615
Fax: (800) 348-7009
www.GeocelUSA.com

3. PRODUCT DESCRIPTION:

Roof Patch Plastic Cement is a single-component, asphalt-based cement designed to bond on wet or dry surfaces for many construction, roofing, agricultural, manufacturing, and industrial applications.

Product Benefits:

- Use on wet or dry surfaces, even underwater
- Formulated to seal quickly; will not pull apart or lose its bond
- Remains soft and pliable, and resists temperature change

Basic Uses:

- Ideal for patching and roof maintenance, sealing and repairing shingles, flashings, and roof seams
- Seals vents, pipes, chimneys, and gutters
- Seals metal building seams
- Shingle tab cement

Adheres to: Asphalt shingles, modified bitumen, steel, brick, wood, aluminum, and other common building substrates

Composition and Materials:

Roof Patch Cement is an asphalt-based material containing no asbestos. This formula produces a product that will bond on wet or dry surfaces.

Grade: Gun grade consistency

Primer: Not required on most surfaces.

Packaging: 10 fl. oz. cartridge

Colors: Black

Limitations:

- Do not paint or thin
- Do not use with single-ply membranes such as EPDM, PVC, CSPE, etc.
- Product contains solvents that may craze some plastic materials
- Store at room temperature for 24 hours before use to improve ease of application

4. INSTALLATION: Surface Preparation: For best results, remove dust and dirt with a stiff brush or broom. Remove old sealant or roof coatings. Surface to be repaired must be clean.

Cure: 1 to 3 days

Service Temperature: -40°F to 150°F (-40°C to 66°C)

Application Temperature: 0°F to 140°F (-18°C to 60°C)

Application and Tooling: Apply with standard caulking gun over area to be sealed. If tooling is desired, use a trowel or putty knife, occasionally dipping in paint thinner. When application is to take place at temperatures below 50°F (10°C), store Roof Patch Cement at room temperature for 24 hours prior to use in order to make application easier.

Cleaning: Clean tools with paint thinner or mineral spirits. Observe manufacturer's precautions when using toxic or flammable solvents.

Storage Life: One year (unopened cartridge)

Warning: Harmful or fatal if swallowed. If swallowed, call a physician immediately. May be harmful if inhaled in an enclosed space. Use only in a well-ventilated area. Avoid prolonged skin contact. Combustible (during cure). KEEP OUT OF REACH OF CHILDREN.

5. AVAILABILITY AND COST: Marketed throughout the U.S., Canada, and in select foreign markets, it is available from lumber yards, hardware stores, and home center. Cost and further technical data are available from your local Geocel Products Group representative or from our office.

6. LIMITED WARRANTY:

If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price for that portion of product that fails to perform in accordance with this limited warranty. Labor or costs associated with labor are not included. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED. Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state

7. MAINTENANCE:

No maintenance should be required. If the sealant is damaged, either remove bead and reseal, or apply additional Roof Patch Cement over the damaged area.

8. TECHNICAL SERVICES:

Geocel Products Group representatives throughout the U.S. are available to provide technical assistance. Our in-house technical staff and laboratory facilities are equipped to respond to specific requests for further information.

THEORETICAL YIELD

Per 10 fl. oz. Cartridge

Joint Size	Linear Feet
1/4" x 1/4"	24.1
1/4" x 3/8"	16.0
1/4" x 1/2"	12.0
1/2" x 3/8"	8.4
1/2" x 1/2"	6.0
3/4" x 1/2"	4.0

For additional product information, refer to the product spec sheet located at www.GeocelUSA.com and/or application testing.