

SS44UV

SAFETY DATA SHEET

1. Identification

Product identifier: SS44UV

Other means of identification

Synonyms: Silicone primer solution

Recommended use and restriction on use

Recommended use: Primer

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials LLC
260 Hudson River Road
Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number
Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Specific Target Organ Toxicity - Single Exposure Category 3¹
Specific Target Organ Toxicity - Repeated Exposure Category 2²
Aspiration Hazard Category 1

Target Organs

1. Narcotic effect., Respiratory tract irritation.
2. Liver, Kidney, hearing

Label Elements

SS44UV

Hazard Symbol:



Signal Word: Danger

Hazard Statement: H225; Highly flammable liquid and vapor.
H315; Causes skin irritation.
H319; Causes serious eye irritation.
H335; May cause respiratory irritation.
H336; May cause drowsiness or dizziness.
H373; May cause damage to organs through prolonged or repeated exposure.
H304; May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. Get medical advice/attention if you feel unwell. In case of fire: Use alcohol resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

SS44UV

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
Acetone	67-64-1	20 - <50%	# This substance has workplace exposure limit(s).
2-Propanol	67-63-0	20 - <50%	# This substance has workplace exposure limit(s).
Xylene	1330-20-7	10 - <20%	# This substance has workplace exposure limit(s).
Ethylbenzene	100-41-4	5 - <10%	# This substance has workplace exposure limit(s).
Tetraethyl Silicate	78-10-4	1 - <5%	# This substance has workplace exposure limit(s).
n-BUTANOL	71-36-3	1 - <3%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth with water. Do not induce vomiting. Seek medical attention. Never give liquid to an unconscious person.
Inhalation:	Move into fresh air and keep at rest. If breathing has stopped, trained personnel should begin artificial respiration immediately and if the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Get medical attention.
Skin Contact:	Flush contaminated area with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur. Wash contaminated clothing before reuse.
Eye contact:	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.

SS44UV

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	This product is not expected to produce adverse effects under normal conditions of use and appropriate personal hygiene.

Indication of immediate medical attention and special treatment needed

Treatment:	Treatment is symptomatic and supportive.
-------------------	--

5. Fire-fighting measures

General Fire Hazards:	Do not use water jet as an extinguisher, as this will spread the fire. Use water spray to keep fire-exposed containers cool.
------------------------------	--

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Alcohol resistant foam. Carbon dioxide Dry chemical.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical:	Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Ground container and transfer equipment to eliminate static electric sparks.
--	--

Special protective equipment and precautions for firefighters

Special fire fighting procedures:	Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Product may charge electrostatically during pouring or filling. All equipment used when handling the product must be grounded.
Special protective equipment for fire-fighters:	Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Avoid contact with eyes, skin, and clothing. Keep out of reach of children. Attention: Not for injection into humans.
Methods and material for containment and cleaning up:	Warn other workers of spill. Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

SS44UV

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below 200 F. Do not breathe vapor/spray. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. See Section 8 of the SDS for Personal Protective Equipment. Wash hands after handling. Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures.

Conditions for safe storage, including any incompatibilities: Keep away from heat, sparks and open flame. Keep container closed. Store in original container.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Acetone	TWA	250 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	500 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	250 ppm 590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	750 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	750 ppm 1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	Ceiling	3,000 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	750 ppm 1,780 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA PEL	500 ppm 1,200 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	LEL	2.5 %	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	IDLH	2,500 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	STEL	1,000 ppm 2,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
	ST ESL	3,300 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	4,800 µg/m3	US. Texas. Effects Screening Levels (Texas

SS44UV

			Commission on Environmental Quality), as amended (06 2018)
	ST ESL	7,800 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
2-Propanol	TWA	200 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	400 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	400 ppm 980 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	500 ppm 1,225 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	400 ppm 980 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	400 ppm 980 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	500 ppm 1,225 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	400 ppm 980 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	STEL	500 ppm 1,225 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA PEL	400 ppm 980 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH	2,000 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	LEL	2.0 %	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	STEL	500 ppm 1,225 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
	AN ESL	200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	4,920 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	492 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Xylene	TWA	100 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	150 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2016)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure

SS44UV

			Limits, Table Z1A, as amended (06 2008)
	TWA PEL	100 ppm 435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	Ceiling	300 ppm	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	150 ppm 655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	STEL	150 ppm 655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
Ethylbenzene	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	STEL	125 ppm 545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	STEL	125 ppm 545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	100 ppm 435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	STEL	30 ppm 130 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	TWA PEL	5 ppm 22 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	LEL	0.8 %	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	IDLH	800 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	STEL	125 ppm 545 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
	ST ESL	6,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	26,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	570 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	130 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
Tetraethyl Silicate	TWA	10 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	REL	10 ppm 85 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	100 ppm 850 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	10 ppm 85 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	TWA	10 ppm 85 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	TWA PEL	10 ppm 85 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)

SS44UV

	IDLH	700 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	ST ESL	100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	85 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	850 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
n-BUTANOL	TWA	20 ppm	US. ACGIH Threshold Limit Values, as amended (03 2015)
	Ceil_Time	50 ppm 150 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	100 ppm 300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	Ceiling	50 ppm 150 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	Ceiling	50 ppm 150 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
	Ceiling	50 ppm 150 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (01 2015)
	IDLH	1,400 ppm	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	LEL	1.4 %	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	AN ESL	20 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	61 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	ST ESL	610 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Acetone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEI (03 2015)
2-Propanol (acetone: Sampling time: End of shift at end of work week.)	40 mg/l (Urine)	ACGIH BEI (03 2015)
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2015)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (03 2015)

Appropriate Engineering Controls

Provide eyewash station and safety shower. General (mechanical) room ventilation is expected to be satisfactory if handled at low temperatures or in covered equipment.

SS44UV

Individual protection measures, such as personal protective equipment

General information:	General (mechanical) room ventilation is expected to be satisfactory if handled at low temperatures or in covered equipment.
Eye/face protection:	Safety glasses with side shields
Skin Protection	
Hand Protection:	Use chemical-resistant, impervious gloves.
Other:	Wear suitable protective clothing and eye/face protection.
Respiratory Protection:	If inhalation exposure is expected, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).
Hygiene measures:	Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Avoid contact with eyes, skin, and clothing. Do not eat, drink or smoke when using the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	liquid
Color:	Pale yellow
Odor:	Pungent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	> 36 °C
Flash Point:	-12 °C (Closed Cup)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Heat of combustion:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	0.85 g/cm3

SS44UV

Relative density:	0.80
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	> 343 °C
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	20.5 mm ² /s (40 °C)
VOC:	624 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Sunlight.
Incompatible Materials:	Bases.
Hazardous Decomposition Products:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

SS44UV

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 7,392.27 mg/kg

Dermal

Product: ATEmix: 3,591.19 mg/kg

Inhalation

Product: ATEmix: 43.79 mg/l
ATEmix : 64.87 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Acetone No data available. (Rabbit): Corrosive

Specified substance(s):

Xylene (Rabbit): Slightly irritating.

Specified substance(s):

Ethylbenzene (Rabbit): Corrosive

Specified substance(s):

n-BUTANOL (Rabbit): Corrosive

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Acetone , No data available. (negative)No data available.

Carcinogenicity

Product: No data available.

SS44UV

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect., Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure: Liver, Kidney, hearing

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Acetone
LC50 (Lepomis macrochirus, 96 h): 8,300 mg/l
LC0 (Leuciscus idus, 48 h): 6,320 mg/l
LC50 (Leuciscus idus, 48 h): 7,505 mg/l

SS44UV

2-Propanol	LC50 (Leuciscus idus, 48 h): 8,970 mg/l LC50 (Pimephales promelas, 96 h): > 65,500 mg/l
Xylene	LC50 (Leuciscus idus, 48 h): 86 mg/l LC50 (Pimephales promelas, 96 h): 13.4 mg/l LC50 (Salmo gairdneri, 96 h): 14 mg/l
Ethylbenzene	LC0 (Leuciscus idus, 48 h): 26 mg/l LC100 (Leuciscus idus, 48 h): 70 mg/l LC50 (Leuciscus idus, 48 h): 44 mg/l LC50 (Salmo gairdneri, 96 h): 4.2 mg/l
Tetraethyl Silicate	LC100 (No data available., 24 h): 9,000 mg/l LC50 (Brachydanio rerio, 96 h): > 245 mg/l
n-BUTANOL	LC0 (Leuciscus idus, 48 h): > 1,000 mg/l LC50 (Leuciscus idus, 48 h): 1,520 mg/l LC50 (Pimephales promelas, 96 h): 1,730 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanol	EC50 (Daphnia magna, 24 h): > 10,000 mg/l EC0 (Daphnia magna): 500 mg/l
Xylene	EC50 (Daphnia magna, 24 h): 165 mg/l
Ethylbenzene	LC0 (Daphnia magna): 137 mg/l (Daphnia magna): 184 mg/l LC100 (Daphnia magna): 200 mg/l
Tetraethyl Silicate	EC50 (Blue Crab): 7,800 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

SS44UV

Specified substance(s):

Acetone	50 % (5 d, No data available.) 78 % (28 d, No data available.)
2-Propanol	82.5 % (5 d, No data available.)
Ethylbenzene	68 % (28 d, No data available.)
Tetraethyl Silicate	98 % (28 d, OECD-Guideline 301 A (DOC Die-Away Test)) Readily biodegradable

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log K_{ow})

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Acetone	No data available.
2-Propanol	No data available.
Xylene	No data available.
Ethylbenzene	No data available.
Tetraethyl Silicate	No data available.
n-BUTANOL	No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information:	The generation of waste should be avoided or minimized wherever possible. Do not discharge into drains, water courses or onto the ground. See Section 8 for information on appropriate personal protective equipment.
Disposal instructions:	Disposal should be made in accordance with federal, state and local regulations.
Contaminated Packaging:	Dispose of as unused product.

SS44UV

14. Transport information

DOT

UN Number:	UN 1993
UN Proper Shipping Name:	Flammable liquids, n.o.s.(Acetone, Isopropanol)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	II
Marine Pollutant:	No

IMDG

UN Number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(Acetone, Isopropanol)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
Packing Group:	II
Marine Pollutant:	No
Limited quantity	1.00L
Excepted quantity	E2

IATA

UN Number:	UN 1993
Proper Shipping Name:	Flammable liquid, n.o.s.(Acetone, Isopropanol)
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	II
Cargo aircraft only Packing	364
Instructions:	
Passenger and cargo aircraft	364
Packing Instructions:	
Limited quantity:	Y341
Packing Instructions:	
Excepted quantity	E2
Environmental Hazards:	Not regulated.
Marine Pollutant:	No

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

SS44UV

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Acetone	Causes mild skin irritation.; Systemic effects
2-Propanol	Moderately irritating to the eyes.; Systemic effects
Xylene	Toxic by skin absorption
Ethylbenzene	Toxic by inhalation.
Tetraethyl Silicate	Moderately irritating to the eyes.; Respiratory hazard.
n-BUTANOL	Toxic by ingestion; Corrosive to eyes; Systemic effects; Respiratory hazard.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Acetone	5,000 lbs.
2-Propanol	100 lbs.
Xylene	100 lbs.
Ethylbenzene	1,000 lbs.
n-BUTANOL	5,000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids)
Skin Corrosion or Irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration Hazard
Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SS44UV

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
---------------------------------	---

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
2-Propanol		
Xylene		
Ethylbenzene		
n-BUTANOL		

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: 100 lbs.
Ethylbenzene	Reportable quantity: 1,000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including Benzene, which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

This product can expose you to chemicals including Ethylbenzene, which is [are] known to the State of California to cause cancer.
This product can expose you to chemicals including Toluene, which is [are] known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.P65Warnings.ca.gov.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity
Acetone
2-Propanol
Xylene
Polyalkylsiloxane
Ethylbenzene
Tetraethyl Silicate

SS44UV

US. Massachusetts RTK - Substance List

Chemical Identity

2-Propanol
Xylene
Ethylbenzene
Tetraethyl Silicate
n-BUTANOL

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanol
Xylene
Ethylbenzene
Tetraethyl Silicate
n-BUTANOL

US. Rhode Island RTK

Chemical Identity

2-Propanol
Xylene
Tetraethyl Silicate
n-BUTANOL

SS44UV

Inventory Status:

Australia AICS:	On or in compliance with the inventory	Remarks: None.
Canada DSL Inventory List:	On or in compliance with the inventory	Remarks: None.
EINECS, ELINCS or NLP:	On or in compliance with the inventory	Remarks: None.
Japan (ENCS) List:	On or in compliance with the inventory	Remarks: None.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory	Remarks: None.
Canada NDSL Inventory:	Not in compliance with the inventory.	Remarks: None.
Philippines PICCS:	On or in compliance with the inventory	Remarks: None.
US TSCA Inventory:	On or in compliance with the inventory	Remarks: None.
New Zealand Inventory of Chemicals:	On or in compliance with the inventory	Remarks: None.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	3
Flammability		4
Physical Hazards		0
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 01/13/2021

Revision Date: No data available.

Version #: 1.3

Further Information: No data available.

SS44UV

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.