

Revision Date: 08/24/2018

SS4179

SAFETY DATA SHEET

1. Identification

Product identifier: SS4179

Other means of identification

Synonyms: Primer solution

Recommended use and restriction on use

Recommended use: Primer Restrictions on use: Not known.

Manufacturer/Importer/Distr :

ibutor Information

Momentive Performance Materials LLC

260 Hudson River Road Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information

+1-800-295-2392

Emergency telephone

number

Supplier : CHEMTREC

1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 2

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Category 1¹

Single Exposure

Specific Target Organ Toxicity - Category 32.

Single Exposure

Specific Target Organ Toxicity - Category 13.

Repeated Exposure

Specific Target Organ Toxicity - Category 24.

Repeated Exposure

Target Organs

SDS_US 1/16



Revision Date: 08/24/2018

SS4179

- 1. Central nervous system.
- 2. Narcotic effect.
- 3. Peripheral nervous system
- 4. Kidney, Liver, Skin

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: H225; Highly flammable liquid and vapor.

H319; Causes serious eye irritation.

H317; May cause an allergic skin reaction.

H370; Causes damage to organs.

H336; May cause drowsiness or dizziness.

H372; Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

[electrical/ventilating/lighting/...] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Call a poison center/doctor. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use

SDS US 2/16



Revision Date: 08/24/2018

SS4179

alcohol resistant foam for extinction.

Storage: Store in a well-ventilated place. Keep cool. Store locked up. Keep container

tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and

vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
ETHYL ACETATE	141-78-6	50 - <100%	# This substance has workplace exposure limit(s).
Methyl Methacrylate	80-62-6	5 - <10%	# This substance has workplace exposure limit(s).
Methanol	67-56-1	3 - <5%	# This substance has workplace exposure limit(s).
DIBENZOYL PEROXIDE	94-36-0	0.1 - <1%	# This substance has workplace exposure limit(s).

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Do NOT induce vomiting.

Inhalation: Move to fresh air.

Skin Contact: Wash the skin immediately with soap and water. Wash contaminated

clothing before reuse. Get medical attention if irritation persists after

washing.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least

15 minutes.

SDS_US 3/16



Revision Date: 08/24/2018

SS4179

Most important symptoms/effects, acute and delayed

Symptoms: Itching Redness

Hazards: This product is not expected to produce adverse effects under normal

conditions of use and appropriate personal hygiene.

Indication of immediate medical attention and special treatment needed

Treatment: Treatment is symptomatic and supportive.

5. Fire-fighting measures

General Fire Hazards: Do not use water jet as an extinguisher, as this will spread the fire. Use

water spray to keep fire-exposed containers cool.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Alcohol resistant foam. Carbon dioxide Dry chemical.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger. Ground container and transfer equipment to eliminate static electric sparks.

In case of fire, gives off (emits): Carbon oxides

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Product may charge electrostatically during pouring or filling. All equipment used when handling the product

must be grounded.

Special protective equipment

for fire-fighters:

Firefighters must wear NIOSH/MSHA approved positive pressure selfcontained breathing apparatus with full face mask and full protective

clothing.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid contact with eyes, skin, and clothing. Keep out of reach of children. Attention: Not for injection into humans.

Methods and material for containment and cleaning up:

Warn other workers of spill. Wear proper protective equipment as specified in the protective equipment section. Wipe, scrape, or soak up in an inert material and put in a container intended for flammable materials for disposal.

SDS_US 4/16



Revision Date: 08/24/2018

SS4179

Notification Procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

immediate area).

Environmental Precautions: Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is expected; material has a flash point below

200 F. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Use only in well-ventilated areas. Wash thoroughly after handling. Product may charge electrostatically during pouring or filling. All equipment used when

handling the product must be grounded.

Conditions for safe storage,

including any incompatibilities:

No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
ETHYL ACETATE	TWA	400 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	400 ppm 1,400 mg/m3	
			Hazards (2010)
	PEL	400 ppm 1,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm 1,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm 1,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	3,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	1,440 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	870 ppt	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	400 ppt	Commission on Environmental Quality) (11 2016)
	TWA PEL	400 ppm 1,400 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Methyl Methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (03 2015)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	100 ppm 410 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	100 ppm 410 mg/m3	
	TWA	100 ppm 410 mg/m3	(1989)
	TWA	100 ppm 410 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)

SDS_US 5/16



Revision Date: 08/24/2018

SS4179

	AN ESL		210 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		860 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		210 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	50 ppm	205 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	100 ppm	410 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Methanol	TWA	200 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	250 ppm	325 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	200 ppm	260 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL TWA	200 ppm	260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) US. OSHA Table Z-1-A (29 CFR 1910.1000)
	STEL	200 ppm 250 ppm	260 mg/m3 325 mg/m3	(1989) US. OSHA Table Z-1-A (29 CFR 1910.1000)
	TWA	200 ppm	260 mg/m3	(1989) US. Tennessee. OELs. Occupational Exposure
	STEL	250 ppm	325 mg/m3	Limits, Table Z1A (06 2008) US. Tennessee. OELs. Occupational Exposure
	AN ESL	230 ppm	2,100 µg/m3	Limits, Table Z1A (06 2008) US. Texas. Effects Screening Levels (Texas
				Commission on Environmental Quality) (11 2016)
	AN ESL		1,600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		3,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		3,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	200 ppm	260 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	Ceiling	1,000 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	STEL	250 ppm	325 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
DIBENZOYL PEROXIDE	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
DIBENZOYL PEROXIDE -	ST ESL		50 μg/m3	US. Texas. Effects Screening Levels (Texas

SDS_US 6/16



Revision Date: 08/24/2018

SS4179

Particulate.			Commission on Environmental Quality) (11 2016)
	AN ESL	5 μg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
DIBENZOYL PEROXIDE	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Methanol (methanol:	15 mg/l (Urine)	ACGIH BEI (03 2015)
Sampling time: End of shift.)		

Appropriate Engineering

Controls

Provide eyewash station and safety shower. If the formation of aerosol/mist cannot be excluded, ensure effective exhaust ventilation in the working

area.

Individual protection measures, such as personal protective equipment

General information: Ventilation and other forms of engineering controls are preferred for

controlling exposures. Respiratory protection may be needed for non-

routine or emergency situations.

Eye/face protection: Face shield Monogoggles

Skin Protection

Hand Protection: Rubber or plastics gloves

Other: Wear rubber apron. Wear suitable protective clothing and eye/face

protection.

Respiratory Protection: If exposure limits are exceeded or respiratory irritation is experienced,

NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA

regulations (see 29CFR 1910.134).

Hygiene measures: Observe good industrial hygiene practices. Wash hands after handling.

When using do not eat, drink or smoke. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective

measures whenever possible.

9. Physical and chemical properties

Appearance

Physical state:liquidForm:liquidColor:Colorless

SDS_US 7/16



Revision Date: 08/24/2018

SS4179

Odor: ester like

Odor threshold:

pH:

No data available.

No data available.

No data available.

No data available.

Initial boiling point and boiling range: ca. 80 °C

Flash Point: -2.80 °C (Tagliabue Closed Cup)

Evaporation rate: ca. 6

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 11.00 %(V)
Flammability limit - lower (%): 2.00 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

No data available.

No data available.

Vapor pressure: Not applicable

Vapor density:No data available.Density:ca. 0.91 g/cm3

Relative density: 0.91

Solubility(ies)

Solubility in water: Insoluble

Solubility (other): SOLUBLE IN ALCOHOLS

Partition coefficient (n-octanol/water) Log

Pow:

Auto-ignition temperature: 385.00 °C

Decomposition temperature:No data available.SADT:No data available.Viscosity, dynamic:No data available.Viscosity, kinematic:No data available.

VOC: 859 g/l;

10. Stability and reactivity

Reactivity: No dangerous reaction if used as recommended.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Hazardous polymerisation does not occur.

No data available.

Conditions to avoid: Keep away from sources of ignition - No smoking.

Incompatible Materials: Oxidizing agents.

SDS_US 8/16



Revision Date: 08/24/2018

SS4179

Hazardous Decomposition

Products:

Methanol Formaldehyde. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde

are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 3,333.33 mg/kg

Specified substance(s):

ETHYL ACETATE LD 50 (Rat, No data available.): 5,620 mg/kg

LD 50 (Guinea Pig, No data available.): 5,500 mg/kg LD 50 (Mouse, No data available.): 4,100 mg/kg LD 50 (Rabbit, No data available.): 4,935 mg/kg

Methyl Methacrylate LD 50 (Rat): 7,872 mg/kg

DIBENZOYL PEROXIDE LD 50 (Rat): 6,400 mg/kg

Dermal

Product: ATEmix: 10,000 mg/kg

Specified substance(s):

ETHYL ACETATE LD 50 (Rabbit, No data available.): 20,000 mg/kg

LD 50 (Rabbit, No data available.): 20,000 mg/kg

Inhalation

SDS_US 9/16



Revision Date: 08/24/2018

SS4179

Product: ATEmix: 60.74 mg/l

Specified substance(s):

ETHYL ACETATE LC50 (Rat, No data available.): 1.6 mg/l

LC50 (Mouse, No data available.): 45 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

SDS_US 10/16



Revision Date: 08/24/2018

SS4179

Target Organs

Specific Target Organ Toxicity - Single Exposure: Central nervous system.

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Specific Target Organ Toxicity - Repeated Exposure: Peripheral nervous system

Specific Target Organ Toxicity - Repeated Exposure: Kidney, Liver, Skin

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

ETHYL ACETATE LC50 (Leuciscus idus, 48 h): ca. 270 mg/l

LC50 (Pimephales promelas, 96 h): 230 mg/l

Methanol LC50 (Pimephales promelas, 96 h): 28,100 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

ETHYL ACETATE LC0 (Daphnia magna): 1,562 mg/l

(Daphnia magna): 3,090 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

SDS_US 11/16



Revision Date: 08/24/2018

SS4179

Specified substance(s):

ETHYL ACETATE 68 % (5 d, No data available.)

85 % (28 d, No data available.)

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)
Product:
No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

ETHYL ACETATE
Methyl Methacrylate
Methanol
DIBENZOYL PEROXIDE
No data available.
No data available.
No data available.
No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever

possible. Do not discharge into drains, water courses or onto the ground.

See Section 8 for information on appropriate personal protective

equipment.

Disposal instructions: Disposal should be made in accordance with federal, state and local

regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT

UN Number: UN 1993

UN Proper Shipping Name: Flammable liquids, n.o.s.(ETHYL ACETATE, METHANOL)

Transport Hazard Class(es)

Class: 3
Label(s): 3
Packing Group: II
Marine Pollutant: No

SDS_US 12/16



Revision Date: 08/24/2018

SS4179

IMDG

UN Number: UN 1993

UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(ETHYL ACETATE, METHANOL)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.: F-E, S-E

Packing Group: II
Marine Pollutant: No
Limited quantity 1.00L

Excepted quantity E2

IATA

UN Number: UN 1993

Proper Shipping Name: Flammable liquid, n.o.s.(ETHYL ACETATE, METHANOL)

364

Transport Hazard Class(es):

Class: 3
Label(s): 3
Packing Group: II
Cargo aircraft only Packing 364

Instructions:

Passenger and cargo aircraft

Packing Instructions:

Limited quantity: Y341

Packing Instructions:

Excepted quantity E2

Environmental Hazards: Not regulated.

Marine Pollutant: No

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u> <u>Reportable quantity</u>

ETHYL ACETATE 5,000 lbs.
Methyl Methacrylate 1,000 lbs.
Methanol 5,000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Flammable (gases, aerosols, liquids, or solids)

Serious eye damage or eye irritation

Respiratory or Skin Sensitization

SDS_US 13/16



Revision Date: 08/24/2018

SS4179

Specific target organ toxicity (single or repeated exposure) Hazards Not Otherwise Classified (HNOC)

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u> <u>Reportable quantity</u>

ETHYL ACETATE 5,000 lbs.

Methyl Methacrylate 1,000 lbs.

Methanol 5,000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity Threshold Planning Quantity

ETHYL ACETATE 10000 lbs
Methyl Methacrylate 10000 lbs
Methanol 10000 lbs
DIBENZOYL PEROXIDE 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for

threshold for manufacturing and

other users processing

Chemical Identity

Methyl Methacrylate

Methanol

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

<u>Chemical Identity</u> <u>Reportable quantity</u>

Methyl Methacrylate Reportable quantity: 1,000 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Reproductive Harm - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

ETHYL ACETATE Methyl Methacrylate

Methanol

gamma-Methacryloxypropyltrimethoxysilane

DIBENZOYL PEROXIDE

SDS_US 14/16



Revision Date: 08/24/2018

SS4179

US. Massachusetts RTK - Substance List

Chemical Identity

ETHYL ACETATE Methyl Methacrylate Methanol

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

ETHYL ACETATE Methyl Methacrylate Methanol

US. Rhode Island RTK

Chemical Identity

ETHYL ACETATE Methyl Methacrylate Methanol

Inventory Status:

inventory Status:		
Australia AICS:	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	y (positive listing)	Remarks: None.
China Inventory of Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (Negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: None.
New Zealand Inventory of	y (positive listing)	Remarks: None.
Chemicals:		
Taiwan. Taiwan inventory (CSNN):	y (positive listing)	Remarks: None.

16.Other information, including date of preparation or last revision

HMIS Hazard ID

Health	4
Flammability	3
Physical Hazards	1
PERSONAL PROTECTION	

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 08/24/2018

SDS_US 15/16



Revision Date: 08/24/2018

SS4179

Revision Date: No data available.

Version #: 3.0

Further Information: No data available.

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives.

Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best ofour knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®,*, and TM indicate trademarks owned by or licensed to Momentive.

SDS_US 16/16