



Spray-Pressure Roller Equipment

Information for use with Elemax™ 2600 AWB

Elemax 2600 AWB can be applied by spray, pressure roller, roller and brush. When spraying or using a pressure roller Elemax 2600 AWB can be dispensed directly from pails and drums using air, electric or engine-powered application equipment. Elemax 2600 AWB cures in the presence of atmospheric moisture thus spray or pressure roller equipment used to process Elemax 2600 AWB:

- Must be free of water prior to loading product into the equipment
- Must be designed to operate safely at the pressures required to deliver Elemax 2600 AWB
- Must be capable of providing a minimum of 3000 psi (207 bar) at the gun
- Should contain hoses that are solvent resistant
- Should contain hoses that are vapor lock in design if product is intended to remain in the lines for extended periods of time

Spray Equipment

The list of equipment below has shown to be sufficient to atomize and properly spray Elemax 2600 AWB. Spray tips with an orifice size between 0.019” and 0.025” are recommended. Spraying with external atomizing air (air-assist) can be used and requires a minimum fluid pressure of 3000 psi (207 bar) at the gun and a minimum of 60 psi (4 bar) of atomizing air.

Manufacturer / Model	Type
Graco GH733 Big Rig	Gas-Powered
Graco GH833 Big Rig	Gas-Powered
Graco GH933ES Big Rig	Gas-Powered
Graco TEXSPRAY 7900HD	Gas-Powered
Graco XTREME X60	Air-Operated
Graco MARK V	Electric
Itwbinks MX3560	Air-Operated

When using power equipment, always follow the equipment manufacturer's operation and safety instructions.



Spray Equipment Requirements

Elemax 2600 AWB requires a minimum of 3000 psi (207 bar) at the gun to obtain an optimized spray pattern. Elemax 2600 AWB works in many commercially available pumping and spray systems however, individual system requirements will be based on a number of factors relative to the desired system and type (ex. hose length, hose diameter, spray tip, gas- powered, air-powered, etc.), as well as the number of applicators to be operated from each pump.

There are a number of methods to deliver material from the drum or pail to the spray equipment, including: direct immersion, pouring material into a hopper, use of a transfer pump, and feed hoses on a self-priming pumping system. It is important that the feed system is able to supply enough material as not to starve the system. Contact the spray equipment manufacturers for system advice based on the above variables and feed options.

Pressure Roller Equipment (Accessories)

The list of equipment below has shown to be sufficient to properly pressure roll Elemax 2600 AWB.

Manufacturer / Model	Type
Graco 218-625	Adjustable Extension Roller Kit
Graco 107591	9 in (230 mm) Roller Cover 3/4 in (19 mm) nap

Equipment Suppliers

For assistance in finding equipment suppliers or determining the suitability of existing equipment, contact Momentive Performance Materials, Inc.

Pump Clean Out

Equipment that is used to apply both water based and solvent based material must be properly flushed with solvent prior to filling the equipment with Elemax 2600 AWB. It is recommended to have designated hoses, guns, roller kits, and pump feeds for each type of chemistry. Clean, dry, and non-reclaimed solvents should be used for flushing. Mineral Spirits, Xylene, Sunnyside 301 or Sunnyside 476 VOC-compliant solvents have shown to be suitable.



Contact us at [gesilicones.com](https://www.gesilicones.com)

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a registered trademark of General Electric Company. Used under trademark license.
The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies.
Copyright 2022 Momentive Performance Materials Inc. All rights reserved.