



GE Silicones

Optic* Translucent Silicone Coating


The difference is clear.



The choice for cost-effective, enduring building repairs.

When a building façade leaks, the usual choice is between costly, invasive renovations or quick, temporary fixes. GE Silicones Optic translucent coating offers the refreshing alternative—without compromising your budget or building performance. Prevent repeated failures, minimize maintenance, and keep your building looking great.

The look you want, the protection you need. Optic coating offers:



CONTINUOUS

sealing across
hairline cracks



CLEAR

protection to
uphold building
appearance



LONG-TERM RESISTANCE

against tough
conditions



**EASY
APPLICATION**
to address leaks
quickly



DEFENSE

against
graffiti

Preserve the look, protect the building—Optic coating can help.

A patented 100% silicone formula arms Optic translucent coating with the power to perform for decades. Unlike penetrating sealers, it creates a clear membrane that remains waterproof, breathable, permanently flexible, and weather resistant.



Building longevity

- Withstands extreme temperatures and UV rays
- Repels wind-driven rain
- Seals hairline cracks in mortar joints and wall materials
- Stays air- and watertight long-term
- Offers high water vapor permeability
- Remains flexible after cure and will not crack, peel, chip, or harden
- Guards against moisture leaks through porous substrates
- Backed by a 10-year warranty

Translucent protection

- Stays clear and does not yellow
- Covers minor holes, cracks, and surface irregularities for a clean appearance
- Allows light to pass through daylighting features such as glass block walls and skylights
- Preserves the natural look of brick, stone, masonry, and more
- Resists graffiti from most paints and inks to enable easy removal

Simple planning & application

- Can be applied without a primer and with minimal surface prep
- Offers application flexibility: roller, power roller, spray, and brush
- Can be rain ready in 30 minutes to help keep projects moving
- Installs in temperatures ranging from 20°F to 120°F (-7°C to 49°C)
- Works with other 100% silicone products to form a continuous waterproof barrier
- Meets low VOC requirements¹

¹ Based on VOC content of less than 50 g/L, as provided for in the 06/2018 US EPA (40 CFR 59) and the 02/2016 South Coast AQMD (Rule 1113) VOC emission standards for architectural coatings.

Use the practical alternative
on your next project.

((contact us)) siliconeforbuilding.com

THE MATERIALS, PRODUCTS, AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS, OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service, or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service, or design in the infringement of any patent or other intellectual property right.

GE is a registered trademark of General Electric Company and is used under license by Momentive Performance Materials Inc.

*Optic is a trademark of Momentive Performance Materials Inc.

Copyright 2018 Momentive Performance Materials Inc. All rights reserved.