

SCS1000 WHITE 24C

SAFETY DATA SHEET

1. Identification

Product identifier: SCS1000 WHITE 24C

Other means of identification

Synonyms: Silicone Sealant

Recommended use and restriction on use

Recommended use: Silicone Elastomer

Restrictions on use: For industrial use only.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials LLC
260 Hudson River Road
Waterford NY 12188

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

**Emergency telephone number
Supplier :** CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Toxic to reproduction	Category 2

Unknown toxicity - Health

Acute toxicity, oral	0 %
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	0 %
Acute toxicity, inhalation, dust or mist	0 %

Label Elements

Hazard Symbol:

SCS1000 WHITE 24C



Signal Word: Danger

Hazard Statement: H315; Causes skin irritation.
H318; Causes serious eye damage.
H361; Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water/... If skin irritation occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see on this label). Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

3. Composition/information on ingredients

SCS1000 WHITE 24C

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
Distillates, petroleum, hydrotreated middle	64742-46-7	10 - <20%	# This substance has workplace exposure limit(s).
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	68611-44-9	5 - <10%	# This substance has workplace exposure limit(s).
Methyltriacetoxysilane	4253-34-3	3 - <5%	# This substance has workplace exposure limit(s).
(1) TITANIUM DIOXIDE	13463-67-7	1 - <5%	# This substance has workplace exposure limit(s).
Octamethylcyclotetrasiloxane	556-67-2	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) Silica	7631-86-9	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) Aluminum oxide	1344-28-1	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

(1) The respirable particle(s) listed above are inextricably bound within the polymer matrix, and therefore does not present an inhalation hazard during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

4. First-aid measures

Ingestion: If swallowed, do NOT induce vomiting. Give a glass of water.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation occurs: Get medical advice/attention.

SCS1000 WHITE 24C

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Most important symptoms/effects, acute and delayed

Symptoms: Treatment is symptomatic and supportive.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use standard firefighting procedures and consider the hazards of other involved materials.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Extinguish with foam, carbon dioxide or dry powder.

Unsuitable extinguishing media: water jet

Specific hazards arising from the chemical: In case of fire, carbon monoxide and carbon dioxide may be formed. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. Pay attention to the corrosive effects arising from contact with water. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

SCS1000 WHITE 24C

Personal precautions, protective equipment and emergency procedures:

Avoid contact with skin and eyes. Use only in well-ventilated areas. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands. Product releases acetic acid during application and curing. Attention: Not for injection into humans. Keep out of reach of children. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up:

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is not expected.

Conditions for safe storage, including any incompatibilities: Keep away from heat, sparks and open flame.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates, petroleum, hydrotreated middle - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
Distillates, petroleum, hydrotreated middle - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates, petroleum, hydrotreated middle	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL	3,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Distillates, petroleum, hydrotreated middle - Mist.	AN ESL	350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
Distillates, petroleum, hydrotreated middle	IDLH	2,500 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica - Particulate.	ST ESL	27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)

SCS1000 WHITE 24C

	AN ESL	2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2015)
(1) TITANIUM DIOXIDE - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	10 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) TITANIUM DIOXIDE - Particulate.	ST ESL	50 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) TITANIUM DIOXIDE	IDLH	5,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)
(1) Silica	REL	6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	6 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	6 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Silica - Particulate.	ST ESL	27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) Silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	IDLH	3,000 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values (10 2017)

SCS1000 WHITE 24C

(1) Aluminum oxide - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values (03 2015)
	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Aluminum oxide - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
(1) Aluminum oxide - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
(1) Aluminum oxide - Respirable fraction.	TWA	5 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Aluminum oxide - Total dust.	TWA	10 mg/m ³	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
(1) Aluminum oxide - Particulate.	AN ESL	5 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL	50 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
(1) Aluminum oxide - Respirable fraction.	TWA PEL	5 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
(1) Aluminum oxide - Total dust.	TWA PEL	10 mg/m ³	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (01 2015)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) Aluminum oxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
(1) Aluminum oxide - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Octamethylcyclotetrasiloxane	TWA	5 ppm	
Octamethylcyclotetrasiloxane - Vapor.	ST ESL	1,000 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL	100 µg/m ³	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Octamethylcyclotetrasiloxane	TWA	10 ppm	US. OARS. WEELs Workplace Environmental Exposure Level Guide (2014)

This product contains one or more substances with an occupational exposure limit. However, the respirable particle(s) of this/these substance(s) are inextricably bound within the polymer matrix. Therefore, we do not expect an exposure to this/these substance(s) during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

Appropriate Engineering Controls

Eye wash facilities and emergency shower must be available when handling this product. Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

General information: No data available.

Eye/face protection: Safety glasses with side shields

SCS1000 WHITE 24C

Skin Protection

Hand Protection: Rubber gloves are recommended.

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection:

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: White

Odor: Acetic acid.

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: > 93.3 °C

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper (%): No data available.

Explosive limit - lower (%): No data available.

Heat of combustion: No data available.

Vapor pressure: No data available.

Vapor density: No data available.

Density: 1.04 g/cm³

Relative density: 1.04

Solubility(ies)

Solubility in water: No data available.

Solubility (other): No data available.

SCS1000 WHITE 24C

Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	7 mm ² /s
VOC:	36 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Keep away from moisture.
Incompatible Materials:	Strong Acids, Strong Bases Water.
Hazardous Decomposition Products:	Carbon dioxide Oxides of silicon. Acetic acid. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

SCS1000 WHITE 24C

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 49,364.63 mg/kg

Specified substance(s):

Methyltriacetoxysilane LD 50 (Rat, female): 1,830 mg/kg
LD 50 (Rat): 1,550 mg/kg

(1) TITANIUM DIOXIDE LD 50 (Rat): > 10,000 mg/kg

Octamethylcyclotetrasiloxane LD 50 (Rat): 4,800 mg/kg

(1) Silica LD 50 (Rat): > 15,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LD 50 (Rabbit): > 10,000 mg/kg

Octamethylcyclotetrasiloxane LD 50 (Rat): > 2,400 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

(1) TITANIUM DIOXIDE LC50 (Rat): > 6.8 mg/l

Octamethylcyclotetrasiloxane LC50 (Rat): 36 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

SCS1000 WHITE 24C

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasiloxane
Ames-Test (OECD-Guideline 471 (Genetic Toxicology: Salmonella typhimurium, Reverse Mutation Assay)): negative (not mutagenic)
Mouse Lymphoma Assay (OECD Guideline 476): negative (not mutagenic)

In vivo

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasiloxane
Chromosomal aberration (OECD-Guideline 474 (Genetic Toxicology: Micronucleus Test)) Inhalation (Rat, male and female): negative

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: Acetic acid released during curing. None.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

SCS1000 WHITE 24C

Fish

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE LC0 (Leuciscus idus, 48 h): > 1,000 mg/l

(1) Silica LC0 (Brachydanio rerio, 96 h): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

(1) Silica LC0 (Brachydanio rerio, 4 d): 5,000 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

(1) TITANIUM DIOXIDE 0 %

Octamethylcyclotetrasiloxane 3.7 % (29 d, 310 Ready Biodegradability - CO₂ in Sealed Vessels (Headspace Test)) Not readily biodegradable.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Octamethylcyclotetrasiloxane Fathead Minnow, Bioconcentration Factor (BCF): 12.40

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

SCS1000 WHITE 24C

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Distillates, petroleum, hydrotreated middle SILANE,	No data available.
DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	No data available.
Methyltriacetoxysilane	No data available.
(1) TITANIUM DIOXIDE	No data available.
Octamethylcyclotetrasiloxane	No data available.
(1) Silica	No data available.
(1) Aluminum oxide	No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever possible. See Section 8 for information on appropriate personal protective equipment. Do not discharge into drains, water courses or onto the ground.

Disposal instructions: Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT
 Not regulated.

IMDG
 Not regulated.

IATA
 Not regulated.

Special precautions for user: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

SCS1000 WHITE 24C

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Skin Corrosion or Irritation
Serious eye damage or eye irritation
Reproductive toxicity

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Distillates, petroleum, hydrotreated middle	10000 lbs
SILANE, DICHLORODIMETHYL-, REAKTION PRODUCTS WITH SILICA, Silane, dichlorodimethyl-, reaction products with silica	10000 lbs
Methyltriacetoxysilane	10000 lbs
(1) TITANIUM DIOXIDE	10000 lbs
Octamethylcyclotetrasiloxane	10000 lbs
(1) Silica	10000 lbs
(1) Aluminum oxide	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

SCS1000 WHITE 24C



WARNING

Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Dimethylpolysiloxane
Distillates, petroleum, hydrotreated middle
Methyltriacetoxysilane
Polydimethylsiloxane
METHYLDIACETOXYISOPROPOXYSILANE
Octamethylcyclotetrasiloxane

US. Massachusetts RTK - Substance List

Chemical Identity

Distillates, petroleum, hydrotreated middle

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Distillates, petroleum, hydrotreated middle
(1) TITANIUM DIOXIDE

US. Rhode Island RTK

Chemical Identity

Distillates, petroleum, hydrotreated middle

SCS1000 WHITE 24C

Inventory Status:

Australia AICS:	On or in compliance with the inventory	Remarks: None.
Canada DSL Inventory List:	Q (quantity restricted)	Remarks: None.
EINECS, ELINCS or NLP:	On or in compliance with the inventory	Remarks: None.
Japan (ENCS) List:	On or in compliance with the inventory	Remarks: None.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory	Remarks: None.
Canada NDSL Inventory:	Not in compliance with the inventory.	Remarks: None.
Philippines PICCS:	On or in compliance with the inventory	Remarks: None.
US TSCA Inventory:	On or in compliance with the inventory	Remarks: None.
New Zealand Inventory of Chemicals:	On or in compliance with the inventory	Remarks: None.
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	*	3
Flammability		0
Physical Hazards		0
PERSONAL PROTECTION		

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 09/23/2019
Revision Date: No data available.
Version #: 1.0
Further Information: No data available.

SCS1000 WHITE 24C

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safehandling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

®, *, and TM indicate trademarks owned by or licensed to Momentive.