



“WET LOOK” CONCRETE & MASONRY LACQUER

**EXPOSED AGGREGATE – STAMPED CONCRETE – POROUS BRICK
NATURAL STONE SLATE – MEXICAN TILE – STUCCO
MANUFACTURED STONE – ADOBE PLAIN & COLORED CONCRETE**

PRODUCT DESCRIPTION

Glaze 'N Seal is a crystal clear, high solids acrylic coating designed to protect and beautify concrete, masonry and tile surfaces. This super-tough film was formulated for interior or exterior use. Walk on it – drive on it (it does reject organic stains). It offers ultimate protection in a clear finish.

USES

Protects garage floors and driveways from oil stains. Eliminates concrete dusting and freeze-thaw problems. Protects patio and barbecue areas from food and grease stains. Saturation with Glaze 'N Seal will actually harden old and deteriorating mortar and plaster for added life. Independent laboratory tests rate Glaze 'N Seal superior for abrasion resistance, sunlight resistance and stain resistance qualities.

FEATURES

- Non-Yellowing
- Use Indoors or Outdoors
- Fast Drying and Long Lasting
- Apply With Brush or Sprayer
- Prevents Staining High Solids
- Strong Resistance to Efflorescence

PREPARATIONS

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paint or sealers. If acid is used, all residue must be removed prior to application. Use Glaze 'N Seal Neutralizing Rinse to neutralize surface. Allow to dry thoroughly before applying LACQUER.

APPLICATION

Apply from 2-4 light, even coats (depending on porosity of surface) of “Wet Look” Lacquer with a natural brush or low pressure/airless sprayer (with metal or teflon tip). Allow 1 to 3 hours between coats or until surface is dry to the touch. Not recommended for dense or presealed surfaces such as glazed ceramic or quarry tile, marble or terrazzo.

Apply in temperatures between 55° and 80° F. Avoid using in direct sunlight. Use only in well ventilated areas. **Helpful Hint:** Use toluene or lacquer thinner for easy clean up.

IMPORTANT: Product contains active toluene and petroleum distillates. Read product label carefully or consult with dealer for more detailed preparation, application and caution information.

SPECIFICATIONS

GLASS TRANSITION RATE	+50°F
DENSITY	7.2 lbs.
TUKON HARDNESS	12 – 13
CLEAN UP	LACQUER THINNER
DRY TIME	1 HOUR
FLASH POINT	+50°F
APPLICATION TEMP.	50°F to 80°F

COVERAGE

100 to 400 square feet per gallon depending on the porosity of the surface.

MAINTENANCE

To protect the sealer and extend life (indoors), use Glaze 'N Seal Floor Polish (Regular or Matte Finish) for a traffic coat. Sweep and damp mop floor frequently.

PACKAGING

Available in quarts, gallons, 5 gallon pails and 55 gallon drums.

SPECIAL NOTES

Always test a small area of surface to verify protection and appearance. NOT RECOMMENDED for glazed tile, marble, dense brick or dense slate. If in doubt, test surface. **Do not** use where hydrostatic pressure is possible.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA

FS 11-12/01