



ADVANCED PAVER CARE

ENHANCED LOOK Paver Sealer

*Plus SAND LOCK for
Interlocking Pavers and Bricks*



LOCKS SAND BETWEEN JOINTS AND SEALS IN ONE STEP!

- Superior Enhanced Look
- Oil and Grease Resistant
- Resists Color Fading
- Deeper Color
- Lasts Longer
- Low Gloss



Professional Results...GUARANTEED!

1-800-486-1414

www.glaze-n-seal.com





“ENHANCED LOOK” PAVER SEALER

Plus SAND LOCK for Interlocking Pavers and Bricks

Glaze 'N Seal Products proudly offers the ultimate paver care system, that is designed to give your project “The Look You Want — The Protection You Need.”

Product Uses: Seals, locks-in sand joints, and enhances porous concrete, pavers, brick, natural stone (like slate and flagstone). Other uses include block and masonry walls, decorative concrete, and more.

Excellent resistance to stains, oil, efflorescence, weeds and UV fading. Deep color enhancement with no gloss finish is easy to apply and maintain.

Special Features:

- Reduces efflorescence
- Reduces freeze thaw effects
- Resists oil, grease rust stains
- Locks sand between joints
- Non-flammable
- No harmful vapors
- Cleans up with water
- Prevents weed growth
- Low VOC
- LEED eligible

DO NOT SHAKE — DO NOT ALLOW TO FREEZE

Surface Preparation: Prior to the application of *Glaze 'N Seal products*, surface must be thoroughly clean and dry. Remove all dirt, oil, grease, paint, efflorescence and surface sealers. General cleaning may be done using **Glaze 'N Seal Heavy Duty Cleaner** for Concrete and Masonry. For efflorescence stains use **Glaze 'N Seal Efflorescence Remover**. When acid has been used for any reason, surface must be neutralized. We recommend **Glaze 'N Seal Neutralizing Rinse**. Read product container for specific instructions and cautions with any cleaner. Never mix cleaners. Allow at least 24 hours of drying time before sealing (48 hours if power washing has been done or if temperature is cool). Applying sealer to a damp or incompletely cured surface may cause a hazy appearance or loss of adhesion.

After tamping down the joint sand and sweeping the application area clean, be sure the sand is at least 1/8 inch below the surface of the pavers. The sand should be dry to its full depth before sealing for best results.

Note: Before applying product to the entire surface, test several small areas to verify the product's appearance, penetration and protective ability.

Application Procedure: Use garden-type sprayer, low pressure airless sprayer, brush, short nap roller or squeegee for application. Apply one coat in liberal saturating manner so that joints are saturated with PAVER SEALER. Ensure that all joints are flooded to maximize

sealer soaking into the dry sand. Roll back or squeegee any excess product to avoid puddling on the surface. Allow additional drying time in moist, cool climates. An optional second coat may be applied after two hours if desired to increase protection and gloss. Do not over apply or puddle. For added slip resistance **Glaze' N Seal Grip 'n Seal Slip Resistance Additive** may be added to the final coat of sealer.

Coverage: 100 to 250 square feet per gallon depending on porosity of surface and method of application.

Limitations: Apply in temperatures between 45°F and 90°F. Air and surface temperature should be above 45°F for 24 hours before and after sealing. Clean up applicator tools with water immediately after use. Do not apply this sealer to areas where sealer will be immersed such as fountains, pools or below grade areas. Do not use on porcelain, polished stone, granite or marble. For professional use only.

WARRANTY: Glaze 'N Seal product liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective and does not include any labor costs or consequential damages. It is the user's responsibility to determine the safety, toxicity and suitability of this product.

WARNING: Hazard Statements: Suspected of causing cancer. Causes serious eye irritation. **Prevention Statements:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. **Response Statements:** If exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **Storage and Disposal:** Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

VOC is <100 grams per liter.

ADVANCED PAVER CARE PRODUCT LINE

“Enhanced Look” Paver Sealer is part of **Glaze 'N Seal's Advanced Paver Care** line of products to protect, maintain, and restore. This state of the art product line includes sealers, polishes, cleaners and restoration products. All products are effective, safe to use and easy to use.

For additional information, contact your Glaze 'N Seal dealer or contact Glaze 'N Seal directly.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • www.glaze-n-seal.com