



Multi-Purpose Sealer

***Indoors & Outdoors
Waterseals & protects
Improves appearance
Medium Gloss
Contractor's Choice***



**For all Decorative and Stamped Concrete,
Natural and Manufactured Stone, Pavers,
Brick, Stucco and Slate**

- Repels Oil and Grease Stains
- Efflorescence Resistant
- Long Lasting
- Breathable
- Blush Free Formula



Professional Results...GUARANTEED!

1-800-486-1414

www.glaze-n-seal.com





STAIN RESISTANT MULTI-PURPOSE SEALER CONCRETE, TILE & MASONRY

FORMULATED SPECIFICALLY FOR

- ALL DECORATIVE CONCRETE • PAVERS • SLATE • FLAGSTONE
- COLORED AND HARD TROWELED CONCRETE • BRICK • TERRAZZO
- STAMPED CONCRETE • EXPOSED AGGREGATE CONCRETE

PRODUCT DESCRIPTION

A clear acrylic waterbase finish designed to protect and beautify concrete, tile and masonry surfaces. Glaze 'N Seal protects against all organic stains including cooking oil, grease and beverages. It may be used indoors or outdoors and is extremely easy to apply and maintain. Non-yellowing.

USES

- Waterseals, protects and improves appearance of all unglazed tile, stamped and exposed aggregate concrete, brick, natural and manufactured stone, stucco and slate.
- Use as a base for interior finishes such as Glaze 'N Seal Acrylic Floor Polish.
- Use to seal concrete and masonry surfaces prior to painting or apply over painted or color stain surfaces for added protection and improved appearance.
- Use indoors and outdoors.
- Ideal to protect concrete countertops.

FEATURES

- Repels Oil and Grease Stains
- Breathable
- Cleans up with Water
- Easy to Apply — Long Lasting
- Will not blush
- Reduces Efflorescence
- Recoatable
- Qualifies for LEED points

PREPARATION

All surfaces must be free of efflorescence, dirt, oil, wax, grease and defective paint or sealers. If muriatic acid is used, all acid residue must be removed prior to application of sealer. Do not allow acid to dry. Use **Glaze 'N Seal Neutralizing Rinse** to neutralize surface before sealing.

APPLICATION

Apply two or more coats of sealer (do not allow it to puddle). Make sure each coat is dry to the touch before applying second coat; usually one to three hours.

Allow additional drying time in moist climates. It can be applied with a brush, roller, wax applicator, or spray equipment dependent on porosity and roughness of surface. Clean tools with water before sealer dries. Apply between 55° and 80°F. If it is necessary to apply sealer on a warm day in direct sunlight, slightly dampen the surface to be sealed with a fine spray of water prior to application of the

sealer. Allow 72 hours curing time against heavy moisture and bulk water. Sealer will continue to gain strength for up to one week.

Important Note: Always test a small area of surface to be sealed to verify penetration and satisfaction of sealed appearance.

SPECIFICATIONS

Base	Aqueous Acrylic Copolymer
Tukon Hardness	+6.0
Friction Level	Excess 6.5
Glass Transition Point	34C
Density	8.58 lbs. per gallon
Refractive Index	Approx. 1.4077
Solids	Excess 16%
Appearance	Milky White — Dries Clear

Coverage: 100 to 400 square feet per gallon dependent on porosity of the surface.

Maintenance: **Glaze 'N Seal Floor Polish** is recommended as a protective finish over the sealer (indoors only). Sweep and damp mop floor frequently.

Packaging: Available in quarts, gallons, 5 gallons and 55 gallon drums.

SAFETY INFORMATION: CAUTION, Liquid contact with eyes and skin causes irritation. Do not ingest. Wash hands thoroughly after use. FIRST AID: Should eye contact occur, flush with plenty of water for 15 minutes. If irritation persists get medical attention. For skin contact flush skin with plenty of soap and water. If irritation persists get medical attention. If swallowed get medical attention immediately. Do not induce vomiting.

This product does not meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910.1200 or the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.



This product contains Ethylene Glycol which is known to the State of California to be a developmental hazard if ingested. For more information, go to www.P65Warnings.gov.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • 800/486-1414
www.glaze-n-seal.com