



ADVANCED PAVER CARE

NATURAL LOOK Paver Sealer

Plus SAND LOCK for Interlocking Pavers and Bricks



LOCKS SAND BETWEEN JOINTS AND SEALS IN ONE STEP!

- No Gloss, Easy to Apply
- Slight Color Enhancement
- Low Maintenance
- Resists Oil, Grease & Fading
- Resists Weeds & Mildew
- Resists Color Fading



Professional Results...**GUARANTEED!**

1-800-486-1414

www.glaze-n-seal.com





“NATURAL LOOK” PAVER SEALER

Plus SAND LOCK for Interlocking Pavers and Bricks

Product Uses: Seals pavers and bricks & locks in sand joints in one easy coat. Excellent resistance to stains, efflorescence, weeds, and UV fading. Natural low-gloss finish is easy to maintain.

Special Features:

- Reduces efflorescence
- Reduces freeze thaw effects
- Resists oil, grease rust stains
- Locks sand between joints
- Non-flammable
- Recoatable
- Cleans up with water
- Prevents weed growth
- Low VOC
- LEED eligible

DO NOT SHAKE — DO NOT ALLOW TO FREEZE

Surface Preparation: Prior to the application of **Glaze 'N Seal** products, surface must be thoroughly clean and dry. Remove all dirt, oil, grease, paint, efflorescence and surface sealers. General cleaning may be done using **Glaze 'N Seal Heavy Duty Cleaner for Concrete and Masonry**. For efflorescence stains use **Glaze 'N Seal Efflorescence Remover**. When acid has been used for any reason, surface must be neutralized. We recommend **Glaze 'N Seal Neutralizing Rinse**. Read product container for specific instructions and cautions with any cleaner. Never mix cleaners. Allow at least 24 hours of drying time before sealing (48 hours if power washing has been done or if temperature is cool). New concrete pavers should cure 14 days or more before sealing. Applying sealer to a damp or incompletely cured surface may cause a hazy appearance or loss of adhesion.

After tamping down the joint sand and sweeping the application area clean be sure the sand (regular or polymeric) is at least 1/8 inch below the surface of the pavers. The sand should be dry to its full depth before sealing for best results.

Note: Before applying **Glaze 'N Seal** products to the entire surface, **test** several small areas to verify the product's appearance, penetration and protective ability.

Application Procedure: Use garden-type sprayer, low pressure airless sprayer, brush, short nap roller or squeegee for application. Apply one coat in liberal saturating manner to ensure that joints are flooded. (If sand is being sealed use a squeegee, not a roller, to remove excess sealer and avoid puddling). Allow additional drying time in moist, cool climates. An optional second coat may be applied after two hours if desired to increase protection and gloss. Recoat as needed. For added slip resistance **Glaze' N Seal Grip 'n Seal Slip Resistance Additive** may be added to the second coat of sealer.

Coverage: 75 to 150 square feet per gallon depending on porosity of surface and method of application.

Limitations: Apply in temperatures between 45°F and 90°F. Air and surface temperature should be above 45°F for 24 hours before and after sealing. Clean up applicators with water immediately after use. Do not apply this sealer to areas where sealer will be immersed such as fountains, pools or below grade areas. Do not use on porcelain, polished stone, granite or marble. For professional use only.

WARRANTY: Glaze 'N Seal product liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective and does not include any labor costs or consequential damages. It is the user's responsibility to determine the safety, toxicity and suitability of this product.

SAFETY INFORMATION: CAUTION, Liquid contact with eyes and skin causes irritation. Do not ingest. Wash hands thoroughly after use. FIRST AID: Should eye contact occur, flush with plenty of water for 15 minutes. If irritation persists get medical attention. For skin contact flush skin with plenty of soap and water. If irritation persists get medical attention. If swallowed get medical attention immediately. Do not induce vomiting. This product contains a chemical known in the State of California to cause cancer.

WARNING

Contains Acrylic Polymers — Harmful if swallowed.
Do NOT induce vomiting — call a physician.
KEEP OUT OF REACH OF CHILDREN

VOC is <100 grams per liter.

Complies with SCAQMD regulations.

This product does not meet the definition of a hazardous substance or preparation as defined by 29 CFR 1910.1200 or the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

ADVANCED PAVER CARE PRODUCT LINE

“Natural Look” Paver Sealer is part of **Glaze 'N Seal's Advanced Paver Care** line of products to protect, maintain, and restore. This state of the art product line includes sealers, polishes, cleaners and restoration products. All products are effective, safe to use and easy to use.

For additional information, contact your Glaze 'N Seal dealer or contact Glaze 'N Seal directly.



Quality Products for Concrete, Tile and Masonry

Glaze 'N Seal Products, Irvine, CA • www.glaze-n-seal.com