

# SAFETY DATA SHEET

## 1. Identification

### Product identifier

#### Product list

### Paper Faced Gypsum Panels

#### Product List A

ToughRock® Veneer Plaster Base (Blueboard)  
ToughRock® Flexroc® Gypsum Board  
ToughRock® Mold-Guard™ Gypsum Board  
ToughRock® Basement Board® Gypsum Board  
ToughRock® Sound Deadening Gypsum Board  
ToughRock® Stretch 54® Gypsum Board  
ToughRock® Soffit Board

#### Product List B

ToughRock® Gypsum Board

#### Product List C

ToughRock® Span 24® Lite-Weight Ceiling Board  
ToughRock® Stretch 54® Lite-Weight Gypsum Board  
ToughRock® Lite-Weight Gypsum Board  
ToughRock® MH Ceiling Board  
ToughRock® Fireguard X® Gypsum Board  
ToughRock® Fireguard 45® Gypsum Board

#### Product List D

ToughRock® Gypsum Sheathing  
ToughRock® Span 24® Ceiling Board  
ToughRock® Fireguard X® Gypsum Sheathing  
ToughRock® Fireguard X® Stretch 54® Gypsum Board  
ToughRock® Fireguard X® Mold-Guard™ Abuse-Resistant Gypsum  
ToughRock® Fireguard X® Veneer Plaster Board  
ToughRock® Fireguard X® Mold-Guard™ Gypsum Board  
ToughRock® Fireguard X® Mold-Guard™ Max-Abuse Gypsum Board  
ToughRock® Fireguard X® Mold-Guard™ Max-Impact Gypsum Board

#### Product List E

ToughRock® Shaftliner  
ToughRock® Fireguard C® Soffit Board  
ToughRock® Fireguard C® Stretch 54® Gypsum Board  
ToughRock® Lite-Weight Fire-Rated Gypsum Board

#### Product List F

ToughRock® Fireguard C® Gypsum Board  
ToughRock® Lite-Weight Veneer Plaster Base

### Other means of identification

#### Product code

GP-71A

### Recommended use

Products accommodate wide range of wall, floor and ceiling applications and soffit treatments.

### Recommended restrictions

Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

## Manufacturer/Importer/Supplier/Distributor information

<b>Company name</b>	Georgia-Pacific Gypsum LLC		
<b>Address</b>	133 Peachtree Street, NE Atlanta, GA 30303		
<b>Telephone</b>	Technical Information	800.225.6119	
	(M)SDS Request	404.652.5119	
<b>E-mail</b>	Not available.		
<b>Emergency phone number</b>	Chemtrec - Emergency	800.424.9300	

## 2. Hazard(s) identification

<b>Emergency overview</b>	This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities such as cutting, sanding, or otherwise working with this product that generate large amount of dusts. Those hazards associated with large amount of dusts are described below.		
<b>Physical hazards</b>	Not classified.		
<b>Health hazards</b>	Eye irritation	Category 2B	
<b>Environmental hazards</b>	Not classified.		
<b>OSHA defined hazards</b>	Not classified.		
<b>Label elements</b>			
<b>Hazard symbol</b>	None.		
<b>Signal word</b>	Warning		
<b>Hazard statement</b>	Causes eye irritation.		
<b>Precautionary statement</b>			
<b>Prevention</b>	Wash thoroughly after handling. Observe good industrial hygiene practices.		
<b>Response</b>	Wash hands after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.		
<b>Storage</b>	Store away from acids.		
<b>Disposal</b>	Dispose of contents/container in accordance with applicable regulations.		
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.		
<b>Supplemental information</b>	None.		

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
CALCIUM SULFATE DIHYDRATE		10101-41-4	≤ 95
VERMICULITE****		1318-00-9	0 - 3
BORIC ACID**		10043-35-3	0.1 - 1
CONTINUOUS FILAMENT GLASS FIBERS***		65997-17-3	0.1 - 1
CRYSTALLINE SILICA (QUARTZ)*		14808-60-7	≤ 0.2

### Composition comments

\*\* Found in products in List B, C and F, Section 1 of this SDS.

\*\*\* Found in products in List C, D, E and F, Section 1 of this SDS.

\*\*\*\* Found in products in List E and F, Section 1 of this SDS.

Gypsum (calcium sulfate, dihydrate) contains naturally occurring silica crystalline (quartz), which is listed as a lung carcinogen. See Section 8 for exposure information.

\*The weight percent for crystalline silica represents total crystalline silica and not the respirable fraction. Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

\*\*Testing conducted by Georgia-Pacific did not detect boric acid during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

## 4. First-aid measures

<b>Inhalation</b>	If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	For skin contact, wash immediately with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Do not rub the eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. May result in obstruction and irritation if ingested. Get medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Firefighters should wear full protective clothing including self contained breathing apparatus.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Use personal protection recommended in Section 8. Keep unnecessary personnel away.
<b>Methods and materials for containment and cleaning up</b>	Minimize dust generation. Sweep up or gather material and place in an appropriate container for disposal. Utilize wet methods, if appropriate, to minimize dust. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Keep out of drains, sewers, ditches, and waterways.

## 7. Handling and storage

<b>Precautions for safe handling</b>	Provide appropriate exhaust ventilation at places where dust is formed. Minimize dust generation and accumulation. Do not breathe dust. Do not get this material in contact with eyes. Do not taste or swallow. Avoid prolonged exposure. Observe good industrial hygiene practices. Use only in well-ventilated areas. Wear appropriate NIOSH/MSHA approved dust mask or filtering facepiece if dust is generated. Do not eat or drink while using the product. Wash hands before eating, drinking, or smoking.
<b>Conditions for safe storage, including any incompatibilities</b>	Store level and keep dry. Dewpoint or other conditions causing the presence of moisture can damage the product during storage. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US OSHA Table Z-3: Time Weighted Average (TWA) (mg/m3)

Components	Type	Value	Form
VERMICULITE**** (CAS 1318-00-9)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	PEL	5 mg/m3	Respirable fraction.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	PEL	15 mg/m3 0.05 mg/m3	Total dust. Respirable dust.

**ACGIH**

Components	Type	Value	Form
CONTINUOUS FILAMENT GLASS FIBERS*** (CAS 65997-17-3)	TWA	5 mg/m3	Inhalable fraction.

**US ACGIH Threshold Limit Values: Short Term Exposure Limit (STEL): mg/m3**

Components	Type	Value	Form
BORIC ACID** (CAS 10043-35-3)	STEL	6 mg/m3	Inhalable fraction.

**US ACGIH Threshold Limit Values: Time Weighted Average (TWA): mg/m3, non-standard units**

Components	Type	Value	Form
BORIC ACID** (CAS 10043-35-3)	TWA	2 mg/m3	Inhalable fraction.
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	10 mg/m3	Inhalable fraction.
CONTINUOUS FILAMENT GLASS FIBERS*** (CAS 65997-17-3)	TWA	1 fibers/cm3	Fiber.
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)	TWA	5 mg/m3	Respirable.
CONTINUOUS FILAMENT GLASS FIBERS*** (CAS 65997-17-3)	TWA	10 mg/m3 5 mg/m3	Total Fiber, total
CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

\*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

\*\*Testing conducted by Georgia-Pacific did not detect boric acid during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

**Appropriate engineering controls** Score and snap method recommended. When using product, provide local and general exhaust ventilation to keep airborne dust concentrations below exposure limits. Use wet methods, if appropriate, to reduce the generation of dust. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Safety glasses or goggles are recommended when using this product. Ensure compliance with OSHA's PPE standard (29 CFR 1910.132 and .133) for eye and face protection. Eye wash fountain is recommended.

**Skin protection**

**Hand protection** For prolonged or repeated skin contact use suitable protective gloves.

**Other**

Impervious protective clothing and gloves recommended to prevent drying or irritation of skin. Ensure compliance with OSHA's PPE standards (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).

**Respiratory protection** A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards** Not applicable.

**General hygiene considerations** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Keep away from food and drink.

**9. Physical and chemical properties**

**Appearance** Paper faced gypsum boards

**Physical state** Solid.

**Form** Solid.

**Color** Facing color varies

**Odor** Odorless

**Odor threshold** Not available.

**pH** 7

**Melting point/freezing point** 2642 °F (1450 °C) estimated

**Initial boiling point and boiling range** Not applicable

**Flash point** Not applicable

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not available.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** Not applicable

**Flammability limit - upper (%)** Not applicable

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** Not applicable

**Vapor density** Not applicable

**Relative density** 2.2 - 2.4 g/cm3

**Solubility(ies)**

**Solubility (water)** 0.2 % @ 22°C

**Partition coefficient (n-octanol/water)** Not applicable

**Auto-ignition temperature** Not applicable

<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not applicable
<b>Other information</b>	
<b>Flash point class</b>	Not flammable
<b>Specific gravity</b>	2.2 - 2.4

## 10. Stability and reactivity

<b>Reactivity</b>	Contact with strong acids produces carbon dioxide.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Contact with incompatible materials. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
<b>Incompatible materials</b>	Acids.
<b>Hazardous decomposition products</b>	May include and are not limited to: calcium oxide and sulfur dioxide.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Inhalation of dusts may cause respiratory irritation.
<b>Skin contact</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.
<b>Eye contact</b>	Dust in the eyes will cause irritation.
<b>Ingestion</b>	Not applicable under normal conditions of use. May cause gastrointestinal irritation if ingested.

**Symptoms related to the physical, chemical and toxicological characteristics** Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort.

### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results
BORIC ACID** (CAS 10043-35-3)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 2 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	2660 mg/kg
CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	> 1581 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

**Serious eye damage/eye irritation** Dust in the eyes will cause irritation.

#### Respiratory or skin sensitization

<b>Respiratory sensitization</b>	Not likely to cause respiratory sensitization.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** Not classified.

**Carcinogenicity** Not expected to be hazardous by OSHA/WHMIS criteria.

Exposure to respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of respirable crystalline silica exposure and the length of time (usually years) of exposure.

### IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7) 1 Carcinogenic to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7) Cancer

### US. National Toxicology Program (NTP) Report on Carcinogens

CONTINUOUS FILAMENT GLASS FIBERS\*\*\* (CAS 65997-17-3) Reasonably Anticipated to be a Human Carcinogen.

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7) Known To Be Human Carcinogen.

<b>Reproductive toxicity</b>	Not classified.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not classified.
<b>Chronic effects</b>	Not hazardous under normal conditions of use.
<b>Further information</b>	*Testing conducted by Georgia-Pacific did not detect respirable crystalline silica during activities associated with the normal use of this product; however, jobsite air monitoring should be conducted to determine actual exposure when permissible exposure limits may be exceeded.

## 12. Ecological information

**Ecotoxicity** Not considered to be harmful to aquatic life.

Components		Species	Test Results
<b>BORIC ACID** (CAS 10043-35-3)</b>			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	766.5 mg/L, 48 Hours
Fish	LC50	Razorback sucker ( <i>Xyrauchen texanus</i> )	> 100 mg/l, 96 hours
<b>CALCIUM SULFATE DIHYDRATE (CAS 10101-41-4)</b>			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	> 1970 mg/l, 96 hours
<b>CONTINUOUS FILAMENT GLASS FIBERS*** (CAS 65997-17-3)</b>			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Zebra danio ( <i>Danio rerio</i> )	> 1000 mg/l, 96 hours ECHA
<b>CRYSTALLINE SILICA (QUARTZ)* (CAS 14808-60-7)</b>			
<b>Aquatic</b>			
<i>Acute</i>			
Fish	LC50	Zebra danio ( <i>Danio rerio</i> )	> 10000 mg/l, 96 Hours OECD SIDS

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

<b>Disposal instructions</b>	Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations.
<b>Contaminated packaging</b>	Not available.

## 14. Transport information

### DOT

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## 15. Regulatory information

### US federal regulations

This product is not hazardous in the form in which it is sold and shipped by the manufacturer. However, the large amount of dusts generated by downstream activities such as cutting, sanding, or otherwise working with this product is considered hazardous and is regulated under the Hazard Communication Standard 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7) Cancer  
lung effects  
immune system effects  
kidney effects

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - No  
Fire Hazard - No  
Pressure Hazard - No  
Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

#### SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

### US state regulations

#### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

BORIC ACID\*\* (CAS 10043-35-3)  
CRYSTALLINE SILICA (QUARTZ)\* (CAS 14808-60-7)

#### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.



## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	March-13-2015
<b>Revision date</b>	September-22-2017
<b>Version #</b>	03
<b>HMIS® ratings</b>	Health: 1 Flammability: 0 Physical hazard: 0
<b>NFPA ratings</b>	Health: 1 Flammability: 0 Instability: 0
<b>Disclaimer</b>	This SDS is intended to quickly provide useful information to the user(s) of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.
<b>Revision information</b>	Product and Company Identification: Product Codes Accidental release measures: Methods and materials for containment and cleaning up Handling and storage: Conditions for safe storage, including any incompatibilities GHS: Classification