Submittal Sheet

Submittal Sheet #03040910-RG

Trim Head Streaker® GrabberGard® Screws (214X)

Product:	Item#	Description	Unit Pack
	17S76RG	8 x 3-in, Trim Head, Streaker®, GrabberGard®, Bulk	2,000
	17SRG	7 x 1-5/8-in, Trim Head, Streaker®, GrabberGard®, Bulk	10,000
	18SRG	7 x 2 1/4-in, Trim Head, Streaker®, GrabberGard®, Bulk	5,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Streaker	Exterior Wood	Trim Head	0.151	0.219	#7-15	1.625	Streaker	1.125	25 ga.	20 ga.	RG
Streaker	Exterior Wood	Trim Head	0.151	0.219	#7-15	2.25	Streaker	1.5	25 ga.	20 ga.	RG
Streaker	Exterior Wood	Trim Head	0.164	0.219	#8-15	3	Streaker	2.02	25 ga.	20 ga.	RG

Application: GRABBER's trim head Streaker® is used to attach wood or plastic trim over single and double layer gypsum to 20-25 gauge steel or wood.

Description: Low profile trim head, #1 Phillips or #1 square drive, fine 18 TPI, phosphate finish with extra sharp. Grabber Trim Steakers are available in GrabberGard® Exterior finish and are ACQ compliant.

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Trim head is completely seated when the head is flush or slightly counter sunk with the work surface. Overdriving may result in failure of the fastener or stripping of the head recess.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved.



Submittal Sheet #03040910-RG

SUBMITTAL APPROVALS:

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Submittal Sheet #03040910-RG

Trim Head Streaker® GrabberGard® Screws (214X)

PRODUCT SPECIFICATIONS	
Application	Composite Decking
Application	Composite Decking
Fastener Classification	Exterior Wood
Fastener Head	Trim
Fastener Drive	#1 Square
Fastener Gauge	#7, #8
Fastener Point	Streaker
Fastener Package Type	Packaged Screws
Fastener Package Weight	1lb Box, Bulk Box
Fastener TPI	15
Fastener Coating	GrabberGard

STANDARD CORROSION TEST RESULTS			
Finish	**Test**	**Standard/Protocol**	**Results**
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.