

## **SUBMITTAL SHEET**

Submittal Sheet #GSCSF

## **Grabber Acoustical Sound Sealant**

Product:	Item# Description		Unit Pack		
	GSCSF	Grabber Acoustical Sound Sealant	12 tubes per case		
Product	Exceeds the requirements of ASTM C834. Tested in accordance with ASTM E84, ASTM E90 and ASTM C919. Meets NFPA Class A fi re rating.				
Features:	WICCIS IVI I A	Olass A II Te Talling.			
	Environmentally safe – VOC-compliant Eliminates sound transmission and seals air gaps Improves STC Values and upgrades sound quality LEED EQ Credit 4.1: Low-Emitting-material, Adhesives and Sealants SCAQMD Rule 1168 Compliant UL 723 classified • Meets GS-36 requirements Repairs cracks and eliminates rattles in drywall and plaster Mold and mildew resistant Easily tools with one pass Cleans easily with water in wet state Post-consumer recycled cartridge and carton Paintable				

Sound	Edge Detail	STC Rating	Comments
Transmission	Uncaulked	29	The open-edge track gave the STC value of 29 through direct leakage
Class (STC)	Single bead at the perimeter of one	49	This bead closed void but did seal leakage around
Ratings:	base layer Two beads, one under each base layer of gypsum board	53	the joint between wallboard and track The beads closed void and sealed leakage around track

Note: Taken from ASTM C919. The test partitions of metal studs 610 mm (24 in.) on center, with double layers of 13 mm (0.5 in.)

Surface Burning	FLAME	SMOKE	Comments
Characteristics	0.0	0.0	Flame Smoke Tested as applied in two 1/4" diameter beads, 8 in. O.C.
For Building	0.0	0.0	(Coverage: 2.8 percent of the exposed test sample
materials:			area).



Submittal Sheet #GSCSF

ce:
nall not be liable for incidental and consequential ges, directly or indirectly sustained, nor for any loss d by application of these goods not in accordance with at printed instruction or for other than the intended use. ability is expressly limited to replacement of defective and Any claim shall be (30) days of the date it was or mably should have been discovered.