


EXTERIOR WOOD

Product #DM110 Deckmaster® Joist Screws (1 OF 2)

For fastening Deckmaster brackets to joists

Finish - GRABBERGARD









APPLICATIONS

Deckmaster Hidden Fastening System

PRODUCT FEATURES

- > Pan head provides a flat bearing surface
- ▶ Available in #2 Square, and #2 LOX® recess drive

SPECIFICATIONS

- ▶ Gauge #8
- Length 1"
- ▶ Head Type Pan
- ▶ Recess Type #2 Square
- Thread Type Single Lead
- Finish 302 Stainless Steel and GRABBERGARD
- GRABBER[®] screws are manufactured in an ISO 9001 and ISO 14001 certified.

INSTALLATION GUIDELINES

- Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and 2500 RPM.
- > The Pan head is fully seated when the head is flush with the work surface.
- Overdriving may result in failure of the fastener or strip out of the work surface.

EXTERIOR WOOD

Product #DM110

Deckmaster[®] Joist Screws (2 OF 2)


PRODUCT SIZES AND ORDERING INFORMATION						
Catalog No.	Gauge/Length	Length Metric	Quantity Per Carton	Weight Per Carton		
DM100JP-100	#8x1"	25 mm	1100	14.00(lbs)		

PRODUCT DIMENSIONS (MILLIMETERS)

Gauge	B Head Dia	Recess Depth	W Gauging Width	d Shank Dia	d1 Minor Dia	d2 Major Dia	TPI
#6	8.00	0.50	#2	2.68	2.25	3.75	8
	8.50	0.80		2.72	2.45	3.95	
#7	8.00	0.50	#2	2.93	2.50	4.05	8
	8.50	0.80		2.97	2.80	4.30	
#8	8.00	0.50	#2	3.18	2.80	4.30	8
	8.50	0.80		3.22	3.10	4.60	
#10	8.50	0.50	#2	3.78	3.20	5.00	8
	8.90	0.80		3.82	3.50	5.30	

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
GRABBERGARD	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GRABBERGARD	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust



All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with ASME B18.6.1. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

