



SUBMITTAL SHEET

DESCRIPTION: DRYWALL NAIL LARGE FLAT HEAD DIAMOND POINT

PRODUCT:

- DWAT125 – Drywall Nail RS, 12.5 Ga Wire x 19/64" Hd x 1 1/4" Length
 - DWAT138 – Drywall Nail RS, 12.5 Ga Wire x 19/64" Hd x 1 3/8" Length
 - DWAT158 – Drywall Nail RS, 12.5 Ga Wire x 19/64" Hd x 1 5/8" Length
 - DWAT200 – Drywall Nail RS, 12.5 Ga Wire x 19/64" Hd x 2" Length
-

SCOPE:

- 2015, 2012, 2009 and 2006 International Building Code® (IBC)
 - 2015, 2012, 2009 and 2006 International Residential Code® (IRC)
 - 1997 Uniform Building Code TM (UBC)
 - 2014 Florida Building Code
 - 2013 California Building Code
-

APPLICATION:

Gypsum panels to wood.

SUBMITTAL SHEET

November 3, 2015

JOB NAME:

CONTRACTOR:

DATE:

TRADEMARKS the following trademark used herein is owned by Grabber Construction Products Inc.
: GRABBER

NOTICE: We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

SPECIFICATIONS

SUBMITTAL SHEET November 3, 2015

Dimensions

| | | | |
|------------------------|----------|---------------------------|----------|
| Assembled Depth (in.) | Assorted | Fastener head width (in.) | 19/64 |
| Assembled Height (in.) | Assorted | Fastener length (in.) | Assorted |
| Assembled Width (in.) | Assorted | Nail Length (In.) | Assorted |

Details

| | | | |
|-----------------------------|--------|-------------------------|----------|
| Angle (Degrees) | N/A | Exposure | Indoor |
| Collation material | N/A | Nail Gauge | 12.5 |
| Fastener Callout Size | 0.099 | Nail Type | Smooth |
| Fastener Head Style | Round | Package Quantity | Assorted |
| Fastener Type | Nail | Product Weight (lb.) | Assorted |
| Fastener/Connector Material | Steel | Specialty Fastener Type | Drywall |
| Finish Family | Bright | | |

STANDARDS:

| | |
|-----------------------|--|
| A510M (Metric) | Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel |
| ASTM C514-04(2014) | Standard Specification for Nails for the Application of Gypsum Board |
| ASTM F1667 – 13 | Standard Specification for Driven Fasteners: Nails, Spikes, and Staples |
| ASTM F1575 - 03(2013) | Standard Test Method for Determining Bending Yield Moment of Nails |
| A153/A153M | Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware |
| A641/A641M | Specification for Zinc-Coated (Galvanized) Carbon Steel Wire |
| B695 | Specification for Coatings of Zinc Mechanically Deposited on Iron and Steel |
| F680 | Test Methods for Nails |
| F1575 | Test Method for Determining Bending Yield Moment of Nails |