

Double unit complete with guard rail
and outriggers (12' H x 6' L x 29" W)



Contractor Grade Scaffolding

Designed with your safety in mind

- ▶ **Maximum Capacity 1,000 lbs.**
- ▶ **High-strength structural steel tubing**
- ▶ **Powder-coated with high UV finish**
- ▶ **Compatible with major scaffold brands**
- ▶ **Meets OSHA safety requirements**
- ▶ **Available in 4', 6' and 8' lengths**



Mini Scaffold



- ▶ **1" Tubular Steel Frame**
- ▶ **Twin Steel Platforms**
- ▶ **Fold Down Flat (4")**
- ▶ **Holds up to 600 lbs.**
- ▶ **4', 5' and 6' models available**

All Grabber Scaffolds, Sawhorses, Drywall Carts, and Benches meet or exceeds requirements of ANSI Code A10.8 Read and follow O.S.H.A. codes and regulations

Drywall Cart



GDC1C - Unit pictured
GDC2C - Heavy Duty Unit
GDC3C - Extra HD Unit
GDC4C - Corner Unit
For Drywall, Paneling, Plywood and Glass

Contractor Grade Sawhorses

- ▶ Holds up to 1600 pounds in pairs
- ▶ Folds flat for easy transporting and convenient storage
- ▶ OSHA Certified
- ▶ Weighs just 13 pounds

FOLD N' GO™



Locks



User friendly squeeze lock with thumb locking wheel. Additional snap pin provides a dual-locked scaffold system.

Alignment Pins



Four platform alignment pins when in place assures that the platform is level and secure. Unit stays together when adjusting the platform.

Stacking Pins



Stacking pin with hole for fastening the top unit with the base unit.

5" Casters



5" swivel casters with lock to prevent both rolling and swiveling when in use. Comes with snap pin to fasten the caster to the unit.

Platform



Edge banding protects all four sides without using rivets, screws or staples. Handle holes on each side make for ease in handling. Platform is held in place with four spring-loaded retaining clips.

Outriggers



Use outriggers on all units more than 1 base unit high. Outrigger includes:

- ▶ 2 - snap pins
- ▶ 1 - thumb screw
- ▶ (5" caster sold separately)