



GRABBER PROFESSIONAL  
DRYWALL ADHESIVE

PHYSICAL PROPERTIES (TYPICAL)	<b>Type</b> Synthetic elastomeric polymer	<b>Weight/gallon</b> 10.25 lbs.
	<b>State</b> Medium-viscosity mastic	<b>Flashpoint</b> Less than 0°F.
	<b>Color</b> Tan	<b>Freeze/thaw stability</b> Will not freeze
	<b>Solids</b> 74%	<b>Storage life</b> 12 months in tightly closed containers at 75°F.
	<b>Viscosity</b> 150,000 cps	
	<b>Calculated VOC:</b> 327 g/L	

APPLICATION GUIDELINES	<b>Application temperature</b> 40°F. to 110°F.			
	<b>Service temperatures</b> 0°F. to 150°F.			
	<b>Method of application</b> Cartridge/caulking gun			
	<b>Coverage (maximum)</b> Approximate length of bead according to bead diameter:			
	Container	1/8" bead	1/4" bead	3/8" bead
	29 oz. Cartridge	355 ft.	89 ft.	39 ft.
	<b>Working time</b> Approximately 60 minutes for 1/4" bead			
	<b>Working surfaces</b> Surfaces to be bonded should be clean, dry and free from excessive oil, grease, water, dirt or any other material that may deter adhesion.			
	<b>Cleanup</b> Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.			

PRODUCT FEATURES	<ul style="list-style-type: none"> <li>• Ideal for use on plywood, hardboard, gypsum wallboard, cold-rolled steel, galvanized steel and aluminum</li> <li>• Exceeds the ASTM C-557 specification</li> <li>• Strong initial tack allows panels to be positioned quickly without slipping</li> <li>• Resists aging – will not become hard or brittle</li> <li>• Exposure to moisture or intermittent cold water immersion has little effect on the dried bond</li> <li>• Fills irregularities and gaps in substrates, providing a more solid backup surface</li> </ul>
---------------------	--

LIMITATIONS	Do not use on polystyrene foam or rigid plastics such as A.B.S. or high-impact polystyrene. Do not use on vinyl-backed drywall.
-------------	---

ORDERING INFORMATION	Cat. No.	Size	Units per Package	Weight	Packages per Pallet
	GDWAF	29 oz. Cartridge	12	30	38

CAUTION STATEMENT	<p><b>DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL.</b> Contains Hexane and Toluene. Keep away from heat, sparks and flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvent in uncured product can cause central nervous system, peripheral nervous system, eye, skin or respiratory system effects. <b>First Aid:</b> If dizziness or other adverse health effects are experienced, move to fresh air; contact physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. <b>KEEP OUT OF THE REACH OF CHILDREN.</b></p> <p><b>WARNING:</b> This product contains toluene, a chemical known to the state of California to cause birth defects or other reproductive harm.</p>
----------------------	---

**Important Notice:** Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.