SAFETY DATA SHEET

Date of issue: 05/06/2015
Revised: 05/06/2015

Section 1: Identification

Trade name: **CLEAR INVERTED TIP**

Product code: GB00200631

Product category PC9a Paints and coatings.

Manufacturer/Supplier:
Grabber Construction Products
5255 West 11000 North
Highland, Utah 1-800-477-TURN
www.grabberman.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

Section 2: Hazard(s) Identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Carc. 2 H351 Suspected of causing cancer.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness. **GHS Hazard pictograms**

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated. Causes skin irritation.
Causes serious eye irritation. Suspected of causing cancer.
Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presentand easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If skin irritation occurs: Get medical advice/attention. If on skin: Wash with plenty of water.
If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/internationalregulations.

Section 3: Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
67-64-1	Acetone	17.89%
1317-65-3	Calcium Carbonate	15.19%
74-98-6	propane	13.86%
64742-47-8	Mineral Spirits	10.57%
106-97-8	n-butane	8.14%
64742-89-8	VM&P Naphtha	8.01%
111-76-2	Glycol Ether EB	5.25%
1330-20-7	xylene (mix)	2.53%

Section 4: First-Aid Measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

Section 5: Fire-Fighting Measures

Extinguishing agents: CO_2, extinguishing powder or water spray. Fight larger fires with waterspray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

Section 7: Handling and Storage

Precautions for safe handling Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

Section 8: Exposure Controls/Personal Protection

Components with limit values that require monitoring at the workplace:	
67-64-1 Acetone	
PEL (USA)	Long-term value: 2400 mg/m^3, 1000 ppm
REL (USA)	Long-term value: 590 mg/m^3, 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m^3, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m^3, (500) NIC-250 ppm BEI
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m^3, 1000 ppm
REL (USA)	Long-term value: 1800
TLV (USA)	mg/m^3, 1000 ppm refer to
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m^3, 800 ppm
TLV (USA)	Short-term value: 2370 mg/m^3, 1000 ppm
111-76-2 Glycol Ether EB	
PEL (USA)	Long-term value: 240 mg/m^3, 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m^3, 5 ppm Skin
TLV (USA)	Long-term value: 97
1330-20-7 xylene (mix)	
PEL (USA)	Long-term value: 435 mg/m^3, 100 ppm
REL (USA)	Short-term value: 655 mg/m^3, 150 ppm Long-term value: 435 mg/m^3, 100 ppm
TLV (USA)	Short-term value: 651 mg/m^3, 150 ppm Long-term value: 434 mg/m^3, 100 ppm BEI
Ingredients with biological limit values:	
67-64-1 Acetone	
BEI (USA)	5 0 m
111-76-2 Glycol Ether EB	
BEI (USA)	20 0 m g/
1330-20-7 xylene (mix)	
BEI (USA)	1 . 5

Hygienic protection:	Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.
Breathing equipment:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.
Hand protection:	Protective gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

Section 9: Physical and Chemical Properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	0.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	503.5 g/l / 4.20 lb/gl
VOC content (less exempt solvents):	49.2 %
MIR Value:	0.74
Solids content:	32.9 %

Section 10: Stability and Reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

Section 11: Toxicological Information

LD/LC50 values that are relevant for classification:		
106-97-8 n-butane		
Inhalative	LC50/4 h	658 mg/l (rat)
111-76-2 Glycol Ether EB		
Oral	LD50	1480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
1330-20-7 xylene (mix)		
Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)		
111-76-2	Glycol Ether EB	3
1330-20-7	xylene (mix)	3
NTP (National Toxicology Program)		
None of the ingredients is listed.		

Section 12: Ecological Information (non-mandatory)

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: Product does not contain CFC's.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

Section 13: Disposal Considerations (non-mandatory)

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

Section 14: Transport Information (non-mandatory)

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity ORM-D Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
ADR	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.1

Section 15: Regulatory Information

SARA Section 355 (extremely hazardous substances):	
None of the ingredients in this product are listed.	
SARA Section 313 (Specific toxic chemical listings):	
111-76-2	Glycol Ether EB
1330-20-7	xylene (mix)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:	
100-41-4	ethyl benzene

CANADIAN ENVIRONMENTAL PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

EPA:		
67-64-1	Acetone	I
111-76-2	Glycol Ether EB	NL
1330-20-7	xylene (mix)	I

Section 16: Other Information

Contact:	Regulatory Affairs
Date of preparation / last revision	05/06/2015 / -