GRABBER



Designed with Your Safety in Mind

- Min


 Earted

 4',

 Fo
 - Maximum Capacity 1,000 Lbs. Distributed
 - א Available in 4', 6' and 8' Lengths

Mini Scaffold

- Easy setup and tear down
- 4', 5' & 6' models
- Folds for compact storage



Distributed by:

Form gb-133-03-03-04



(12' H x 6' L x 29" W)

and outriggers

Grabber Concord 205 Mason Circle, Concord CA 94520 1.800.477.8876 www.grabberman.com

- 1			
- 1			
- 1			
- 1			
- 1			

Double unit complete with guard rail

Drywall Cart FOLD N'GO **Contractor Grade Sawhorses** ▶ Holds up to 1600 pounds ▶ Folds flat for easy transporting and convenient storage ■ OSHA Certified GDWC-2C - Heavy Duty Unit **¥** Weighs just 13 pounds ☑ GDWC-3D - Extra HD Únit ■ Satisfaction Guaranteed GDWC-4C - Corner Unit For Drywall, Paneling, Plywood and Glass **Stacking Pins Locks Alignment Pins** Four platform alignment pins User friendly squeeze lock with Stacking pin with hole for when in place assures that the fastening the top unit with the thumb locking wheel. Additional snap pin provides a dual-locked platform is level and secure. Unit base unit. scaffold system. stays together when adjusting the platform. **Platform 5" Casters Outriggers** 5" swivel casters with lock to Edge banding protects all four Use outriggers on all units more prevent both rolling and swiveling sides without using rivets, screws than 1 base unit high. Outrigger or staples. Handle holes on each includes: when in use. Comes with snap side make for ease in handling. ■ 2 - snap pins pin to fasten the caster to the

Platform is held in place with four

spring-loaded retaining clips.

unit.

1 - thumb screw

凶 (5" caster sold seperately)