


Cabinet Screw

Interior Wood















Description

Used for cabinet assembly and installation.

Specifications

Size | Gauge: #6

Length: 1 1/4 in. and 1 1/2 in.

Head Type: Pan Head

Recess Type: #2 Phillips or #2 Square Thread Type: Single Lead, Coarse

Finish: Phosphate

Quality Assurance: Grabber[®] fasteners are manufactured in ISO 9001 and ISO 14001 certified and approved factories.

LEED Reporting: The post-consumer

recycled steel content is 25%.

Compliance: n/a

Applications

- Cabinet assembly and installation
- Face frame assembly

Installation

- Use a standard screw gun with a depthsensitive nose piece. Suggested screw gun specification for optimal performance: size #6, up to 2,500 RPM.
- The pan head is fully seated when the bottom of the head is flush with the work surface.
- The fastener should penetrate the wood at least 5/8 in., in accordance with AWC-NDS for wood construction.
- Overdriving may result in failure of the fastener or failure of the wood board.

Features

- The flat-bearing surface provides reliable holding power.
- A coarse thread screw for general interior applications into wood.
- Type 17 point is designed to smoothly penetrate wood without cracking the surface.
- Conveniently available with Phillips or square recess.

Cabinet Screw

Interior Wood



Standard Corrosion **Test Results**

Finish	Test	Standard/Protocol	Results
Phosphate	Salt Spray	ASTM B117	24 hrs., no red rust

Note: Salt Spray Testing (SST) results are not intended to predict corrosion in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool for comparing different metals and different metal coatings in a tightly controlled, highly corrosive environment for specific periods of time. For more information about corrosion resistance, refer to Grabber's Coatings and Corrosion Resistance Classifications in the Technical Data section of Grabber Fastener Solutions, PG1000. Consult with a corrosion specialist or the architect or engineer of record for detailed guidance and recommendations specific to your project.



Product Dimensions

Size	B Head Dia.	Recess	D1 Minor Dia.	D2 Major Dia.	TPI ¹
#6	0.288 in.	#2 Phillips	0.101 in.	0.138 in.	20
	0.288 in.	#2 Square	0.101 in.	0.138 in.	20
	0.293 in.	#2 Square	0.100 in.	0.138 in.	12

¹TPI stands for Threads Per Inch. This is a count of the number of threads per inch measured along the length of a fastener.

Ordering Information and Product Options

Item No.	Size	Recess	Head Dia.	TPI ¹	Quantity	Weight	Special Features	
Phosphate								
90	6 x 1 1/2 in.	#2 Phillips	0.288 in.	20	5,000	27 lb.		
90-4	6 x 1 1/4 in.	#2 Phillips	0.288 in.	20	10,000	45 lb.		
902Q	6 x 1 1/2 in.	#2 Square	0.288 in.	20	5,000	26 lb.	Type 17 point	
902Q4	6 x 1 1/4 in.	#2 Square	0.288 in.	20	10,000	43 lb.		
902QCT	6 x 1 1/2 in.	#2 Square	0.293 in.	12	5,000	27 lb.		
90-4HLQ	6 x 1 1/4 in.	#2 Square	0.288 in.	20	10,000	45 lb.	Type 17 point, Hi-Low thread	

¹TPI stands for Threads Per Inch. This is a count of the number of threads per inch measured along the length of a fastener.

Note: Product availability is subject to change without prior notice and the availability of products may differ from what is printed in literature and displayed on our website. The items listed are bulk size. Most are also available in smaller packages such as 5 lb. and 1 lb. Contact your local Grabber Branch or Grabber Pro for more information.

Cabinet Screw PS1026 USA-ENG/Rev. 02-25

GRABBER CONSTRUCTION PRODUCTS, INC. 5255 W 11000 N., STE 100 HIGHLAND, UT 84003

(800) 477-8876 | GrabberPro.com

SAFETY FIRST: Wear appropriate personal protective equipment. Read applicable SDS and literature before handling and installation.

TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, Grabber Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. Grabber Construction Products reserves the right to modify this document without prior notice.

